

Han[®] Hv ES / Han[®] Hv E

Page

Technical characteristics Han Hv ES	04.10
Technical characteristics Han Hv E	04.11
Han 3 Hv ES	04.12
Han 3 Hv E	04.14
Han 6 Hv ES	04.16
Han 6 Hv E	04.18
Han 10 Hv ES	04.20
Han 10, 16 Hv E	04.22
Han 12 Hv ES / Hv E	04.24
Han 20 Hv ES / 20, 26, 32 Hv E	04.26
Difference: Han Hv E to Standard Hoods/Housings	04.28

Han
Hv E

Specifications

DIN VDE 0627
DIN VDE 0110

Approvals

, SEV

Inserts

Number of contacts	3, 6, 10, 12 (2 x 6), 20 (2 x 10) + PE + 2 additional contacts for safe high voltage connections 16 A max.
Working current (see current carrying capacity)	
Working voltage	750 V
- Relay contacts	400 V
Test voltage U_{rms}	3 kV
Insulation group	C
Insulation resistance	$\geq 10^{10} \Omega$
Material	Polycarbonate
Temperature range	- 40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- Mating cycles	≥ 500
Working voltage acc. to UL/CSA	600 V
- Relay contacts	250 V

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
Contact resistance	$\leq 3 \text{ m}\Omega$
Cage-clamp terminal	
- mm^2	0.14 - 2.5 mm^2
- AWG	26 - 14

Hoods/Housings

Material	die cast aluminium
Surface	powder-coated RAL 7037
Locking element	steel, zinc plated/Han-Easy Lock®
Hoods/Housings sealing	NBR
Temperature range	- 40 °C ... +125 °C
Degree of protection acc. to DIN 40 050 for coupled connector	IP 65
Further selection of hoods/housings	chapter 30



Accessories

Cable clamps	chapter 40
Coding of hoods/housings	chapter 40
Label acc. to CSA-approval	chapter 40
Han-Snap	chapter 11

Current carrying capacity

The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interrupted current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-3.



- ① Han 3 Hv ES
② Han 6 Hv ES
③ Han 10 Hv ES

Specifications

DIN VDE 0627
DIN VDE 0110

Approvals

SEV

Inserts

Number of contacts	3, 6, 10, 12 (2 x 6), 16, 20 (2 x 10), 26 (10 + 16), 32 (2 x 16) + PE + 2 additional contacts for safe high voltage connections
Working current (see current carrying capacity)	16 A max.
Working voltage	660 V
- Relay contacts	400 V
Test voltage U_{rms}	3 kV
Insulation group	C
Insulation resistance	$\geq 10^{10} \Omega$
Material	Polycarbonate
Temperature range	- 40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- Mating cycles	≥ 500
Working voltage acc. to UL/CSA	600 V
- Relay contacts	250 V

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm^2	0.5 - 4 mm^2
- AWG	20 - 12
Screw terminal	
- mm^2	2.5 mm^2
- AWG	14
- Tightening/test torque	0.5 Nm

Hoods/Housings

Material	die cast aluminium
Surface	powder-coated RAL 7037
Locking element	steel, zinc plated/Han-Easy Lock®
Hoods/Housings sealing	NBR
Temperature range	- 40 °C ... +125 °C
Degree of protection acc. to DIN 40 050 for coupled connector	IP 65



Accessories

Crimping tools	chapter 12
Cable clamps	chapter 40
Coding of Hoods/Housings	chapter 40
Label acc. to CSA-approval	chapter 40
Han-Snap	chapter 11

Current carrying capacity

The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interrupted current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-3.



- ① Han 3 Hv E
② Han 6 Hv E
③ Han 10 Hv E
Han 16 Hv E

For a fully equipped crimp connector the following contacts are required:

Type	Female contacts	Operating contacts	Relay contacts
Han 3 Hv E	5	3	2
Han 6 Hv E	8	6	2
Han 10 Hv E	12	10	2
Han 12 Hv E	16	12	4
Han 16 Hv E	18	18	—
Han 20 Hv E	24	20	4
Han 26 Hv E	30	28	2
Han 32 Hv E	36	36	—




Number of contacts

3 +

+ 2 additional contacts for safe high voltage connections

Inserts



Part No.


Identification Series Male insert (M) Female insert (F) Drawing Dimensions in mm

Cage-clamp terminal

Han
Hv ES

09 34 003 2616


09 34 003 2716



¹⁾ Distance for contacts max. 21 mm


Contact arrangement View from termination side

Han 3 Hv ES



- Operating contact
- ◐ Relay contact
- Without contact

Panel cut out for inserts
for use without hoods/housings




		Part No.		Pg	Drawing	Dimensions in mm
Identification		Low construction	High construction			
Hoods	Hoods side-entry	09 30 010 1521	09 30 010 0522 09 30 010 0523	16 21 29		
	Hoods top-entry	09 30 010 1421	09 30 010 0422 09 30 010 0423	16 21 29		
	Protection covers thermoplastic/metal	09 30 010 5401 09 30 010 5423				
	Housing bulkhead mounting	09 30 010 0301		—		
	Housings surface mounting 1 side-entry	09 30 010 1231	09 30 010 0232 09 30 010 0233	16 21 29		
	Housings surface mounting 2 side-entries	09 30 010 1271	09 30 010 0272 09 30 010 0273	16 21 29		Blind way for one cable entry
	Protection covers thermoplastic/metal	09 30 010 5407 09 30 010 5425				
	Hoods cable to cable	09 30 010 1731	09 30 010 0732 09 30 010 0733	16 21 29		
	Protection cover metal	09 30 010 5427				

Number of contacts

3 +

+ 2 additional contacts for safe high voltage connections

Inserts



		Part No.		Drawing	Dimensions in mm
Identification	Series	Male insert (M)	Female insert (F)		
Screw terminal 	Han Hv E	09 34 003 2601	09 34 003 2701	 ¹⁾ Distance for contact max. 21 mm Contact arrangement View from termination side Han 3 Hv E M F ● Operating contact ○ Relay contact ○ Without contact Panel cut out for inserts for use without hoods/housings 	
Crimp terminal Order crimp contacts separately 	Han Hv E	09 34 003 2602	09 34 003 2702		

		Wire gauge	Part No.		Drawing	Dimensions in mm																																
Identification		(mm²)	Male contacts	Female contacts																																		
Han 3 Hv E	Crimp contacts				Operating contact	Relay contact																																
					Identification																																	
3 x		0.5	09 33 000 6121	09 33 000 6220																																		
		0.75	09 33 000 6114	09 33 000 6214																																		
		1.0	09 33 000 6105	09 33 000 6205																																		
		1.5	09 33 000 6104	09 33 000 6204																																		
		2.5	09 33 000 6102	09 33 000 6202																																		
5 x		3	09 33 000 6106	09 33 000 6206																																		
		4	09 33 000 6107	09 33 000 6207																																		
2 x		0.75-1	09 33 000 6109																																			
		1.5	09 33 000 6110																																			
		2.5	09 33 000 6111																																			
Number of pieces per insert					Crimp contact identification																																	
					<table><tr><th>Identification</th><th colspan="2">Wire gauge</th><th>Stripping length</th></tr><tr><td>no groove</td><td>0.5 mm²</td><td>AWG 20</td><td>7.5 mm</td></tr><tr><td>1 groove*</td><td>0.75 mm²</td><td>AWG 18</td><td>7.5 mm</td></tr><tr><td>1 groove</td><td>1 mm²</td><td>AWG 18</td><td>7.5 mm</td></tr><tr><td>2 grooves</td><td>1.5 mm²</td><td>AWG 16</td><td>7.5 mm</td></tr><tr><td>3 grooves</td><td>2.5 mm²</td><td>AWG 14</td><td>7.5 mm</td></tr><tr><td>wide groove</td><td>3.0 mm²</td><td>AWG 12</td><td>7.5 mm</td></tr><tr><td>no groove</td><td>4 mm²</td><td>AWG 12</td><td>7.5 mm</td></tr></table>	Identification	Wire gauge		Stripping length	no groove	0.5 mm²	AWG 20	7.5 mm	1 groove*	0.75 mm²	AWG 18	7.5 mm	1 groove	1 mm²	AWG 18	7.5 mm	2 grooves	1.5 mm²	AWG 16	7.5 mm	3 grooves	2.5 mm²	AWG 14	7.5 mm	wide groove	3.0 mm²	AWG 12	7.5 mm	no groove	4 mm²	AWG 12	7.5 mm	
Identification	Wire gauge		Stripping length																																			
no groove	0.5 mm²	AWG 20	7.5 mm																																			
1 groove*	0.75 mm²	AWG 18	7.5 mm																																			
1 groove	1 mm²	AWG 18	7.5 mm																																			
2 grooves	1.5 mm²	AWG 16	7.5 mm																																			
3 grooves	2.5 mm²	AWG 14	7.5 mm																																			
wide groove	3.0 mm²	AWG 12	7.5 mm																																			
no groove	4 mm²	AWG 12	7.5 mm																																			
					* on the back crimp collar																																	

Stock items in bold type

Identification		Part No.	Pg	Drawing	Dimensions in mm
Hoods	Hood side-entry	09 34 003 0501	16		
	Hood top-entry	09 34 003 0401	16		
	Protection covers thermoplastic/metal	09 30 010 5401 09 30 010 5423			
Housings	Housing bulkhead mounting	09 34 003 0301	—	Panel cut out 60 x 35 mm 	
	Housing surface mounting 2 side-entries	09 34 003 0201	16		
	Protection covers thermoplastic/metal	09 30 010 5407 09 30 010 5425			
	Hood cable to cable	09 34 003 0701	16		
	Protection cover metal	09 30 010 5427			




Number of contacts

6 +

+ 2 additional contacts for safe high voltage connections

Inserts



Han
Hv E

Cage-clamp terminal

Han
Hv ES

Part No.

Identification

Series

Male insert (M)


Female insert (F)

Drawing

Dimensions in mm

09 34 006 2616


09 34 006 2716



¹⁾ Distance for contact max. 21 mm


Contact arrangement View from termination side

Han 6 Hv ES



- Operating contact
- Relay contact
- Without contact

Panel cut out for inserts
for use without hoods/housings




		Part No.										
Identification		Low construction	High construction	Pg	Drawing	Dimensions in mm						
Hoods	Hoods side-entry	09 30 016 1520		21								
			09 30 016 0520 09 30 016 0521	21 29								
	Hoods top-entry	09 30 016 1420		21								
			09 30 016 0420 09 30 016 0421	21 29								
	Protection covers thermoplastic/metal	09 30 016 5401										
		09 30 016 5422										
Housings	Housing bulkhead mounting	09 30 016 0301		—	Panel cut out 82 x 35 mm 							
	Housings surface mounting 1 side-entry	09 30 016 1230	09 30 016 0230 09 30 016 0231	21 29								
	2 side-entries	09 30 016 1270	09 30 016 0270 09 30 016 0271	21 29	Blind way for one cable entry <table border="1"><thead><tr><th></th><th>h</th></tr></thead><tbody><tr><td>Low construction</td><td>56</td></tr><tr><td>High construction</td><td>81</td></tr></tbody></table>		h	Low construction	56	High construction	81	
		h										
	Low construction	56										
	High construction	81										
Protection covers thermoplastic/metal	09 30 016 5405											
	09 30 016 5425											
Hoods cable to cable	09 30 016 1730	09 30 016 0730 09 30 016 0731	21 29		<table border="1"><thead><tr><th></th><th>h</th></tr></thead><tbody><tr><td>Low construction</td><td>47.5</td></tr><tr><td>High construction</td><td>78.5</td></tr></tbody></table>		h	Low construction	47.5	High construction	78.5	
	h											
Low construction	47.5											
High construction	78.5											
	Protection cover metal	09 30 016 5426										

Number of contacts

6 +

+ 2 additional contacts for safe high voltage connections

Inserts











		Part No.		Drawing	Dimension in mm
Identification	Series	Male insert (M)	Female insert (F)		
Screw terminal 	Han Hv E	09 34 006 2601	09 34 006 2701		
Crimp terminal Order crimp contacts separately 	Han Hv E	09 34 006 2602	09 34 006 2702	¹⁾ Distance for contact max. 21 mm Contact arrangement View from termination side Han 6 Hv E 	
				Panel cut out for inserts for use without hoods/housings 	

		Wire gauge	Part No.		Drawing	Dimensions in mm																															
Identification		(mm²)	Male contacts	Female contacts																																	
Han 6 Hv E	Crimp contacts				Operating contact	Relay contact																															
6 x	Operating contact silver plated	0.5 0.75 1.0 1.5 2.5	09 33 000 6121 09 33 000 6114 09 33 000 6105 09 33 000 6104 09 33 000 6102	09 33 000 6220 09 33 000 6214 09 33 000 6205 09 33 000 6204 09 33 000 6202																																	
	8 x		3 4	09 33 000 6106 09 33 000 6107			09 33 000 6206 09 33 000 6207																														
		Relay contact silver plated	0.75-1 1.5 2.5	09 33 000 6109 09 33 000 6110 09 33 000 6111																																	
			2 x																																		
Number of pieces per insert					Crimp contact identification																																
					<table><tr><th>Identification</th><th colspan="2">Wire gauge</th><th>Stripping length</th></tr><tr><td>no groove</td><td>0.5 mm²</td><td>AWG 20</td><td>7.5 mm</td></tr><tr><td>1 groove*</td><td>0.75 mm²</td><td>AWG 18</td><td>7.5 mm</td></tr><tr><td>1 groove</td><td>1 mm²</td><td>AWG 18</td><td>7.5 mm</td></tr><tr><td>2 grooves</td><td>1.5 mm²</td><td>AWG 16</td><td>7.5 mm</td></tr><tr><td>3 grooves</td><td>2.5 mm²</td><td>AWG 14</td><td>7.5 mm</td></tr><tr><td>wide groove</td><td>3.0 mm²</td><td>AWG 12</td><td>7.5 mm</td></tr><tr><td>no groove</td><td>4 mm²</td><td>AWG 12</td><td>7.5 mm</td></tr></table>	Identification	Wire gauge		Stripping length	no groove	0.5 mm²	AWG 20	7.5 mm	1 groove*	0.75 mm²	AWG 18	7.5 mm	1 groove	1 mm²	AWG 18	7.5 mm	2 grooves	1.5 mm²	AWG 16	7.5 mm	3 grooves	2.5 mm²	AWG 14	7.5 mm	wide groove	3.0 mm²	AWG 12	7.5 mm	no groove	4 mm²	AWG 12	7.5 mm
Identification	Wire gauge		Stripping length																																		
no groove	0.5 mm²	AWG 20	7.5 mm																																		
1 groove*	0.75 mm²	AWG 18	7.5 mm																																		
1 groove	1 mm²	AWG 18	7.5 mm																																		
2 grooves	1.5 mm²	AWG 16	7.5 mm																																		
3 grooves	2.5 mm²	AWG 14	7.5 mm																																		
wide groove	3.0 mm²	AWG 12	7.5 mm																																		
no groove	4 mm²	AWG 12	7.5 mm																																		
					* on the back crimp collar																																

* on the back crimp collar

Stock items in bold type

Identification		Part No.	Pg	Drawing	Dimensions in mm
Hoods	Hood side-entry 	09 34 006 0501	21		
	Hood top-entry 	09 34 006 0401	21		
	Protection covers thermoplastic/metal 	09 30 016 5401 09 30 016 5422			
Housings	Housing bulkhead mounting 	09 34 006 0301	—	Panel cut out 82 x 35 mm 	
	Housing surface mounting  2 side-entries	09 34 006 0201	21		
	Protection covers thermoplastic/metal 	09 30 016 5405 09 30 016 5425			
	Hood cable to cable 	09 34 006 0701	21		
	Protection cover metal 	09 30 016 5426			




Number of contacts

10 +

+ 2 additional contacts for safe high voltage connections

Inserts




		Part No.		Drawing	Dimensions in mm
Identification	Series	Male insert (M)	Female insert (F)		

Cage-clamp terminal

Han
Hv ES

09 34 010 2616


09 34 010 2716



¹⁾ Distance for contact max. 21 mm


Contact arrangement View from termination side

Han 10 Hv ES



- Operating contact
- Relay contact
- Without contact

Panel cut out for inserts
for use without hoods/housings



		Part No.		Pg	Drawing	Dimensions in mm
Identification		Low construction	High construction			
Hoods	Hoods side-entry	09 30 024 1520	09 30 024 0520 09 30 024 0521	21 21 29		
	Hoods top-entry	09 30 024 1421	09 30 024 0420 09 30 024 0421	29 21 29		
	Protection covers thermoplastic/metal	09 30 024 5401 09 30 024 5422				
	Housing bulkhead mounting	09 30 024 0301		—		
	Housings surface mounting 1 side-entry	09 30 024 1230	09 30 024 0230 09 30 024 0231	21 29		
	Housings surface mounting 2 side-entries	09 30 024 1270	09 30 024 0270 09 30 024 0271	21 29		
Housings	Protection covers thermoplastic/metal	09 30 024 5405 09 30 024 5425				
	Hoods cable to cable	09 30 024 1731	09 30 024 0730 09 30 024 0731	21 29		
	Protection cover metal	09 30 024 5426				


10, 16 + 




Part No.

Han
Hv E

Han
Hy E




09 34 010 2701



Contact arrangement view from termination side


Han
Hv E

Order crimp contacts separately



09 34 010 2702

Han
Hv E




09 34 016 2701

Han 16 Hv E

Figure 1 consists of four panels, each representing a different group: Males (M), Females (F), Males (M), and Females (F). Each panel shows a 12-item test. The items are arranged in two rows of six. The top row items are labeled 1 through 12, and the bottom row items are labeled 1 through 12. The items are represented by circles with different patterns of dots and lines. The panels are labeled M, F, M, F at the bottom.

- Operating contact
- ◐ Relay contact
- Without contact

Panel cut out
for inserts
for use without
hoods/housings



Han 10	Han 16
Hv E	Hv E

Wire gauge
(mm²)


Operating contact
silver plated



0.5
0.75
1.0
1.5
2.5
3
4

09 33 000 6121
09 33 000 6114
09 33 000 6105
09 33 000 6104
09 33 000 6102
09 33 000 6106
09 33 000 6107

09 33 000 6220
09 33 000 6214
09 33 000 6205
09 33 000 6204
09 33 000 6202
09 33 000 6206
09 33 000 6207




Relay contact
silver plated



0.75-1
1.5
2.5

09 33 000 6109
09 33 000 6110
 09 33 000 6111

Relay contact











Crimp contact identification

Identification	Wire gauge		Stripping length
no groove	0.5 mm ²	AWG 20	7.5 mm
1 groove*	0.75 mm ²	AWG 18	7.5 mm
1 groove	1 mm ²	AWG 18	7.5 mm
2 grooves	1.5 mm ²	AWG 16	7.5 mm
3 grooves	2.5 mm ²	AWG 14	7.5 mm
wide groove	3.0 mm ²	AWG 12	7.5 mm
no groove	4 mm ²	AWG 12	7.5 mm

* on the back crimp collar

Stock items in bold type

Identification		Part No.	Pg	Drawing	Dimensions in mm
Hoods	Hood side-entry	09 34 010 0501	21		
	Hood top-entry	09 34 010 0401	29		
	Protection covers thermoplastic/metal	09 30 024 5401 09 30 024 5422			
Housings	Housing bulkhead mounting	09 34 010 0301	—		
	Housing surface mounting 2 side-entries	09 34 010 0201	21		
	Protection covers thermoplastic/metal	09 30 024 5405 09 30 024 5425			
	Hood cable to cable	09 34 010 0701	29		
	Protection cover metal	09 30 024 5426			


Identification		Part No.	Pg	Drawing	Dimensions in mm
Hoods	Hoods side-entry		09 30 032 0521 09 30 032 0522 09 30 032 0523	29 36 42	
	Hoods top-entry		09 30 032 0421 09 30 032 0422 09 30 032 0423	29 36 42	
	Protection cover for hoods	09 30 032 5420	—		
Housings	Housing bulkhead mounting		09 30 032 0301	—	 Panel cut out
	Housings surface mounting		09 30 032 0231 09 30 032 0232 09 30 032 0233 09 30 032 0271 09 30 032 0272 09 30 032 0273	1 x 29 1 x 36 1 x 42 2 x 29 2 x 36 2 x 42	 Blind way for one cable entry
	Hoods cable to cable		09 30 032 0731 09 30 032 0732 09 30 032 0733	29 36 42	
	Protection covers	for housings	09 30 032 5425	—	
	for cable to cable hoods	09 30 032 5426 09 30 032 5427	42 36		







Number of contacts

20, 26, 32 +

+ 4 additional contacts for
safe high voltage connections




Inserts










		Part No.		Drawing	Dimensions in mm
Identification	Series	Male insert (M)	Female insert (F)		
Cage-clamp terminal	Han Hv ES			Dimensions for inserts page 04.20 / 04.22 Contact arrangement View from termination side Han 20 Hv ES	
	1-10 1-10	09 34 010 2616 09 34 010 2616	09 34 010 2716 09 34 010 2716		
Screw terminal	Han Hv E			Han 20 Hv E	
	1-10 1-10 1-10 1-16 1-16 1-16	09 34 010 2601 09 34 010 2601 09 34 010 2601 09 34 016 2601 09 34 016 2601 09 34 016 2601	09 34 010 2701 09 34 010 2701 09 34 010 2701 09 34 016 2701 09 34 016 2701 09 34 016 2701		
Crimp terminal Order crimp contacts separately	Han Hv E			Han 26 Hv E	
	1-10 1-10	09 34 010 2602 09 34 010 2602	09 34 010 2702 09 34 010 2702		
				Han 32 Hv E	
					
				● Operating contact ◐ Relay contact ○ Without contact	
				Panel cut out for inserts for use without hoods/housings see chapter 03 size 48 E.	

- Operating contact
- Relay contact
- Without contact

Panel cut out for inserts for use without
hoods/housings see chapter 03 size 48 E.


				Wire gauge	Part No.																																			
Identification				(mm²)	Male contacts	Female contacts	Drawing	Dimensions in mm																																
Crimp contacts																																								
Han 20 Hv E	Han 26 Hv E	Han 32 Hv E	Operating contact silver plated	0.5	09 33 000 6121	09 33 000 6220																																		
20 x	28 x	36 x		0.75	09 33 000 6114	09 33 000 6214																																		
				1.0	09 33 000 6105	09 33 000 6205																																		
				1.5	09 33 000 6104	09 33 000 6204																																		
				2.5	09 33 000 6102	09 33 000 6202																																		
24 x	30 x	36 x	Relay contact silver plated	3	09 33 000 6106	09 33 000 6206																																		
				4	09 33 000 6107	09 33 000 6207																																		
				0.75-1	09 33 000 6109																																			
				1.5	09 33 000 6110																																			
				2.5	09 33 000 6111																																			
4 x	2 x	—																																						
Number of pieces per assembly																																								
							Crimp contact identification																																	
							<table><tr><th>Identification</th><th colspan="2">Wire gauge</th><th>Stripping length</th></tr><tr><td>no groove</td><td>0.5 mm²</td><td>AWG 20</td><td>7.5 mm</td></tr><tr><td>1 groove*</td><td>0.75 mm²</td><td>AWG 18</td><td>7.5 mm</td></tr><tr><td>1 groove</td><td>1 mm²</td><td>AWG 18</td><td>7.5 mm</td></tr><tr><td>2 grooves</td><td>1.5 mm²</td><td>AWG 16</td><td>7.5 mm</td></tr><tr><td>3 grooves</td><td>2.5 mm²</td><td>AWG 14</td><td>7.5 mm</td></tr><tr><td>wide groove</td><td>3.0 mm²</td><td>AWG 12</td><td>7.5 mm</td></tr><tr><td>no groove</td><td>4 mm²</td><td>AWG 12</td><td>7.5 mm</td></tr></table>		Identification	Wire gauge		Stripping length	no groove	0.5 mm²	AWG 20	7.5 mm	1 groove*	0.75 mm²	AWG 18	7.5 mm	1 groove	1 mm²	AWG 18	7.5 mm	2 grooves	1.5 mm²	AWG 16	7.5 mm	3 grooves	2.5 mm²	AWG 14	7.5 mm	wide groove	3.0 mm²	AWG 12	7.5 mm	no groove	4 mm²	AWG 12	7.5 mm
Identification	Wire gauge		Stripping length																																					
no groove	0.5 mm²	AWG 20	7.5 mm																																					
1 groove*	0.75 mm²	AWG 18	7.5 mm																																					
1 groove	1 mm²	AWG 18	7.5 mm																																					
2 grooves	1.5 mm²	AWG 16	7.5 mm																																					
3 grooves	2.5 mm²	AWG 14	7.5 mm																																					
wide groove	3.0 mm²	AWG 12	7.5 mm																																					
no groove	4 mm²	AWG 12	7.5 mm																																					
							* on the back crimp collar																																	

Identification	Part No.	Pg	Drawing	Dimensions in mm
Hoods	Hoods side-entry			
	 09 30 048 0540 09 30 048 0541 09 30 048 0542	29 36 42		
Hoods	Hoods top-entry			
	 09 30 048 0440 09 30 048 0441 09 30 048 0442	29 36 42		
Housings	Housings bulkhead mounting			
	with thermo- plastic cover 09 30 048 0301 with metal cover 09 30 048 0317	— —	  Panel cut out 	
Housings	Housings surface mounting	2 side-entries		
	 09 30 048 0290 09 30 048 0291 with thermo- plastic cover 09 30 048 0295 09 30 048 0296 with metal cover 09 30 048 2295 09 30 048 2296	29 36 29 36 29 36	  ¹⁾ Blind way	

Standard Hood/Housing Han B

Suitable for all Standard inserts (also Hv ES)

Coding bar




Special Hood/Housing Han Hv E

Han Hv E inserts may be used together with the corresponding Hv E hoods/housings only

Milled Coding bar

Stop



Insulation tape