


Contents

	Page
Description of the Han-Modular® system	06.03
Summary Han-Modular®	06.04
Han-Modular® Compact	06.08
Han-Modular® Twin	06.12
Han-Modular® Hinged frames	06.14
Han-Modular® Docking frames	06.16
Han-Modular® ECO	06.20
Han® 200 A Axial module	06.24
Han® 200 A Crimp module	06.26
Han® 100 A Axial module	06.28
Han® 100 A Crimp module	06.30
Han® 100 A Single module	06.32
Han® 70 A Axial module	06.34
Han® 70 A Crimp module	06.36
Han® 70 A Hybrid module	06.38
Han® 40 A Axial module	06.40
Han® 40 A Crimp module	06.42
Han® C Axial module	06.44
Han® C module	06.46
Han® CC Protected module	06.48
Han® CD module	06.50
Han E® module	06.52
Han® E Quick Lock module	06.54
Han® EE module	06.56
Han® EE Quick Lock module	06.58
Han E® Protected module	06.60
Han® EEE module	06.62
Han® ES module	06.64

Contents

	Page
Han® HV Single module	06.66
Han® HV module	06.68
Han DD® module	06.72
Han DD® Quick Lock module	06.74
Han® DDD module	06.76
Han® High Density module	06.78
Han® D-Sub module	06.80
Han® USB module	06.82
Han® FireWire module	06.84
Han® RJ45 module	06.86
Han® GigaBit module	06.92
Han® MegaBit module	06.94
Han® Shielded module	06.96
Han-Quintax® module	06.100
Han® Coax module	06.102
Han® Multi module according to DIN 41 626	06.104
Han® Multi module according to D-Sub	06.106
Han® Multi module	06.108
Han® Pneumatic module	06.110
Han® SC module	06.114
Han-Elisa®	06.116
Han-Elisa® Pt100 module	06.118
Han-Elisa® Output module	06.120
Han-Elisa® ID module	06.122
Han-Modular® Accessories	06.124

Description of the Han-Modular® system



The Han-Modular® series is a new system of inserts designed to meet the specific requirements of individual customers. In close cooperation with potential users a range of modular inserts have been developed allowing the simple assembly of custom designed complete connectors which meet the diverse requirements encountered by designers today.

Han-Modular® is a logical development of the Han-Com® series which already offers the combination of power and signal circuits in one connector.

The individual modules of this series now allow the integration of electrical, optical and gaseous signal and power connections in one connector assembly.

The pneumatic contacts are also suitable for the connection of liquid media. However it must be stated that a combination of electrical and liquid connections in one connector is not allowed according to VDE regulations.


The individual contacts used in this system are all from existing well proven ranges and it is possible to use combinations of 1 to 12 modules depending on the size of the hoods and housings chosen.

The basic modules snap into a mounting frame and can be exchanged separately at any time.

Advantages:

- Custom designs can be simply assembled
- Optimum solutions can be reached
- Stock can be minimized

Assembly details



Han-Modular® Compact



Page 06.08

Han-Modular® Twin



Page 06.12

Han-Modular® Hinged frames in Han® B hoods and housings



Page 06.14

Han-Modular® Docking frame



Page 06.16

Han-Modular® ECO



Page 06.20

Summary Han-Modular®



Series	Han® 200 A Axial module	Han® 200 A Crimp module	Han® 100 A Axial module	Han® 100 A Crimp module
Number of contacts	1	1	2	2
Modules	Axial screw terminal 	Crimp terminal 	Axial screw terminal 	Crimp terminal 
Rated current	200 A	200 A	100 A	100 A
Rated voltage	1000 V	1000 V	1000 V	1000 V
Wire gauge	25 ... 70 mm ²	25 ... 70 mm ²	10 ... 38 mm ²	10 ... 35 mm ²
Page	06.24	06.26	06.28	06.30

Series	Han® 100 A Single module	Han® 70 A Axial module	Han® 70 A Crimp module	Han® 70 A Hybrid module
Number of contacts	1	2	2	1 / 4
Modules	Axial screw terminal 	Axial screw terminal 	Crimp terminal 	Axial screw terminal 
Rated current	100 A	70 A	70 A	70 A / 16 A
Rated voltage	830 V	1000 V	1000 V	1000 V / 400 V
Wire gauge	10 ... 35 mm ²	6 ... 22 mm ²	10 ... 25 mm ²	6 ... 22 mm ² / 0.14 ... 4 mm ²
Page	06.32	06.34	06.36	06.38

Series	Han® 40 A Axial module	Han® 40 A Crimp module	Han® C Axial module	Han® C module
Number of contacts	2	2	3	3
Modules	Axial screw terminal 	Crimp terminal 	Axial screw terminal 	Crimp terminal 
Rated current	40 A	40 A	40 A	40 A
Rated voltage	1000 V	1000 V	690 V	690 V
Wire gauge	2.5 ... 10 mm ²	1.5 ... 10 mm ²	2.5 ... 10 mm ²	1.5 ... 10 mm ²
Page	06.40	06.42	06.44	06.46

Series	Han® CC Protected module	Han® CD module	Han E® module	Han® E Quick Lock module
Number of contacts		3 / 4	6	6
Modules	Crimp terminal 	Crimp terminal 	Crimp terminal 	Quick Lock terminal 
Rated current	40 A	40 A / 10 A	16 A	16 A
Rated voltage	830 V	830 V / 830 V	500 V	500 V
Wire gauge	1.5 ... 6 mm ²	1.5 ... 6 mm ² / 0.14 ... 2.5 mm ²	0.14 ... 4 mm ²	0.5 ... 2.5 mm ²
Page	06.48	06.50	06.52	06.54

Summary Han-Modular®



Series	Han® EE module	Han® EE Quick Lock module	Han E® Protected module	Han® EEE module
Number of contacts	8	8		
Modules	Crimp terminal	Quick Lock terminal	Crimp terminal	Crimp terminal
Rated current	16 A	16 A	16 A	16 A
Rated voltage	400 V	400 V	830 V	500 V
Wire gauge	0.14 ... 4 mm ²	0.5 ... 2.5 mm ²	0.14 ... 4 mm ²	0.14 ... 4 mm ²
Page	06.56	06.58	06.60	06.62
Han Modular	Series	Han® ES module	Han® HV Single module	Han® HV module
Number of contacts	5	2	2	2
Modules	Cage-clamp terminal	Crimp terminal	Crimp terminal	Crimp terminal
Rated current	16 A	16 A	16 A	40 A
Rated voltage	400 V	2500 V	2900 / 5000 V	2900 / 5000 V
Wire gauge	0.14 ... 2.5 mm ²	0.5 ... 4 mm ²	0.5 ... 4 mm ²	1.5 ... 10 mm ²
Page	06.64	06.66	06.68	06.70
Series	Han DD® module	Han DD® Quick Lock module	Han® DDD module	Han® High Density module
Number of contacts	12	12	17	25
Modules	Crimp terminal	Quick Lock terminal	Crimp terminal	Crimp terminal
Rated current	10 A	10 A	10 A	4 A
Rated voltage	250 V	250 V	160 V	50 V
Wire gauge	0.14 ... 2.5 mm ²	0.25 ... 1.5 mm ²	0.14 ... 2.5 mm ²	0.08 ... 0.52 mm ²
Page	06.72	06.74	06.76	06.78
Series	Han® D-Sub module		Han® USB module	Han® FireWire module
Number of contacts	9		4	6
Modules	Crimp terminal		USB 2.0	IEEE 1394
Rated current	5 A			
Rated voltage	50 V			
Wire gauge	0.08 ... 0.52 mm ²			
Page	06.80		06.82	06.84

Summary Han-Modular®



Series	Han® RJ45 module	Han® GigaBit module	Han® MegaBit module	Han® Shielded module
Number of contacts	8	8	2 x 4	20
Modules	Ethernet Cat. 6	Ethernet Cat. 6A	Ethernet Cat. 5e	Crimp terminal
Page	06.86	06.92	06.94	06.96
Series	Han-Quintax® module			
Number of contacts	2			
Modules				
Page	06.100	06.102	75 Ω	50 Ω
Contacts	Han-Quintax® contact 4 + shielding 	High Density Quintax contact 8 + shielding 	Han D® Coax contact 1 + shielding 	Han E® Coax contact 1 + shielding
Series	Han® Multi module			
Number of contacts	4		12	
Modules				
Page	06.104	06.106	06.108	06.108
Contacts	FOC contacts 	Coaxial contacts 	FOC contacts 	Coaxial contacts
	Multimode F.O. HCS®* / PCF F.O. 1 mm POF	50 Ω RG 174 75 Ω RG 179 50 Ω RG 58	Multimode F.O. HCS®* / PCF F.O. 1 mm POF	50 Ω RG 174 75 Ω RG 179
Series	Han® Pneumatic module	Han® SC module	Han-Elisa®	Dummy module
Number of contacts	2	3	4	
Modules				
Page	06.110	06.112	06.114	06.116
Contacts	Ø 6.0 mm Ø 1.6 mm Ø 3.0 mm Ø 4.0 mm	SC contact for GI 50; 62.5 / 125 µm		Temperature I/O modules ID module
	06.124			

* HCS® = Hard Clad Silica (is registered trade mark of the SpecTran Corporation)

Features

- Compact design saves space
- Modular structure increases flexibility
- Simple and quick assembly
- Robust design
- Two part grommet housing

Technical characteristics

Hoods/Housings

Material	zinc die-cast
Surface	nickel plated
Locking element	stainless steel
Hoods/Housings sealing	NBR
Limiting temperatures	-40 °C ... +125 °C
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65
Mechanical working life - mating cycles	500
PE contact	
wire gauge	10 mm ² / AWG 8
Stripping length	10 mm
Tightening tourque	1 Nm


Protection covers for housings, bulkhead mounting

Material	Polyamide
Locking element	Polyamide
Hoods/Housings sealing	NBR
Limiting temperatures	-40 °C ... +125 °C
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65
Flammability acc. to UL 94	V 0

Current carrying capacity


The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① Han® 40 A Axial module, wire gauge: 10 mm²

② Han® C module, wire gauge: 6 mm²



① Hood with side entry

② Thread M25

③ Bulkhead mounted housing with locking lever


④ Carrier hood

Identification	Part number	Drawing	Dimensions in mm
Hoods side entry M25	19 14 001 0501	4 screws are included in the delivery range	
Hoods top entry M25	19 14 001 0401	4 screws are included in the delivery range	
Hoods top entry M32	19 14 001 0402	4 screws are included in the delivery range	
Carrier hood	09 14 001 0311		
Protection covers	09 14 001 5402		
Housings, bulkhead mounting	09 14 001 0301	Panel cut out	
Protection covers for housings, bulkhead mounting	09 14 001 5401		



Coding pins

Identification	Part number	Drawing	Dimensions in mm
Coding pin 1 (red)	09 14 000 9971	16 Coding options	
Coding pin 2 (blue)	09 14 000 9972		
Coding pin 3 (black)	0914 000 9973	Example for coding option IV	
Coding pin 4 (yellow)	09 14 000 9974	Remark Coding pins can be retro fitted from the front.	

Identification	Part number	Drawing	Dimensions in mm
Fixing bracket for Han-Modular® Compact 	09 14 000 9947	 1 Panel cut out	

Han
Modular06
11


Features

- Compact and space saving
- High degree of flexibility due to modular assembly
- Easy and quick assembly
- Robust design
- Hood consists of two parts

Technical characteristics

Hoods/Housings

Material	aluminium die-cast
Surface	powder-coated
Locking element	Han-Easy Lock®
Material	
Panel feed through housing /	
Shielding frame	zinc die-cast
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... +125 °C
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65
Mechanical working life - mating cycles	≥ 500
PE contact	
wire gauge	10 mm² / AWG 8
Stripping length	10 mm
Tightening torque	1 Nm



- ① Hood with top entry
- ② Carrier hood
- ③ Bulkhead mounted housing with locking lever
- ④ Switch board panel
- ⑤ Panel feed through housing
- ⑥ Thread M32



Identification	Part number	Drawing	Dimensions in mm
Hoods top entry M32	19 14 002 0402		
Shielding frame	09 14 000 9924		
Carrier hood	09 14 002 0311		
Housings, bulkhead mounting	09 14 002 0301		
Panel feed through housings	09 14 000 9928		

Stock items in bold type

Features

- Pre-leading grounding system according VDE
- Modules can only be assembled polarized to guarantee a correct orientation
- Alphabetical marking of module position
- High mechanical reliability of modules in case of vibration and impact stress
- No tools necessary to remove modules

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
<hr/>	
Hinged frames	
Number of modules	2, 3, 4, 6
PE contact	
Wire gauge	
- Power side *	4 ... 10 mm ² AWG 12 ... 8
- Signal side	1 ... 2.5 mm ² AWG 18 ... 14
Material	zinc die-cast
Limiting temperatures	-40 °C ... +125 °C
Mechanical working life	
- mating cycles	≥ 500

Hoods/Housings

Selection of hoods/housings	see chapter 31
Material	aluminium die-cast
Surface	powder-coated RAL 7037
Locking element	Han-Easy Lock®
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... +125 °C
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65

Accessories

Coding of hoods/housings	chapter 95
--------------------------	------------



Identification	Size	Part number for Hood/Housing 2) Marking A ... F	Marking a ... f	Drawing	Dimensions in mm																				
Hinged frame for 2 modules	6 B	09 14 006 0303	09 14 006 0313	Hoods 	Housings 																				
Hinged frame for 3 modules	10 B	09 14 010 0303	09 14 010 0313																						
Hinged frame for 4 modules	16 B	09 14 016 0303	09 14 016 0313																						
Hinged frame for 6 modules	24 B	09 14 024 0303	09 14 024 0313																						
				Panel cut out 	<table border="1"> <thead> <tr> <th>Size</th><th>A</th><th>B</th><th>C</th></tr> </thead> <tbody> <tr> <td>6 B</td><td>35</td><td>44</td><td>52</td></tr> <tr> <td>10 B</td><td>49</td><td>57</td><td>66</td></tr> <tr> <td>16 B</td><td>64</td><td>77.5</td><td>85.5</td></tr> <tr> <td>24 B</td><td>94</td><td>104</td><td>112</td></tr> </tbody> </table>	Size	A	B	C	6 B	35	44	52	10 B	49	57	66	16 B	64	77.5	85.5	24 B	94	104	112
Size	A	B	C																						
6 B	35	44	52																						
10 B	49	57	66																						
16 B	64	77.5	85.5																						
24 B	94	104	112																						
Locking element for hinged frames (20 pieces per bloc)		09 14 000 9960	09 14 000 9960																						

1) Distance max. 20.5 mm

2) Hinged frames can be used either in hood or housing
Both different markings must be used for one connector!

Features

- Blind mating connector system for drawer systems
- Direct panel mounting without housing
- Very robust design
- Solid pre-leading guid pins and float bushes
- Can be fixed with standard M4 screws

Notice:

Due the plastic material used in the docking frame without PE, the panel will need to be grounded separately

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Docking frames

Number of modules	2, 3, 4, 6
Material	polycarbonate
- Docking frames	zinc die-cast
- Float washer	
Floating tolerance	± 2 mm
Aligning tolerance	± 4 mm
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500



Identification	Part number Marking A ... F	Part number Marking a ... f	Drawing	Dimensions in mm
Docking frame for 2 modules float mount	09 14 006 1701			<p>① floating tolerance ± 2 mm</p> <p>Panel cut out</p>
Docking frame for 2 modules fixed		09 14 006 1711		<p>Panel cut out</p>
Docking frame for 3 modules float mount		09 14 010 1701		<p>① floating tolerance ± 2 mm</p> <p>Panel cut out</p>
Docking frame for 3 modules fixed		09 14 010 1711		<p>① floating tolerance ± 2 mm</p> <p>Panel cut out</p>

Han
Modular


Han-Modular® Docking frame



Identification	Part number Marking A ... F	Marking a ... f	Drawing	Dimensions in mm
Docking frame for 4 modules float mount	09 14 016 1701			
Docking frame for 4 modules fixed		09 14 016 1711		
Docking frame for 6 modules float mount		09 14 024 1701		
Docking frame for 6 modules fixed		09 14 024 1711		

Panel cut out

Panel cut out

Identification	Part number	Drawing	Dimensions in mm
Float washer to enable the frame to be float mounted using standard M4 fixing screws	09 14 000 9936		
Removal tool for modules			
Thermoplastic	09 99 000 0331		
Metal	09 99 000 0828		

Features

- Suitable for all Han-Modular® single modules
- The variant with PE connection uses pin 1 of the module as PE
- Slim, space saving design
- Low cost plastic hoods and housings

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Hoods/Housings

Material

- Hoods/Housings	polycarbonate
- Seal	NBR
- Cable gland	Polyamide

Limiting temperatures

-40 °C ... +85 °C

Flammability acc. to UL 94

V 0


Degree of protection acc. to DIN EN 60 529

IP 20 / IP 65

Mechanical working life

- mating cycles ≥ 500

Plastic hoods/housings
with PE marking



Identification	Part number	Drawing	Dimensions in mm
Hoods with PE marking (pin 1 = PE) IP 65 top entry	09 14 001 0421		Han Modular
Hoods with PE marking (pin 1 = PE) IP 20 top entry	09 14 001 0423		
Housing, bulkhead mounting with PE marking (pin 1 = PE) IP 20 / IP 65	09 14 001 0321		Panel cut out
Cable to cable hoods with PE marking (Pin 1 = PE) top entry IP 20	09 14 001 0721		
IP 65	09 14 001 0723		
Coding pin	09 14 000 9929		Range of delivery: 8 pieces per frame

Plastic hoods/housings
without PE



Identification	Part number	Drawing	Dimensions in mm
Hoods without PE IP 65 top entry	09 14 001 0420		
Hoods without PE IP 20 top entry	09 14 001 0422		
Housing, bulkhead mounting without PE IP 20 / IP 65	09 14 001 0320		Panel cut out
Cable to cable hoods without PE top entry IP 20	09 14 001 0720		
IP 65	09 14 001 0722		
Coding pin	09 14 000 9929		Range of delivery: 8 pieces per frame

Features


- Axial-screw termination
- No special tools required
- Power module for big wire gauge up to 70 mm²
- Suitable as a 3 + PE connector in a Han® 32 B housing
- Compatible to the Han® 200 A module with crimp terminal

Han
Modular

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 3 modules; wire gauge: 50 mm²

② 24 B hoods/housings with 3 modules; wire gauge: 70 mm²

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts


Number of contacts	1
Electrical data	
acc. to EN 61 984	200 A 1000 V 8 kV 3
Rated current	200 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	0.2 mΩ
Screw terminal	
- Wire gauge ¹⁾	25 ... 70 mm ²
- AWG	2 ... 00
- Hexagonal driver	SW 5
- Stripping length	16 mm
- Tightening torque	
mm ²	25 35 50 70
Nm	8 8 9 10

Number of contacts

1

Identification	Part number	Drawing	Dimensions in mm
Axial screw terminal 200 A	Male insert (M) 09 14 001 2663 Female insert (F) 09 14 001 2763	M F 	Dimensions in mm
25 ... 40 mm ²			
40 ... 70 mm ²	09 14 001 2662 09 14 001 2762		
Axial screw terminal 200 A PE (Ground)	Male insert (M) 09 14 001 2668 Female insert (F) 09 14 001 2768	M F 	Dimensions in mm
25 ... 40 mm ²			
40 ... 70 mm ²	09 14 001 2667 09 14 001 2767		
Identification	Part number	Drawing	Dimensions in mm
Hex key SW 5 for axial setscrew			
with grip	09 99 000 0364		
adapter 3/8"	09 99 000 0371		

Features

- Crimp termination
- Contacts can be unlocked from the mating side
- Compatible with Han® 200 A modules with axial screw terminal

Technical characteristics

Specifications

EN 50 124-1
DIN EN 60 664-1
DIN EN 61 984

Inserts

Number of contacts	1
Electrical data	
acc. to EN 61 984	200 A 1000 V 8 kV 3
Rated current	200 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Crimp terminal	
- mm²	25 ... 70 mm²
Max. insulation diameter	18 mm

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 3 modules; wire gauge: 50 mm²

② 24 B hoods/housings with 3 modules; wire gauge: 70 mm²

Number of contacts

1

Identification	Part number		Drawing	Dimensions in mm		
	Male insert (M)	Female insert (F)				
Crimp terminal Modul	09 14 001 3001	09 14 001 3101				
Removal tool for TC contacts in 200 A crimp module	09 99 000 0820	09 99 000 0820				
Identification	Wire gauge (mm ²)	Part number	Drawing	Dimensions in mm		
Crimp contacts* silver plated	25	Male contact				
		09 11 000 6120				
		09 11 000 6121				
		09 11 000 6122				
	35	Female contact				
		09 11 000 6220				
		09 11 000 6221				
		09 11 000 6222				
	50	Male contact				
		09 11 000 6123				
		09 11 000 6223				
		Female contact				
	70	Male contact				
		09 11 000 6124				
		09 11 000 6224				
		Female contact				
Wire gauge		Ø	Stripping length A			
25 mm ²		7	19 mm			
35 mm ²		8.2	20 mm			
50 mm ²		10	22.5 mm			
70 mm ²		11.5	22.5 mm			
for stranded wire according to IEC 60 228 Class 5						

* Crimp zone acc. to DIN EN 46 235


Features

- Axial-screw termination
- No special tools required
- Connect PE contact with special cable shoe
- Compatible to the Han® 100 A module with crimp terminal

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



Ambient temperature

① 24 B hoods/housings with 3 modules; wire gauge: 35 mm²

② 24 B hoods/housings with 3 modules; wire gauge: 25 mm²

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	2
Electrical data	
acc. to EN 61 984	100 A 1000 V 8 kV 3
Rated current	100 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3


Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	0.3 mΩ
Screw terminal	
- Wire gauge ¹⁾	10 ... 38 mm ²
- AWG	6 ... 2
- Hexagonal driver	SW 4
- Stripping length	13 mm
- Tightening torque	
mm ²	10 16 25 35
Nm	6 6 7 8

Number of contacts

2



Identification	Part number Male insert (M)	Part number Female insert (F)	Drawing	Dimensions in mm
Axial screw terminal 100 A				
10 ... 25 mm ²	09 14 002 2653	09 14 002 2753	M	
16 ... 35 mm ²	09 14 002 2651	09 14 002 2751	F	
38 mm ²	09 14 002 2650	09 14 002 2750		

Han
Modular

Identification	Part number	Drawing	Dimensions in mm
Hex key SW 4 for axial setscrew			
with grip	09 99 000 0363		
adapter 3/8"	09 99 000 0370		
Cable shoe 16 mm ² for PE extension	09 14 000 9912		
Comment for hoods/ housings high construction only			Please use pressing tools for non-insulated cable shoes fol- lowing DIN 46 230 with 16 mm ² range (eg. K25, co. Klauke)

Features

- Crimp termination
- Unlock of contacts from mating side
- Connect PE contact with special cable shoe
- Compatible to Han® 100 A module with axial screw terminal

Han
Modular

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts


Number of contacts	2
Electrical data acc. to EN 61 984	100 A 1000 V 8 kV 3
Rated current	100 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Crimp terminal	
- mm ²	10 ... 35 mm ²
Max. cable diameter	14 mm

Crimp zone (C)



09 11 000 6114

09 11 000 6116


09 11 000 6125

09 11 000 6135

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 3 modules; wire gauge: 16 mm²

② 24 B hoods/housings with 3 modules; wire gauge: 25 mm²

③ 24 B hoods/housings with 3 modules; wire gauge: 35 mm²

Number of contacts

2

Identification	Part number		Drawing	Dimensions in mm	
	Male insert (M)	Female insert (F)			
Crimp terminal Modul	09 14 002 3051	09 14 002 3151			
Removal tool for TC contacts in 100 A crimp module	09 99 000 0383	09 99 000 0383			
Identification	Wire gauge (mm²)	Part number	Drawing	Dimensions in mm	
Crimp contacts* silver plated	10	Male contact	Female contact		
		09 11 000 6114	09 11 000 6214		
		09 11 000 6116	09 11 000 6216		
		09 11 000 6125	09 11 000 6225		
		09 11 000 6135	09 11 000 6235		
Wire gauge		Ø	Stripping length (A)		
10 mm²		4.3	19 mm		
16 mm²		5.5	19 mm		
25 mm²		7.0	19 mm		
35 mm²		8.2	16 mm		
for stranded wire acc. to IEC 60 228 Class 5					

* Crimp zone acc. to DIN EN 46 235

Features

- Crimp or axial screw termination available
- Unlock the contacts from mating side with a screw driver or removal tool
- Separate axial screw contacts can be terminated without any special tools directly to the wire

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Inserts

Number of contacts	1
Electrical data acc. to EN 61 984	100 A 830 V 8 kV 3
Rated current	100 A
Rated voltage	830 V
Rated impulse voltage	8 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500
Max. insulation diameter	13 mm

Crimp Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Crimp terminal - wire gauge	10 ... 35 mm²

Axial Screw Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Screw terminal - wire gauge ¹⁾	10 ... 35 mm²
- AWG	6 ... 2
- hexagonal driver	SW 4
- tightening torque	
mm²	10
Nm	6
mm²	16
Nm	6
mm²	25
Nm	7
mm²	35
Nm	8

1) geometric wire gauge

Number of contacts

1



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
100 A single module order contacts separately	09 14 001 3031	09 14 001 3131		M F
Removal tool for TC contacts in 100 A single module	09 99 000 0827	09 99 000 0827		view termination side

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm															
		Male contact	Female contact																	
Contacts axial screw terminal	10-25 16-35	09 11 000 6112 09 11 000 6113	09 11 000 6212 09 11 000 6213																	
crimp terminal*	10	09 11 000 6114	09 11 000 6214																	
	16	09 11 000 6116	09 11 000 6216																	
	25	09 11 000 6125	09 11 000 6225																	
	35	09 11 000 6135	09 11 000 6235																	
<table border="1"> <thead> <tr> <th>Wire gauge</th> <th>Ø</th> <th>Stripping length (A)</th> </tr> </thead> <tbody> <tr> <td>10 mm²</td> <td>4.3</td> <td>19 mm</td> </tr> <tr> <td>16 mm²</td> <td>5.5</td> <td>19 mm</td> </tr> <tr> <td>25 mm²</td> <td>7.0</td> <td>19 mm</td> </tr> <tr> <td>35 mm²</td> <td>8.2</td> <td>16 mm</td> </tr> </tbody> </table> <p>for stranded wire acc. to IEC 60 228 Class 5</p>						Wire gauge	Ø	Stripping length (A)	10 mm²	4.3	19 mm	16 mm²	5.5	19 mm	25 mm²	7.0	19 mm	35 mm²	8.2	16 mm
Wire gauge	Ø	Stripping length (A)																		
10 mm²	4.3	19 mm																		
16 mm²	5.5	19 mm																		
25 mm²	7.0	19 mm																		
35 mm²	8.2	16 mm																		

* Crimp zone acc. to DIN EN 46 235

Stock items in bold type


Features

- Axial-screw termination
- 2 contacts (70 A) for power circuits
- Male inserts with protection collar
- Male and female contacts are finger safe
- Compatible to Han® 70 A module with crimp terminal

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



Ambient temperature

① 24 B hoods/housings with 6 modules; wire gauge: 6 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 16 mm²

③ 24 B hoods/housings with 6 modules; wire gauge: 22 mm²

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	2
Electrical data	
acc. to EN 61 984	70 A 1000 V 8 kV 3
Rated current	70 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500

Contacts

Material copper alloy

Surface - hard-silver plated
3 µm Ag
0.5 mΩ

Contact resistance
Screw terminal
- Wire gauge¹⁾
- AWG
- Hexagonal driver
- Stripping length

mm ²	6	10	16	22
mm	11 ⁺¹	11 ⁺¹	11 ⁺¹	12.5 ⁺¹

- Tightening tourque

mm ²	6	10	16	22
Nm	2	3	4	4

Number of contacts

2

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Axial screw terminal 70 A				
6 ... 16 mm ²	09 14 002 2646	09 14 002 2741		
14 ... 22 mm ²	09 14 002 2647	09 14 002 2742		
Axial screw terminal 70 A with finger protected male contacts				
6 ... 16 mm ²	09 14 002 2641			
14 ... 22 mm ²	09 14 002 2642			

Identification	Part number	Drawing	Dimensions in mm
Hex key SW 2.5 for axial setscrew			
Bit 1/4"	09 99 000 0375		

Features

- Crimp termination
- Compatible with Han® 70 A module with axial screw termination
- Contacts are removed without tools


Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Inserts	
Number of contacts	2
Electrical data acc. to DIN EN 61 984	70 A 1000 V 8 kV 3
Rated current	70 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Material	Polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	≥ 500 mating cycles
Contacts	
Power contacts	
Material	Copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.5 \text{ m}\Omega$
Crimp terminal	
- wire gauge	10 - 25 mm²
Max. insulation diameter	11 mm
Stripping length	15.5 mm

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 16 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 25 mm²

Number of contacts

2



Identification	Part-Number		Drawings	Dimensions in mm
	Male insert (M)	Female insert (F)		
Han® 70 A module Crimp terminal	09 14 002 3041	09 14 002 3141	M F 	View termination side

Identification	Wire gauge mm²	Part-Number		Drawings	Dimensions in mm
		Male contacts (M)	Female contacts (F)		
Crimp contacts* Silver plated	10 16 25	09 11 000 6131 09 11 000 6132 09 11 000 6133	09 11 000 6231 09 11 000 6232 09 11 000 6233	 	

Wire gauge	Ø	Stripping length
10 mm²	4.3	15.5 mm
16 mm²	5.5	15.5 mm
25 mm²	7.0	15.5 mm
for stranded wires acc. to IEC 60 228 class 5		

* Crimp zone acc. to DIN EN 46 235

Features

- One contact (70 A) for power circuits
- Four contacts (16 A) for signal circuits
- Combination of power and signal contacts in one module

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 60 61984

Inserts

Number of contacts	1 / 4
Electrical data accd. to DIN EN 61 984	
Power contacts	70 A 1000 V 8 kV 3
Rated current	70 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Signal contacts	16 A 400 V 6 kV 3
Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3

Insulation resistance	$\geq 10^{10} \Omega$
Material	Polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	≥ 500 mating cycles

Power Contacts

Material	Copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.5 \text{ m}\Omega$
Axial screw terminal	
- geometric wire gauge	6 ... 22 mm ²
- AWG	8 ... 4
- Hexagonal drive	SW 2.5

Tightening torque	mm ²	6	10	16	22
	Nm	2	3	4	4
Stripping length	mm ²	6	10	16	22
	mm	11 ⁺¹	11 ⁺¹	11 ⁺¹	12.5 ⁺¹

Signal Contacts

Material	Copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Ag over 3 µm Ni
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 4 mm ²
- AWG	26 ... 12

Han-Modular® 70 A Hybrid Module



Number of contacts

**1 x 70 A
4 x 16 A**



Identification	Part-Number		Drawings	Dimensions in mm
	Male insert (M)	Female insert (F)		
Han® 70 A Hybrid Module axial screw terminal 6 ... 16 mm ²	09 14 005 2646	09 14 005 2741		
14 ... 22 mm ²	09 14 005 2647	09 14 005 2742		

Identification	Part-Number	Depiction
Hex Key SW 2.5 for axial screw terminal Bit 1/4 "	09 99 000 0375	

Identification	Wire gauge (mm ²)	Male insert (M)	Female insert (F)	Drawings	Dimensions in mm
Signal contacts crimp terminal	0.14-0.37	09 33 000 6127	09 33 000 6227		
silver plated	0.5	09 33 000 6121	09 33 000 6020		
	0.75	09 33 000 6114	09 33 000 6214		
	1	09 33 000 6105	09 33 000 6205		
	1.5	09 33 000 6104	09 33 000 6204		
	2.5	09 33 000 6102	09 33 000 6202		
	3	09 33 000 6106	09 33 000 6206		
	4	09 33 000 6107	09 33 000 6207		
gold plated crimp terminal	0.14-0.37	09 33 000 6117	09 33 000 6117		
	0.5	09 33 000 6122	09 33 000 6222		
	0.75	09 33 000 6115	09 33 000 6215		
	1	09 33 000 6118	09 33 000 6218		
	1.5	09 33 000 6116	09 33 000 6216		
	2.5	09 33 000 6123	09 33 000 6223		
	4	09 33 000 6119	09 33 000 6221		

Identification	Wire gauge	Stripping length
no groove	0.14 ... 0.37 mm ²	AWG 26-22
no groove	0.5 mm ²	AWG 20
1 grooves*	0.75 mm ²	AWG 18
1 grooves	1 mm ²	AWG 18
2 grooves	1.5 mm ²	AWG 16
3 grooves	2.5 mm ²	AWG 14
wide groove	3 mm ²	AWG 12
no groove	4 mm ²	AWG 12

*on the back crimp collar

Crimp contacts 0.14 ... 0.37 mm² only used with BUCHANAN crimping tool 09 99 000 0001

Stock items in bold type

Features

- Axial-screw termination
- No special tools required
- Compatible to Han® 40 A module with crimp terminal

Technical characteristics

Han
Modular

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	2
Electrical data	
acc. to EN 61 984	40 A 1000 V 8 kV 3
Rated current	40 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500


Contacts

Material	copper alloy														
Surface	<ul style="list-style-type: none">- hard-silver plated														
Contact resistance	3 µm Ag														
Screw terminal	0.5 mΩ														
- Wire gauge ¹⁾	2.5 ... 10 mm ²														
- AWG	14 ... 8														
- Hexagonal driver	SW 2														
- Stripping length	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>mm²</td><td>2.5</td><td>4</td><td>6</td><td>10</td></tr> <tr> <td>mm</td><td>5⁺¹</td><td>5⁺¹</td><td>8⁺¹</td><td>11⁺¹</td></tr> </table>					mm ²	2.5	4	6	10	mm	5 ⁺¹	5 ⁺¹	8 ⁺¹	11 ⁺¹
mm ²	2.5	4	6	10											
mm	5 ⁺¹	5 ⁺¹	8 ⁺¹	11 ⁺¹											
- Tightening tourque	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>mm²</td><td>2.5</td><td>4</td><td>6</td><td>10</td></tr> <tr> <td>Nm</td><td>1.5</td><td>1.5</td><td>2</td><td>2</td></tr> </table>					mm ²	2.5	4	6	10	Nm	1.5	1.5	2	2
mm ²	2.5	4	6	10											
Nm	1.5	1.5	2	2											

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



Ambient temperature

① 24 B hoods/housings with 6 modules; wire gauge: 10 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 6 mm²

Number of contacts

2

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Axial screw terminal 40 A				
2.5 ... 8 mm ²	09 14 002 2601	09 14 002 2701	M	
6 ... 10 mm ²	09 14 002 2602	09 14 002 2702	F	
Contact arrangement view from termination side				

Identification	Part number	Drawing	Dimensions in mm
Hex key SW 2 for axial setscrew			
with grip	09 99 000 0313		
Bit 1/4"	09 99 000 0369		

Features


- Crimp termination
- Compatible with Han® 40 A module with axial screw terminal

Han
Modular

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



Ambient temperature

① 24 B hoods/housings with 6 modules; wire gauge: 10 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 6 mm²

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	2
Electrical data	
acc. to EN 61 984	40 A 1000 V 8 kV 3
Rated current	40 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Crimp terminal	
- mm ²	1.5 ... 10 mm ²
- AWG	16 ... 8


Number of contacts

2



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 002 3002	09 14 002 3102	 Contact arrangement view from termination side	Han Modular

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	1.5	09 32 000 6104	09 32 000 6204		
	2.5	09 32 000 6105	09 32 000 6205		
	4	09 32 000 6107	09 32 000 6207		
	6	09 32 000 6108	09 32 000 6208		
	10	09 32 000 6109	09 32 000 6209		



Wire gauge	∅	Stripping length
1.5 mm²	AWG 16	1.75
2.5 mm²	AWG 14	2.25
4 mm²	AWG 12	2.85
6 mm²	AWG 10	3.5
10 mm²	AWG 8	4.3

Stripping length a = 15 mm for cables ≥ 5 mm
Stripping length a = 18 mm for cables ≥ 6.4 mm

Features

- Axial screw terminal
- No special tools required for assembly
- Compatible to Han® C module with crimp terminal

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	3
Electrical data	
acc. to EN 61 984	40 A 690 V 8 kV
Rated current	40 A
Rated voltage	690 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500


Contacts

Material	copper alloy														
Surface	 - hard-silver plated														
Contact resistance	3 µm Ag														
Screw terminal	0.3 mΩ														
- Wire gauge ¹⁾	2.5 ... 10 mm ²														
- AWG	14 ... 8														
- Hexagonal driver	SW 2														
- Stripping length	<table border="1"> <tr> <td>mm²</td> <td>2.5</td> <td>4</td> <td>6</td> <td>10</td> </tr> <tr> <td>mm</td> <td>5⁺¹</td> <td>5⁺¹</td> <td>8⁺¹</td> <td>11⁺¹</td> </tr> </table>					mm ²	2.5	4	6	10	mm	5 ⁺¹	5 ⁺¹	8 ⁺¹	11 ⁺¹
mm ²	2.5	4	6	10											
mm	5 ⁺¹	5 ⁺¹	8 ⁺¹	11 ⁺¹											
- Tightening tourque	<table border="1"> <tr> <td>mm²</td> <td>2.5</td> <td>4</td> <td>6</td> <td>10</td> </tr> <tr> <td>Nm</td> <td>1.5</td> <td>1.5</td> <td>2</td> <td>2</td> </tr> </table>					mm ²	2.5	4	6	10	Nm	1.5	1.5	2	2
mm ²	2.5	4	6	10											
Nm	1.5	1.5	2	2											

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 4 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 6 mm²

③ 24 B hoods/housings with 6 modules; wire gauge: 10 mm²

1) geometric wire gauge

Number of contacts

3

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Axial screw terminal 40 A				
2.5 ... 8 mm ²	09 14 003 2601	09 14 003 2701	M	
6 ... 10 mm ²	09 14 003 2602	09 14 003 2702	F	

Identification	Part number	Drawing	Dimensions in mm
Hex key SW 2 for axial setscrew			
with grip	09 99 000 0313		
Bit 1/4"	09 99 000 0369		

06
45

Stock items in bold type

Features

- Suitable for Han® C crimp contacts
- Standard module for power up to 40 A
- Compatible to Han® C module with axial screw terminal

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	3
Electrical data	
acc. to EN 61 984	40 A 690 V 8 kV 3
Rated current	40 A
Rated voltage	690 V
Rated impulse voltage	8 kV
Pollution degree	3

Insulation diameter	up to 7.5 mm
Rated voltage	
acc. to UL/CSA	600 V
Rated current	
acc. to UL/CSA	32 A
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Crimp terminal	
- mm ²	1.5 ... 10 mm ²
- AWG	16 ... 8

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 4 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 6 mm²

③ 24 B hoods/housings with 6 modules; wire gauge: 10 mm²

Number of contacts

3



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 003 3001	09 14 003 3101		

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	1.5	09 32 000 6104	09 32 000 6204		
	2.5	09 32 000 6105	09 32 000 6205		
	4	09 32 000 6107	09 32 000 6207		
	6	09 32 000 6108	09 32 000 6208		
	10	09 32 000 6109	09 32 000 6209		
Wire gauge		∅	Stripping length		
1.5 mm²	AWG 16	1.75	9.5 mm		
2.5 mm²	AWG 14	2.25	9.5 mm		
4 mm²	AWG 12	2.85	9.5 mm		
6 mm²	AWG 10	3.5	9.5 mm		
10 mm²	AWG 8	4.3	12 mm		

Features

- Suitable for Han® C crimp contacts
- Designed for a high working voltage up to 830 V
- Finger safe male and female contacts
- High contact density

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	4
Electrical data	
acc. to EN 61 984	40 A 830 V 8 kV 3
Rated current	40 A
Rated voltage	830 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Crimp terminal	
- mm ²	1.5 ... 6 mm ²
- AWG	16 ... 10

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2




① 24 B hoods/housings with 6 modules; wire gauge: 4 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 6 mm²

Number of contacts

4



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 004 3041	09 14 004 3141		Han Modular

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	1.5 2.5 4 6	09 32 000 6104 09 32 000 6105 09 32 000 6107 09 32 000 6108	09 32 000 6204 09 32 000 6205 09 32 000 6207 09 32 000 6208		

Wire gauge	Ø	Stripping length
1.5 mm²	AWG 16	1.75
2.5 mm²	AWG 14	2.25
4 mm²	AWG 12	2.85
6 mm²	AWG 10	3.5

Features

- 3 contacts (40 A) for power circuits and 4 contacts (10 A) for signal circuits
- Ideal as motor drive connector
- Male and female contacts are finger safe

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	3 / 4
Electrical data acc. to EN 61 984	
Power contacts	40 A 830 V 8 kV 3
Rated current	40 A
Rated voltage	830 V
Rated impulse voltage	8 kV
Pollution degree	3

Signal contacts	10 A 830 V 8 kV 3
Rated current	10 A
Rated voltage	830 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	
Power contacts	$\leq 0.3 \text{ m}\Omega$
Signal contacts	$\leq 3 \text{ m}\Omega$
Crimp terminal	
- mm ²	
Power contacts	1.5 ... 6 mm ²
Signal contacts	0.14 ... 2.5 mm ²
- AWG	
Power contacts	16 ... 10
Signal contacts	26 ... 14
Max. insulation diameter	
- Power contacts	5 mm

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 4 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 6 mm²

Number of contacts

3 / 4



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 007 3001	09 14 007 3101	M F 	Contact arrangement view from termination side

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	1.5 2.5 4 6	09 32 000 6104 09 32 000 6105 09 32 000 6107 09 32 000 6108	09 32 000 6204 09 32 000 6205 09 32 000 6207 09 32 000 6208	 	Wire gauge Ø Stripping length 1.5 mm² AWG 16 1.75 9.5 mm 2.5 mm² AWG 14 2.25 9.5 mm 4 mm² AWG 12 2.85 9.5 mm 6 mm² AWG 10 3.5 9.5 mm
Signal contacts silver plated	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6104 09 15 000 6103 09 15 000 6105 09 15 000 6102 09 15 000 6101 09 15 000 6106	09 15 000 6204 09 15 000 6203 09 15 000 6205 09 15 000 6202 09 15 000 6201 09 15 000 6206	 	Wire gauge Ø Stripping length 0.14-0.37 mm² AWG 26-22 0.9 8 mm 0.5 mm² AWG 20 1.1 8 mm 0.75 mm² AWG 18 1.3 8 mm 1 mm² AWG 18 1.45 8 mm 1.5 mm² AWG 16 1.75 8 mm 2.5 mm² AWG 14 2.25 6 mm
gold plated	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6124 09 15 000 6123 09 15 000 6125 09 15 000 6122 09 15 000 6121 09 15 000 6126	09 15 000 6224 09 15 000 6223 09 15 000 6225 09 15 000 6222 09 15 000 6221 09 15 000 6226		

Stock items in bold type


Features

- Suitable for Han E® crimp contacts
- Standard module for power up to 40 A

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 2.5 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	6
Electrical data	
acc. to EN 61 984	16 A 500 V 6 kV
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3

Rated voltage	
acc. to UL/CSA	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 4 mm ²
- AWG	26 ... 12

Number of contacts

6



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 006 3001	09 14 006 3101		

Contact arrangement view from termination side

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm																																			
		Male contact	Female contact																																					
Crimp contacts																																								
Power contacts																																								
silver plated	0,14-0,37 0,5 0,75 1 1,5 2,5 3 4	09 33 000 6127 09 33 000 6121 09 33 000 6114 09 33 000 6105 09 33 000 6104 09 33 000 6102 09 33 000 6106 09 33 000 6107	09 33 000 6227 09 33 000 6220 09 33 000 6214 09 33 000 6205 09 33 000 6204 09 33 000 6202 09 33 000 6206 09 33 000 6207																																					
gold plated	0,14-0,37 0,5 0,75 1 1,5 2,5 4	09 33 000 6117 09 33 000 6122 09 33 000 6115 09 33 000 6118 09 33 000 6116 09 33 000 6123 09 33 000 6119	09 33 000 6217 09 33 000 6222 09 33 000 6215 09 33 000 6218 09 33 000 6216 09 33 000 6223 09 33 000 6221	<table border="1"> <thead> <tr> <th>Identification</th> <th>Wire gauge</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>no groove</td> <td>0,14-0,37 mm²</td> <td>AWG 26-22</td> <td>7.5 mm</td> </tr> <tr> <td>no groove</td> <td>0,5 mm²</td> <td>AWG 20</td> <td>7.5 mm</td> </tr> <tr> <td>1 groove*</td> <td>0,75 mm²</td> <td>AWG 18</td> <td>7.5 mm</td> </tr> <tr> <td>1 groove</td> <td>1 mm²</td> <td>AWG 18</td> <td>7.5 mm</td> </tr> <tr> <td>2 grooves</td> <td>1,5 mm²</td> <td>AWG 16</td> <td>7.5 mm</td> </tr> <tr> <td>3 grooves</td> <td>2,5 mm²</td> <td>AWG 14</td> <td>7.5 mm</td> </tr> <tr> <td>wide groove</td> <td>3 mm²</td> <td>AWG 12</td> <td>7.5 mm</td> </tr> <tr> <td>no groove</td> <td>4 mm²</td> <td>AWG 12</td> <td>7.5 mm</td> </tr> </tbody> </table>	Identification	Wire gauge	Stripping length	no groove	0,14-0,37 mm²	AWG 26-22	7.5 mm	no groove	0,5 mm²	AWG 20	7.5 mm	1 groove*	0,75 mm²	AWG 18	7.5 mm	1 groove	1 mm²	AWG 18	7.5 mm	2 grooves	1,5 mm²	AWG 16	7.5 mm	3 grooves	2,5 mm²	AWG 14	7.5 mm	wide groove	3 mm²	AWG 12	7.5 mm	no groove	4 mm²	AWG 12	7.5 mm	* on the back crimp collar
Identification	Wire gauge	Stripping length																																						
no groove	0,14-0,37 mm²	AWG 26-22	7.5 mm																																					
no groove	0,5 mm²	AWG 20	7.5 mm																																					
1 groove*	0,75 mm²	AWG 18	7.5 mm																																					
1 groove	1 mm²	AWG 18	7.5 mm																																					
2 grooves	1,5 mm²	AWG 16	7.5 mm																																					
3 grooves	2,5 mm²	AWG 14	7.5 mm																																					
wide groove	3 mm²	AWG 12	7.5 mm																																					
no groove	4 mm²	AWG 12	7.5 mm																																					
Relay contact silver plated	0,75-1 1,5 2,5	09 33 000 6109 09 33 000 6110 09 33 000 6111																																						

Crimp contacts 0.14 ... 0.37 mm² only used with BUCHANAN crimping tool 09 99 000 0001

Stock items in bold type

Features

- Innovative Han-Quick Lock® termination technology
- Field assembly without special tools
- Compatible to Han® E module with crimp terminal
- Reduced wiring times

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984


Inserts



Number of contacts	6
Electrical data acc. to EN 61 984	16 A 500 V 6 kV 3
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hart gold plated	2 µm Au over 3 µm Ag Ni
Contact resistance	$\leq 1 \text{ m}\Omega$
Quick Lock termination	
- mm²	0.5 ... 2.5 mm²
- AWG	20 ... 14

Number of contacts

6

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Quick Lock termination	09 14 006 26 33	09 14 006 27 33		

Contact arrangement
view from
termination side06
55

Stock items in bold type

Features

- Suitable for Han E® crimp contacts
- High contact density
- Compatible to the Han® EE module with Quick Lock terminal


Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	8
Electrical data acc. to EN 61 984	16 A 400 V 6 kV
Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500
Contacts	
Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 4 mm ²
- AWG	26 ... 12

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 2.5 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²

Number of contacts

8



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 008 3001	09 14 008 3101		Han Modular

Contact arrangement view from termination side

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	0.14-0.37	09 33 000 6127	09 33 000 6227		Operating contact identification
	0.5	09 33 000 6121	09 33 000 6220		Relay contact
	0.75	09 33 000 6114	09 33 000 6214		
	1	09 33 000 6105	09 33 000 6205		
	1.5	09 33 000 6104	09 33 000 6204		
	2.5	09 33 000 6102	09 33 000 6202		
	3	09 33 000 6106	09 33 000 6206		
	4	09 33 000 6107	09 33 000 6207		
gold plated	0.14-0.37	09 33 000 6117	09 33 000 6217		Operating contact identification
	0.5	09 33 000 6122	09 33 000 6222		Relay contact
	0.75	09 33 000 6115	09 33 000 6215		
	1	09 33 000 6118	09 33 000 6218		
	1.5	09 33 000 6116	09 33 000 6216		
	2.5	09 33 000 6123	09 33 000 6223		
	4	09 33 000 6119	09 33 000 6221		
Relay contact silver plated	0.75-1	09 33 000 6109			
	1.5	09 33 000 6110			
	2.5	09 33 000 6111			

Identification	Wire gauge	Stripping length
no groove	0.14-0.37 mm²	AWG 26-22
no groove	0.5 mm²	AWG 20
1 groove*	0.75 mm²	AWG 18
1 groove	1 mm²	AWG 18
2 grooves	1.5 mm²	AWG 16
3 grooves	2.5 mm²	AWG 14
wide groove	3 mm²	AWG 12
no groove	4 mm²	AWG 12

* on the back crimp collar

Features

- Innovative Han-Quick Lock® termination technology
- Field assembly without special tools
- Compatible to Han® EE module with crimp terminal
- Reduced wiring times

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	8
Electrical data acc. to EN 61 984	16 A 400 V 6 kV 3
Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface - hard-silver plated	$3 \mu\text{m}$ Ag
Contact resistance	$\leq 1 \text{ m}\Omega$
Termination	
Termination	Han-Quick Lock®

blue slide

Terminal wire gauge	0.5 ... 2.5 mm ² (AWG 20 - 14)
max. Insulation diameter	3.6 mm


black slide

Terminal wire gauge	0.25 ... 1.5 mm ² (AWG 23 - 16)
max. Insulation diameter	3.0 mm

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5-2




① 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 2.5 mm²

Number of contacts

8

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Quick Lock termination 				
0.5 ... 2.5 mm ² 	09 14 008 2633	09 14 008 2733		Contact arrangement view from termination side
0.25 ... 1.5 mm ² 	09 14 008 2634	09 14 008 2734		

Features

- Suitable for Han E® crimp contacts
- designed for a high working voltage up to 830 V
- finger safe male and female contacts

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	6
Electrical data	
acc. to EN 61 984	16 A 830 V 8 kV
Rated current	16 A
Rated voltage	830 V
Rated impulse voltage	8 kV
Pollution degree	3

Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 4 mm ²
- AWG	26 ... 12

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 2.5 mm²

③ 24 B hoods/housings with 6 modules; wire gauge: 4 mm²

Number of contacts

6



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 006 3041	09 14 006 3141	M F M F 	Han Modular

Contact arrangement view from termination side

Identification	Wire gauge (mm ²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	0.14-0.37 0.5 0.75 1 1.5 2.5 3 4	09 33 000 6127 09 33 000 6121 09 33 000 6114 09 33 000 6105 09 33 000 6104 09 33 000 6102 09 33 000 6106 09 33 000 6107	09 33 000 6227 09 33 000 6220 09 33 000 6214 09 33 000 6205 09 33 000 6204 09 33 000 6202 09 33 000 6206 09 33 000 6207	 Operating contact identification Relay contact	
gold plated	0.14-0.37 0.5 0.75 1 1.5 2.5 4	09 33 000 6117 09 33 000 6122 09 33 000 6115 09 33 000 6118 09 33 000 6116 09 33 000 6123 09 33 000 6119	09 33 000 6217 09 33 000 6222 09 33 000 6215 09 33 000 6218 09 33 000 6216 09 33 000 6223 09 33 000 6221	 Identification Wire gauge Stripping length	
Relay contact silver plated	0.75-1 1.5 2.5	09 33 000 6109 09 33 000 6110 09 33 000 6111			

Crimp contacts 0.14 ... 0.37 mm² only used with BUCHANAN crimping tool 09 99 000 0001

Stock items in bold type

Features

- Suitable for Han E® crimp contacts
- High contact density
- Up to 16 A per contact
- Also suitable as a reliable signal connector


Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	20
Electrical data acc. to EN 61 984	16 A 500 V 6 kV
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500
Contacts	
Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 4 mm ²
- AWG	26 ... 12

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



- ① 24 B hoods/housings with 3 modules; wire gauge: 1.5 mm²
- ② 24 B hoods/housings with 3 modules; wire gauge: 2.5 mm²
- ③ 24 B hoods/housings with 3 modules; wire gauge: 4 mm²

Number of contacts

20



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 020 3001	09 14 020 3101		

Contact arrangement view from termination side

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	0.14-0.37	09 33 000 6127	09 33 000 6227		
	0.5	09 33 000 6121	09 33 000 6220		
	0.75	09 33 000 6114	09 33 000 6214		
	1	09 33 000 6105	09 33 000 6205		
	1.5	09 33 000 6104	09 33 000 6204		
	2.5	09 33 000 6102	09 33 000 6202		
	3	09 33 000 6106	09 33 000 6206		
	4	09 33 000 6107	09 33 000 6207		
gold plated	0.14-0.37	09 33 000 6117	09 33 000 6217		
	0.5	09 33 000 6122	09 33 000 6222		
	0.75	09 33 000 6115	09 33 000 6215		
	1	09 33 000 6118	09 33 000 6218		
	1.5	09 33 000 6116	09 33 000 6216		
	2.5	09 33 000 6123	09 33 000 6223		
	4	09 33 000 6119	09 33 000 6221		
Relay contact silver plated	0.75-1	09 33 000 6109			
	1.5	09 33 000 6110			
	2.5	09 33 000 6111			

Identification	Wire gauge	Stripping length
no groove	0.14-0.37 mm²	AWG 26-22
no groove	0.5 mm²	AWG 20
1 groove*	0.75 mm²	AWG 18
1 groove	1 mm²	AWG 18
2 grooves	1.5 mm²	AWG 16
3 grooves	2.5 mm²	AWG 14
wide groove	3 mm²	AWG 12
no groove	4 mm²	AWG 12

* on the back crimp collar

Features

- Cage-clamp terminal
- No special tools required

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	5
Electrical data	
acc. to EN 61 984	16 A 400 V 6 kV
Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3

Rated voltage	
acc. to UL	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500


Contacts

Material	copper alloy
Surface	
- hard-silver plated	$3 \mu\text{m}$ Ag
Contact resistance	$\leq 3 \text{ m}\Omega$
Cage clamp terminal	
- mm ²	0.14 ... 2.5 mm ²
- AWG	26 ... 14

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.


Measuring and testing techniques according to
DIN EN 60 512-5-2




① 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 2.5 mm²

Number of contacts

5

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Cage-clamp terminal	09 14 005 2616	09 14 005 2716		 Han Modular

Contact arrangement view from termination side

06
65

Stock items in bold type

Features

- Suitable for Han® E crimp contacts
- 2 contacts up to 2500 V
- Insulator out of a voltage resistant teflon material
- Combination with all other modules (pneumatic, signal etc.) is possible

Technical characteristics

Specifications	DIN EN 61 984 DIN VDE 0115 DIN EN 60 664-1
Inserts	
Number of contacts	2
Electrical data acc. to EN 61 984	16 A 2500 V 15 kV 3
Rated current	16 A
Rated voltage	2500 V
Rated impulse voltage	15 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Material	Polycarbonate/Teflon (PTFE)
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500
Contacts	
Material	Copper alloy
Surface	3 µm Ag 2 µm Au over 3 µm Ag Ni
- hard-silver plated	
- hard gold plated	
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.5 ... 4 mm ²
- AWG	20 ... 12

Number of contacts

2



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately Range of delivery: - 1 module - 2 locking sleeves - 2 heat shrink tubes	09 14 002 3025	09 14 002 3125		
Removal tool for locking sleeve	09 99 000 0335	09 99 000 0335		

Han Modular

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts Han E® Power contacts					
silver plated	0.14-0.37	09 33 000 6127	09 33 000 6227		
	0.5	09 33 000 6121	09 33 000 6220		
	0.75	09 33 000 6114	09 33 000 6214		
	1.0	09 33 000 6105	09 33 000 6205		
	1.5	09 33 000 6104	09 33 000 6204		
	2.5	09 33 000 6102	09 33 000 6202		
	3.0	09 33 000 6106	09 33 000 6206		
	4.0	09 33 000 6107	09 33 000 6207		
Wire gauge		Identification	Stripping length		
4.0-0.37 mm²	AWG 26-22	no groove	7.5 mm		
0.5 mm²	AWG 20	no groove	7.5 mm		
0.75 mm²	AWG 18	1 groove*	7.5 mm		
1.0 mm²	AWG 18	1 groove	7.5 mm		
1.5 mm²	AWG 16	2 grooves	7.5 mm		
2.5 mm²	AWG 14	3 grooves	7.5 mm		
3.0 mm²	AWG 12	wide groove	7.5 mm		
4.0 mm²	AWG 12	no groove	7.5 mm		

* on the back crimp collar

06
67

Stock items in bold type


Features

- Suitable for Han E® crimp contacts
- 2 contacts up to 5000 V
- Insulator out of a voltage resistant teflon material
- Combination of all other modules (pneumatic, signal etc.)

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① Housing Han® 16 B with 1 Han® HV module, wire gauge:
2.5 mm²

Technical characteristics

Specifications

DIN EN 61 984
DIN VDE 0115
DIN EN 60 664-1

Inserts


Number of contacts	2
Electrical data acc. to EN 61 984	16 A 2900/5000 V 15 kV 3
Rated current	16 A
Rated voltage conductor - ground	2900 V
Rated voltage conductor - conductor	5000 V
Rated impulse voltage	15 kV
Pollution degree	3

Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate/Teflon (PTFE)
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	$\leq 1 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.5 ... 4 mm ²
- AWG	20 ... 12

Assembly instructions



Number of contacts

2



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately			M	
Range of delivery: - 1 module - 2 locking sleeves - 2 heat shrink tubes	09 14 002 3021	09 14 002 3121	F	

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
silver plated					
	0.5	09 33 000 6121	09 33 000 6220		
	0.75	09 33 000 6114	09 33 000 6214		
	1	09 33 000 6105	09 33 000 6205		
	1.5	09 33 000 6104	09 33 000 6204		
	2.5	09 33 000 6102	09 33 000 6202		
	3	09 33 000 6106	09 33 000 6206		
	4	09 33 000 6107	09 33 000 6207		
Identification	Wire gauge		Stripping length		
no groove	0.5 mm²	AWG 20	9.5 mm		
1 groove*	0.75 mm²	AWG 18	9.5 mm		
1 groove	1 mm²	AWG 18	9.5 mm		
2 grooves	1.5 mm²	AWG 16	9.5 mm		
3 grooves	2.5 mm²	AWG 14	9.5 mm		
wide groove	3 mm²	AWG 12	9.5 mm		
no groove	4 mm²	AWG 12	9.5 mm		

* on the back crimp collar

Features

- Suitable for Han® C crimp contacts
- 2 contacts up to 5000 V
- Insulator out of a voltage resistant teflon material
- Combination of all other modules (pneumatic, signal etc.)

Technical characteristics

Specifications

DIN EN 61 984
DIN VDE 0115
DIN EN 60 664-1

Inserts

Number of contacts	2
Electrical data	
acc. to EN 61 984	40 A 2900/5000 V 15 kV 3
Rated current	40 A
Rated voltage conductor - ground	2900 V
Rated voltage conductor - conductor	5000 V
Rated impulse voltage	15 kV
Pollution degree	3

Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate/Teflon (PTFE)
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Max. cable diameter	9 mm
Mechanical working life - mating cycles	≥ 500


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	$\leq 0.3 \text{ m}\Omega$
Crimp terminal	
- mm ²	1.5 ... 10 mm ²
- AWG	16 ... 8

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.


Measuring and testing techniques according to
DIN EN 60 512-5-2





24 B hoods/housings with 3 modules; wire gauge: 6 mm²

Assembly instructions

Han® C Crimp contact Locking sleeve



Cable



Crimp with tool 0999 000 0001,
0999 000 0110 or 0999 000 0377
Snap crimped cable in the insert

shrink the heat shrink tube over the
rear of contact

Number of contacts

2



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately			M	
Range of delivery: - 1 module - 2 locking sleeves - 2 heat shrink tubes	09 14 002 3023	09 14 002 3123	F	
Removal tool for locking sleeve	09 99 000 0327	09 99 000 0327		

Han Modular

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	1.5 2.5 4 6 10	09 32 000 6104 09 32 000 6105 09 32 000 6107 09 32 000 6108 09 32 000 6109	09 32 000 6204 09 32 000 6205 09 32 000 6207 09 32 000 6208 09 32 000 6209		
Wire gauge		∅	Stripping length		
1.5 mm²	AWG 16	1.75	13 mm		
2.5 mm²	AWG 14	2.25	13 mm		
4 mm²	AWG 12	2.85	13 mm		
6 mm²	AWG 10	3.5	13 mm		
10 mm²	AWG 8	4.3	13 mm		

06
71

Stock items in bold type


Features

- Suitable for Han D® crimp contacts
- Standard module for power up to 10 A
- Compatible to Han DD® module with Quick Lock terminal

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



- ① 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²
 ② 24 B hoods/housings with 6 modules; wire gauge: 1.0 mm²

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	12
Electrical data	
acc. to EN 61 984	10 A 250 V 4 kV 3
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3

Rated voltage	
acc. to UL/CSA	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	$\leq 3 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 2.5 mm ²
- AWG	26 ... 14

Number of contacts

12



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 012 3001	09 14 012 3101	 	Han Modular

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	0.14-0.37	09 15 000 6104	09 15 000 6204		
	0.5	09 15 000 6103	09 15 000 6203		
	0.75	09 15 000 6105	09 15 000 6205		
	1	09 15 000 6102	09 15 000 6202		
	1.5	09 15 000 6101	09 15 000 6201		
	2.5	09 15 000 6106	09 15 000 6206		
gold plated	0.14-0.37	09 15 000 6124	09 15 000 6224		
	0.5	09 15 000 6123	09 15 000 6223		
	0.75	09 15 000 6125	09 15 000 6225		
	1	09 15 000 6122	09 15 000 6222		
	1.5	09 15 000 6121	09 15 000 6221		
	2.5	09 15 000 6126	09 15 000 6226		
F.O. contacts					
for 1 mm plastic fibre					
		20 10 001 3211	20 10 001 3221		

Features

- Innovative Han-Quick Lock® termination technology
- Field assembly without special tools
- Mating compatible with standard Han® DD module with crimp terminal
- Reduced wiring times

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Inserts

Number of contacts	12
Electrical data	
acc. to EN 61 984	10 A 250 V 4 kV 3
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	- mating cycles


Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
- hard-gold plated	2 µm Au over 3 µm Ni
Contact resistance	$\leq 3 \text{ m}\Omega$
Quick Lock termination	
- mm²	0.25 ... 1.5 mm²
- AWG	22 ... 16

Current carrying capacity


The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.


Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²

Number of contacts

12

Identification	Part number Male insert (M)	Part number Female insert (F)	Drawing	Dimensions in mm
Quick Lock termination				
with silver plated contacts	09 14 012 2632	09 14 012 2732		
with gold plated contacts	09 14 012 2634	09 14 012 2734		

Contact arrangement view from termination side

Han Modular

06
75

Stock items in bold type

Features

- Suitable for Han D® crimp contacts
- High contact density


Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	17
Electrical data acc. to EN 61 984	10 A 160 V 2.5 kV 3
Rated current	10 A
Rated voltage	160 V
Rated impulse voltage	2.5 kV
Pollution degree	3
Rated voltage acc. to UL	250 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500
Contacts	
Material	copper alloy
Surface	<ul style="list-style-type: none"> - hard-silver plated - hard-gold plated
Contact resistance	$\leq 3 \text{ m}\Omega$
Crimp terminal	<ul style="list-style-type: none"> - mm² - AWG
	0.14 ... 2.5 mm ²
	26 ... 14

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 1.5 mm²

② 24 B hoods/housings with 6 modules; wire gauge: 1.0 mm²

Number of contacts

17



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 017 3001	09 14 017 3101	M: F:	Front view of the crimp terminal from the termination side.

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm
		Male contact	Female contact		
Crimp contacts					
Power contacts					
silver plated	0.14-0.37	09 15 000 6104	09 15 000 6204		
	0.5	09 15 000 6103	09 15 000 6203		
	0.75	09 15 000 6105	09 15 000 6205		
	1	09 15 000 6102	09 15 000 6202		
	1.5	09 15 000 6101	09 15 000 6201		
	2.5	09 15 000 6106	09 15 000 6206		
gold plated	0.14-0.37	09 15 000 6124	09 15 000 6224		
	0.5	09 15 000 6123	09 15 000 6223		
	0.75	09 15 000 6125	09 15 000 6225		
	1	09 15 000 6122	09 15 000 6222		
	1.5	09 15 000 6121	09 15 000 6221		
	2.5	09 15 000 6126	09 15 000 6226		
F.O. contacts					
for 1 mm plastic fibre					
		20 10 001 3211	20 10 001 3221		

Features

- Suitable for D-Sub crimp contacts
- High contact density
- Using of guiding pins (male and female) is recommended (see chapter 95).

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	25
Electrical data acc. to EN 61 984	4 A 50 V 0.8 kV 3
Rated current	4 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	< 30 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500


Contacts

Crimp terminal - mm ²	0.08 ... 0.52 mm ²
- AWG	28 ... 20
turned contacts	Performance level 1 as per CECC 75 301-802, 500 mating cycles, 10 days 4 mixed gas test - IEC 60 512

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to
DIN EN 60 512-5-2



① 24 B hoods/housings with 6 modules; wire gauge: 0.5 mm²
turned contacts

② 24 B hoods/housings with 6 modules; wire gauge: 0.5 mm²
stamped contacts

Number of contacts

25



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 14 025 3001	09 14 025 3101		

Identification	Part number		Drawing	Dimensions in mm												
		Male contact	Female contact													
D-Sub crimp contacts	0.08-0.21 0.13-0.33 0.21-0.52	09 67 000 7576 09 67 000 5576 09 67 000 8576	09 67 000 7476 09 67 000 5476 09 67 000 8476	<table border="1"> <thead> <tr> <th>Wire gauge</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>0.08-0.21 mm²</td> <td>AWG 28-24</td> <td>4 mm</td> </tr> <tr> <td>0.13-0.33 mm²</td> <td>AWG 26-22</td> <td>4 mm</td> </tr> <tr> <td>0.21-0.52 mm²</td> <td>AWG 24-20</td> <td>4 mm</td> </tr> </tbody> </table>	Wire gauge	Stripping length	0.08-0.21 mm ²	AWG 28-24	4 mm	0.13-0.33 mm ²	AWG 26-22	4 mm	0.21-0.52 mm ²	AWG 24-20	4 mm	
Wire gauge	Stripping length															
0.08-0.21 mm ²	AWG 28-24	4 mm														
0.13-0.33 mm ²	AWG 26-22	4 mm														
0.21-0.52 mm ²	AWG 24-20	4 mm														
Insertion / Removal tool for D-Sub crimp contacts		09 99 000 0368	09 99 000 0368		06 79											

Features

- 9-pin D-Sub connector of the Han-Modular® system
- Ideal for the transmission of sensitive signals
- Compatible to crimp, solder or IDC termination
- Using of guiding pins (male and female) is recommended (see chapter 95).

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	9
Electrical data acc. to EN 61 984	5 A 50 V 0.8 kV 3
Rated current	5 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	< 30 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Number of contacts

9

Identification	Part number		Drawing	Dimensions in mm						
	Male insert (M)	Female insert (F)								
Crimp terminal Order crimp contacts separately (see page 06.91)	09 14 009 3001	09 14 009 3101								
Adapter module without D-Sub insert for one cable	09 14 000 9930	09 14 000 9931								
for two cables	09 14 000 9932	09 14 000 9933								
Screw terminal for RS 485-based bus systems with T-functionality		09 14 009 3151		Contact arrangement view from termination side						
			<table border="1"> <thead> <tr> <th>Signal</th><th>Contact no.</th></tr> </thead> <tbody> <tr> <td>A</td><td>8</td></tr> <tr> <td>B</td><td>3</td></tr> </tbody> </table>	Signal	Contact no.	A	8	B	3	
Signal	Contact no.									
A	8									
B	3									

Features

- According to USB 2.0 specification
- Simple and cost effective termination by plug in patch cable
- Cable tie strain relief

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals 

Inserts

Number of contacts	4
Electrical data acc. to EN 61 984	1 A 50 V 0.8 kV 3
Rated current	1 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	< 30 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +85 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Number of contacts

4



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Module for patch cable Male insert	09 14 001 4601			
Module for patch cable Female insert		09 14 001 4701		
Module for screw termina-tion Male insert	09 14 001 4651			
Patch cable USB male / male Style A	2 m 39 50 903 0050	2 m 39 50 903 0050		
	5 m 39 50 903 0051	5 m 39 50 903 0051		

Han Modular

06
83

Features

- Compatibel to IEEE 1394
- Simple and cost effective termination by plug in patch cable
- Cable tie strain relief

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	6
Electrical data acc. to EN 61 984	1 A 50 V 0.8 kV 3
Rated current	1 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	< 30 V
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +85 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Number of contacts

6

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Module for patch cable Male insert	09 14 001 4611			
Module for patch cable Female insert		09 14 001 4711		

Features

- Single module with standard shielded RJ45 plug and jack
- Cat 6 for all data pairs (all 8 pins)
- Conforming to the RoHS directive
- The RJ45 inserts are protected by a reliable plastic insulator
- Patch cables are assembled/removed without tools

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984


Approvals



Inserts

Number of contacts	8
Electrical data acc. to EN 61 984	1 A 50 V 0.8 kV 3
Rated current	1 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	< 30 V
Transmission features	Category 6 / Class E up to 250 MHz; acc. to ISO/IEC 11 801:2002 and EN 50 173-1
Transmission rate	10/100/1000 Mbit/s
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +85 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Number of contacts

8

Identification	Part number Male insert (M)	Part number Female insert (F)	Drawing	Dimensions in mm
Gender Changer for patch cable		09 14 001 4721		
Male insert	09 14 001 4623			
Adapter for HARTING patch cable	09 14 000 9966			
Adapter for HARTING RJ Industrial® see page 06.91				

Features

- Locking lever protection for RJ45 connector latch
- Very short plug design in combination with robust bend protection
- RoHS compliant
- Fully EMC screened (aluminium-clad foil and braid)

Technical characteristics

Specifications

ISO/IEC 24 702
ISO/IEC 11 801
ISO/IEC 61 935-2

Cat. 5 e RJ45 patch cable

Transmission features

Category 5 /
Class D up to 100 MHz;
acc. to ISO/IEC 24 702
or ISO/IEC 11 801
10/100/1000 Mbit/s
1:1 EIA/TIA 568 B, 8 poles
SF/UTP, PUR, yellow

Transmission rate

Cable type

Material cables

Limiting temperatures

- mobile
- stationary

Flammability

Degree of protection

0 °C ... +60 °C
-40 °C ... +80 °C
flame retardant, halogen-free
IP 20

Cat. 6 RJ45 patch cable

Transmission features

Category 6 /
Class E up to 250 MHz;
acc. to ISO/IEC 24 702
or ISO/IEC 11 801
10/100/1000 Mbit/s
1:1 EIA/TIA 568 B, 8 poles
SF/UTP, PUR, yellow

Transmission rate

Cable type

Material cables

Limiting temperatures

- mobile
- stationary

Flammability

Degree of protection

0 °C ... +60 °C
-20 °C ... +80 °C
flame retardant, halogen-free
IP 20

Number of contacts

8

Identification	Part number	Drawing	Dimensions in mm
Cat. 5e RJ45 patch cable		 	Han Modular
Length	0.2 m 09 47 474 7001 0.3 m 09 47 474 7002 0.4 m 09 47 474 7003 0.5 m 09 47 474 7004 0.6 m 09 47 474 7005 0.7 m 09 47 474 7006 0.8 m 09 47 474 7007 0.9 m 09 47 474 7008 1.0 m 09 47 474 7009 1.5 m 09 47 474 7010 2.0 m 09 47 474 7011 2.5 m 09 47 474 7012 3.0 m 09 47 474 7013 4.0 m 09 47 474 7014 5.0 m 09 47 474 7015 6.0 m 09 47 474 7016 7.0 m 09 47 474 7017 7.5 m 09 47 474 7018 8.0 m 09 47 474 7019 9.0 m 09 47 474 7020 10 m 09 47 474 7021 15 m 09 47 474 7022 20 m 09 47 474 7023		
Cat. 6 RJ45 patch cable		 	
Length	0.2 m 09 47 474 7101 0.3 m 09 47 474 7102 0.4 m 09 47 474 7103 0.5 m 09 47 474 7104 0.6 m 09 47 474 7105 0.7 m 09 47 474 7106 0.8 m 09 47 474 7107 0.9 m 09 47 474 7108 1.0 m 09 47 474 7109 1.5 m 09 47 474 7110 2.0 m 09 47 474 7111 2.5 m 09 47 474 7112 3.0 m 09 47 474 7113 4.0 m 09 47 474 7114 5.0 m 09 47 474 7115 6.0 m 09 47 474 7116 7.0 m 09 47 474 7117 7.5 m 09 47 474 7118 8.0 m 09 47 474 7119 9.0 m 09 47 474 7120 10 m 09 47 474 7121 15 m 09 47 474 7122 20 m 09 47 474 7123		

Features

Han-Modular® RJ Industrial RJ45 connector set

- Conforming to the RoHS directive
- 360° shielded contact
- Field assembly without tools possible by means of HARAX® rapid termination in IDC technology
- Suitable for termination of massive and flexible wires

Han-Modular® RJ Industrial Gigalink RJ45 connector set

- Conforming to the RoHS directive
- 360° shielded contact
- Field assembly by means of piercing contacts
- Suitable for termination of flexible wires

Technical characteristics

Specifications

IEC 60 603-7
DIN EN 60 664-1
DIN EN 61 984

HARTING RJ Industrial®, 4 pins

Number of contacts	4
Transmission features	Category 5 / Class D up to 100 MHz; acc. to ISO/IEC 11 801:2002 and EN 50 173-1
Transmission rate	10/100 Mbit/s
Wire termination	IDC contacts; without tools
Terminated cable	- Conductor cross section flexible solid
	AWG 24/7 ... AWG 22/7
	- Cable outside diameter
	≤ 1.6 mm
Material insert	polyamide
Limiting temperatures	-40 °C ... +70 °C

HARTING RJ Industrial® 10G, 8 pins

Number of contacts	8
Transmission features	Category 6 / Class E up to 250 MHz; acc. to ISO/IEC 11 801:2002 and EN 50 173-1
Transmission rate	10/100 Mbit/s and 1/10 Gbit
Wire termination	IDC contacts; without tools
Terminated cable	- Conductor cross section flexible solid
	AWG 27/7 ... AWG 22/7
	- Cable outside diameter
	≤ 1.5 mm
Material insert	polyamide
Limiting temperatures	-40 °C ... +70 °C

HARTING RJ Industrial® Gigalink, 8 pins

Number of contacts	8
Transmission features	Category 6A / Class E _A up to 500 MHz; acc. to ISO/IEC 11 801:2002 and EN 50 173-1
Transmission rate	10/100 Mbit/s and 1/10 Gbit
Wire termination	Piercing contacts
Terminated cable	- Conductor cross section flexible
	AWG 28/7 ... AWG 24/7
	- Cable outside diameter
	≤ 1.05 mm
Material insert	polyamide
Limiting temperatures	-40 °C ... +70 °C

Number of contacts

4 / 8

Identification	Part number Male insert (M)	Drawing	Dimensions in mm
Han-Modular® RJ Industrial RJ45 connector set			
Cat. 5			
4 pins for AWG 24 ... 22	09 45 400 1100		
4 pins for AWG 26	09 45 400 1109		
Cat. 6			
10G, 8 pins	09 45 400 1560		
Cat. 6A			
Gigalink, 8 pins	09 45 400 1520		
			Set consists of the relevant RJ45 insert and the suitable adapter for Han® RJ45 male module (please order the male module 09 14 001 4623 separately)
HARTING RJ Industrial® Gigalink Assembly tool	09 45 800 0520		

* usable with male insert 09 14 001 4623 (see page 06.87)

Features

- Shielding bus separate from housing potential
- Ideal for the transmission of sensitive signals (e.g. bus signals)
- Usable for Gigabit Ethernet Cat. 6A

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	8
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

GigaBit contacts

Number of contacts	8 + shielding
Electrical data acc. to EN 61 984	5 A 50 V 0.8 kV 3
Rated current	5 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	< 30 V
Material - Insulator	polycarbonate
- Outer conductor	zinc alloy
Contact resistance	$\leq 4 \text{ m}\Omega$
Limiting temperatures	-40 °C ... +85 °C
Flammability acc. to UL 94	V 0
Outer surface finish	nickel
Cable diameter	5 ... 12 mm

D-Sub crimp contacts

Crimp terminal - mm ²	0.08 ... 0.52 mm ²
- AWG	28 ... 20
turned contacts	Performance level 1

Accessories

Crimp flange	see page 06.98
Crimp ferrule	see page 06.98
Cable clamp	see page 06.98

Number of contacts

8



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Module	09 14 001 3011	09 14 001 3111	M 	
			F 	
Identification	Wire gauge (mm²)	Part number	Drawing	Dimensions in mm
Han® GigaBit insert 8 + shielding		Male contact 09 14 008 3011 Female contact 09 14 008 3111	M 	
Order crimp contacts separately			F 	
D-Sub crimp contacts	0,08-0,21 0,13-0,33 0,21-0,52	09 67 000 7576 09 67 000 5576 09 67 000 5476 09 67 000 8576 09 67 000 7476 09 67 000 5476 09 67 000 8476	Wire gauge Stripping length	0,08-0,21 mm² AWG 28-24 4 mm 0,13-0,33 mm² AWG 26-22 4 mm 0,21-0,52 mm² AWG 24-20 4 mm

Features

- Shielding bus separate from housing potential
- Suitable for Ethernet Cat. 5e
- Suitable for Han B, Han M, Han EMC and Han HPR hoods/housings, high construction

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Han® module adapter

Number of contacts	2 x 4
Insulation resistance	$\geq 10^{10} \Omega$
Material	Polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	≥ 500 mating cycles

Han® MegaBit insert

Number of contacts	2 x 4 + shielding
Electrical data acc. to DIN EN 61 984	10 A 50 V 0.8 kV 3
Rated current	10 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Material	
- insulator	Polycarbonate
- outer conductor	Zinc alloy
Contact resistance	$\leq 4 \text{ m}\Omega$
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Outer surface finish	Nickel
Cable diameter	5 ... 12 mm

Han D® crimp contacts

Material	Copper alloy
Surface	
- hard gold plated	3 μm Au over 3 μm Ni
Contact resistance	$\leq 3 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 2.5 mm ²
- AWG	26 ... 14

Accessories

Crimp flange	see page 06.98
Crimp ferrule	see page 06.98
Cable clamp	see page 06.98

Number of contacts

2 x 4



Identification	Part-Number		Drawings	Dimensions in mm
	Male insert (M)	Female insert (F)		
Module	09 14 001 3011	09 14 001 3111	M F 	

Identification	Wire gauge mm ²	Part-Number		Drawings	Dimensions in mm
		Male contacts (M)	Female contacts (F)		
Han® MegaBit insert 2 x 4 contacts crimp contacts order separately		09 14 008 3016	09 14 008 3116	M F 	Contact arrangement View termination side
2 x 4 contacts with additional shield connection to the hinged frame crimp contacts order separately		09 14 008 3017	09 14 008 3117		

Han D® crimp contacts gold plated	0.14-0.37	09 15 000 6124		09 15 000 6224		Wire gauge	∅	Stripping length of stranded wire
		0.5	0.9	0.14 - 0.37 mm ²	AWG 26-22			
	0.5	09 15 000 6123	09 15 000 6223	0.5 mm ²	AWG 20	1.1	8 mm	
	0.75	09 15 000 6125	09 15 000 6225	0.75 mm ²	AWG 18	1.3	8 mm	
	1.0	09 15 000 6122	09 15 000 6222	1.0 mm ²	AWG 18	1.45	8 mm	
	1.5	09 15 000 6121	09 15 000 6221	1.5 mm ²	AWG 16	1.75	8 mm	
	2.5	09 15 000 6126	09 15 000 6226	2.5 mm ²	AWG 14	2.25	6 mm	

Stock items in bold type

Features

- Data bus shielding separated from housing
- Ideal for the transmission of very sensitive signals (e.g. bus signals)

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Han® Module adapter

Number of contacts	20 + shield
Insulation resistance	$\geq 10^{10} \Omega$
Material	Polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	≥ 500 mating cycles

Shielded insert

Electrical data acc. to DIN EN 61 984	4 A 32 V 0.8 kV 3
Rated current	4 A
Rated voltage	32 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Material	Liquid Crystalline Polymer
- Insulator	Zinc alloy
- Outer conductor	
Contact resistance	$\leq 4 \text{ m}\Omega$
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Outer surface finish	Nickel
Cable diameter	5 ... 12 mm

Han® D-Sub crimp contacts


Crimp terminal	
- mm ²	0.08 ... 0.52 mm ²
- AWG	28 ... 20
Turned contacts	Performance level 1

Accessories

Crimp flange	see page 06.98
Crimp ferrule	see page 06.98
Cable clamp	see page 06.98

Number of contacts

20



Identification	Part-Number		Drawings	Dimensions in mm
	Male insert (M)	Female insert (F)		
Module	09 14 001 3011	09 14 001 3111	M F 	

Identification	Wire gauge mm ²	Part-Number		Drawings	Dimensions in mm
		Male contacts (M)	Female contacts (F)		
Han® Shielded module insert 20 + shield crimp contacts order separately		09 14 020 3013	09 14 020 3113	M F 	Contact arrangement View termination side

Han® D-Sub crimp contacts gold plated	Wire gauge	Ø	Stripping length of stranded wire
	0.08-0.21	0.09 67 000 7576	0.09 67 000 7476
	0.13-0.33	0.09 67 000 5576	0.09 67 000 5476
	0.33-0.52	0.09 67 000 8576	0.09 67 000 8476

Identification	Part number	Drawing	Dimensions in mm																																																						
Crimp flange																																																									
Han Modular	<table> <thead> <tr> <th>D1</th> <th>D2</th> <th></th> </tr> </thead> <tbody> <tr><td>3.0</td><td>4.0</td><td>61 03 000 0062</td></tr> <tr><td>3.5</td><td>4.5</td><td>61 03 000 0063</td></tr> <tr><td>4.0</td><td>5.0</td><td>61 03 000 0064</td></tr> <tr><td>4.5</td><td>5.5</td><td>61 03 000 0065</td></tr> <tr><td>5.0</td><td>6.0</td><td>61 03 000 0066</td></tr> <tr><td>5.5</td><td>6.5</td><td>61 03 000 0166</td></tr> <tr><td>6.0</td><td>7.0</td><td>61 03 000 0067</td></tr> <tr><td>6.5</td><td>7.5</td><td>61 03 000 0068</td></tr> <tr><td>7.0</td><td>8.0</td><td>61 03 000 0069</td></tr> <tr><td>7.5</td><td>8.5</td><td>61 03 000 0070</td></tr> <tr><td>8.0</td><td>9.0</td><td>61 03 000 0071</td></tr> <tr><td>8.5</td><td>9.5</td><td>61 03 000 0165</td></tr> <tr><td>9.0</td><td>10.0</td><td>61 03 000 0072</td></tr> </tbody> </table>	D1	D2		3.0	4.0	61 03 000 0062	3.5	4.5	61 03 000 0063	4.0	5.0	61 03 000 0064	4.5	5.5	61 03 000 0065	5.0	6.0	61 03 000 0066	5.5	6.5	61 03 000 0166	6.0	7.0	61 03 000 0067	6.5	7.5	61 03 000 0068	7.0	8.0	61 03 000 0069	7.5	8.5	61 03 000 0070	8.0	9.0	61 03 000 0071	8.5	9.5	61 03 000 0165	9.0	10.0	61 03 000 0072														
D1	D2																																																								
3.0	4.0	61 03 000 0062																																																							
3.5	4.5	61 03 000 0063																																																							
4.0	5.0	61 03 000 0064																																																							
4.5	5.5	61 03 000 0065																																																							
5.0	6.0	61 03 000 0066																																																							
5.5	6.5	61 03 000 0166																																																							
6.0	7.0	61 03 000 0067																																																							
6.5	7.5	61 03 000 0068																																																							
7.0	8.0	61 03 000 0069																																																							
7.5	8.5	61 03 000 0070																																																							
8.0	9.0	61 03 000 0071																																																							
8.5	9.5	61 03 000 0165																																																							
9.0	10.0	61 03 000 0072																																																							
Crimp ferrule																																																									
	<table> <thead> <tr> <th>D3</th> <th>D4</th> <th></th> </tr> </thead> <tbody> <tr><td>5.0</td><td>6.0</td><td>61 03 000 0045</td></tr> <tr><td>5.5</td><td>6.5</td><td>61 03 000 0046</td></tr> <tr><td>6.0</td><td>7.0</td><td>61 03 000 0047</td></tr> <tr><td>6.5</td><td>7.5</td><td>61 03 000 0048</td></tr> <tr><td>7.0</td><td>8.0</td><td>61 03 000 0049</td></tr> <tr><td>7.5</td><td>8.5</td><td>61 03 000 0050</td></tr> <tr><td>8.0</td><td>9.0</td><td>61 03 000 0051</td></tr> <tr><td>8.5</td><td>9.5</td><td>61 03 000 0052</td></tr> <tr><td>9.0</td><td>10.0</td><td>61 03 000 0053</td></tr> <tr><td>9.5</td><td>10.5</td><td>61 03 000 0054</td></tr> <tr><td>10.0</td><td>11.0</td><td>61 03 000 0055</td></tr> <tr><td>10.5</td><td>11.5</td><td>61 03 000 0056</td></tr> <tr><td>11.0</td><td>12.0</td><td>61 03 000 0057</td></tr> <tr><td>11.5</td><td>12.5</td><td>61 03 000 0058</td></tr> <tr><td>12.0</td><td>13.0</td><td>61 03 000 0142</td></tr> <tr><td>12.5</td><td>13.5</td><td>61 03 000 0059</td></tr> <tr><td>13.0</td><td>14.0</td><td>61 03 000 0127</td></tr> </tbody> </table>	D3	D4		5.0	6.0	61 03 000 0045	5.5	6.5	61 03 000 0046	6.0	7.0	61 03 000 0047	6.5	7.5	61 03 000 0048	7.0	8.0	61 03 000 0049	7.5	8.5	61 03 000 0050	8.0	9.0	61 03 000 0051	8.5	9.5	61 03 000 0052	9.0	10.0	61 03 000 0053	9.5	10.5	61 03 000 0054	10.0	11.0	61 03 000 0055	10.5	11.5	61 03 000 0056	11.0	12.0	61 03 000 0057	11.5	12.5	61 03 000 0058	12.0	13.0	61 03 000 0142	12.5	13.5	61 03 000 0059	13.0	14.0	61 03 000 0127		
D3	D4																																																								
5.0	6.0	61 03 000 0045																																																							
5.5	6.5	61 03 000 0046																																																							
6.0	7.0	61 03 000 0047																																																							
6.5	7.5	61 03 000 0048																																																							
7.0	8.0	61 03 000 0049																																																							
7.5	8.5	61 03 000 0050																																																							
8.0	9.0	61 03 000 0051																																																							
8.5	9.5	61 03 000 0052																																																							
9.0	10.0	61 03 000 0053																																																							
9.5	10.5	61 03 000 0054																																																							
10.0	11.0	61 03 000 0055																																																							
10.5	11.5	61 03 000 0056																																																							
11.0	12.0	61 03 000 0057																																																							
11.5	12.5	61 03 000 0058																																																							
12.0	13.0	61 03 000 0142																																																							
12.5	13.5	61 03 000 0059																																																							
13.0	14.0	61 03 000 0127																																																							
Cable clamp																																																									
	<p>cable diameter approx. 5 ... 7 mm cable diameter approx. 7 ... 10 mm cable diameter approx. 10 ... 12 mm</p>	61 03 000 0141 61 03 000 0044 61 03 000 0143																																																							

Features

- Shielding bus separate from housing potential
- Perfect for transmission of sensitive signals (eg. bus signals)
- The four pole Han® Quintax contact is suitable for Ethernet Cat. 5e and PROFIBUS when diagonally wiring of the data pairs.

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	2
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Quintax contacts

Number of contacts	
- Quintax	4 + shielding
- High Density Quintax	8 + shielding

Electrical data	
acc. to EN 61 984	
- Quintax	10 A 50 V 0.8 kV 3
- High Density Quintax	5 A 50 V 0.8 kV 3
Rated current	10 A / 5 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3

Material	
- Insulator	polycarbonate
- Outer conductor	zinc alloy
Contact resistance	$\leq 4 \text{ m}\Omega$
Limiting temperatures	-40 °C ... +85 °C
Flammability acc. to UL 94	V 0
Outer surface finish	nickel
Cable diameter	3 ... 9.5 mm

Han D® contacts

Material	copper alloy
Surface	
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	$\leq 3 \text{ m}\Omega$
Crimp terminal	
- mm ²	0.14 ... 2.5 mm ²
- AWG	26 ... 14

D-Sub crimp contacts

Crimp terminal	
- mm ²	0.08 ... 0.52 mm ²
- AWG	28 ... 20

turned contacts Performance level 1

Number of contacts

2



Identification	Part number		Drawing	Dimensions in mm												
	Male insert (M)	Female insert (F)														
Module		09 14 002 3001	09 14 002 3101	M 	Dimensions in mm											
Quintax metal adapter option		09 14 000 9915	09 14 000 9915		Han Modular											
Identification	Wire gauge (mm ²)	Part number	Drawing	Dimensions in mm												
	Male contact	Female contact														
Quintax contact 4 + shielding Han D® crimp contacts		09 15 004 3013	09 15 004 3113													
Han D® Crimp contact gold plated	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6124 09 15 000 6123 09 15 000 6125 09 15 000 6122 09 15 000 6121 09 15 000 6126	09 15 000 6224 09 15 000 6223 09 15 000 6225 09 15 000 6222 09 15 000 6221 09 15 000 6226													
High Density Quintax contact 8 + shielding Han® D-Sub contacts		09 15 008 3013	09 15 008 3113													
D-Sub crimp contact	0.08-0.21 0.13-0.33 0.21-0.52	09 67 000 7576 09 67 000 5576 09 67 000 8576	09 67 000 7476 09 67 000 5476 09 67 000 8476	<table border="1"><thead><tr><th>Wire gauge</th><th>Stripping length</th></tr></thead><tbody><tr><td>0.08-0.21 mm²</td><td>AWG 28-24</td><td>4 mm</td></tr><tr><td>0.13-0.33 mm²</td><td>AWG 26-22</td><td>4 mm</td></tr><tr><td>0.21-0.52 mm²</td><td>AWG 24-20</td><td>4 mm</td></tr></tbody></table>	Wire gauge	Stripping length	0.08-0.21 mm ²	AWG 28-24	4 mm	0.13-0.33 mm ²	AWG 26-22	4 mm	0.21-0.52 mm ²	AWG 24-20	4 mm	
Wire gauge	Stripping length															
0.08-0.21 mm ²	AWG 28-24	4 mm														
0.13-0.33 mm ²	AWG 26-22	4 mm														
0.21-0.52 mm ²	AWG 24-20	4 mm														

Order crimp contacts separately

Stock items in bold type


Features

- Well known Quintax concept
- Suitable for contacts with large diameters
- Han E® coax is applicable to the ETCS Eurobalise cable

Technical characteristics

RF transmission characteristics

Impedance 75 Ω



Impedance 50 Ω

Han E® Coax with ETCS S21 Eurobalise cable (4 mm²)	27 MHz
Return loss [db]	35.4
Attenuation [db]	0.017

Han E® Coax with RG 213 cable (2.5 mm²)	200 MHz	500 MHz	1.0 GHz	1.2 GHz	1.5 GHz	2.0 GHz	2.5 GHz
Return loss [db]	23.8	21.1	>18.7	>17.7	>16.4	>14.1	>12.0
Attenuation [db]	0.07	0.11	0.17	0.2	<0.23	<0.53	<2.0

Inserts

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	

Coax contacts

Number of contacts	1 + shielding
Electrical data acc. to EN 61 984	
- Han D® Coax	10 A 50 V 0.8 kV 3
- Han E® Coax	16 A 50 V 0.8 kV 3
Rated current	10 A / 16 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Impedance	
- Han D® Coax	75 Ω
- Han E® Coax	50 Ω
Material	
- Insulator	polycarbonate
- Outer conductor	zinc alloy
Contact resistance	≤ 4 mΩ
Limiting temperatures	-40 °C ... +85 °C
Flammability acc. to UL 94	V 0
Outer surface finish	nickel
Cable diameter	3 ... 9.5 mm

Han D® contacts

Material	copper alloy
Surface	
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 3 mΩ
Crimp terminal	
- mm²	0.14 ... 2.5 mm²
- AWG	26 ... 14

Han E® contacts

Material	copper alloy
Surface	
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 1 mΩ
Crimp terminal	
- mm²	0.14 ... 5.5 mm²
- AWG	26 ... 10

Number of contacts

2

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Module	09 14 002 3001	09 14 002 3101	M F 	

Identification	Part number		Drawing	Dimensions in mm	
		Male contact	Female contact		
Han® D Coax contact 1 + shielding, 75 Ω				M 	
Han D® crimp contacts		09 15 001 3013	09 15 001 3113		
Han D® Crimp contact gold plated	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6124 09 15 000 6123 09 15 000 6125 09 15 000 6122 09 15 000 6121 09 15 000 6126	09 15 000 6224 09 15 000 6223 09 15 000 6225 09 15 000 6222 09 15 000 6221 09 15 000 6226	M 	F
Han® E Coax contact 1 + shielding, 50 Ω				M 	
Han E® crimp contacts		09 15 001 3023	09 15 001 3123		
Han E® contacts gold plated	0.14-0.37 0.5 0.75 1 1.5 2.5 4 5.5	09 33 000 6117 09 33 000 6122 09 33 000 6115 09 33 000 6118 09 33 000 6116 09 33 000 6123 09 33 000 6119 09 33 000 6139	09 33 000 6217 09 33 000 6222 09 33 000 6215 09 33 000 6218 09 33 000 6216 09 33 000 6223 09 33 000 6221 09 33 000 6239		

Order crimp contacts separately

Stock items in bold type

Features

- Suitable for FOC and coaxial contacts acc. to DIN 41 626
- Using of guiding pins (male and female) is imperative (see chapter 95).

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	4
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

<u>Coaxial contacts</u>	copper alloy
Material	
Surface	demand level 2
- hard-gold plated	$50 \Omega / 75 \Omega$
Impedance	
Contact resistance	
- Internal wire	$\leq 10 \text{ m}\Omega$
- Outer conductor	$\leq 3 \text{ m}\Omega$
Rated current	1.5 A
Rated voltage	50 V
 <u>F.O. contacts</u>	
Fibre type	Glas fibre (GI)
Attenuation	< 1.5 dB
 <u>F.O. contacts</u>	
Fibre type	Polymer Optical Fibre (POF)
Attenuation	< 2.5 dB


Contact arrangement according to following matrix

Contacts	Male insert (M) 09 14 004 4501	Female insert (F) 09 14 004 4512
Coaxial contacts	09 14 000 62xx	09 14 000 61xx
F.O. contacts	20 10 xxx 421x	20 10 xxx 422x

Coaxial cables (group 2)

Wires	Shell \varnothing	Internal wire \varnothing	Attenuation db/100 m at				
			mm	mm	100 MHz	200 MHz	800 MHz
50 Ω							
RG 174 / U	2.5	0.48					
RG 188 A / U	2.6	0.54	29		40		84
RG 316 / U	2.5	0.54			40		
75 Ω							
RG 179 B / U	2.55	0.3			41		
RG 187 A / U	2.7	0.3			41		

Assembly instructions



Solder temperature approx. 300 °C
Solder duration approx. 2 s

Due to the closed entry design of female insert the upper part has to be removed by screw driver (7 mm) before extracting the contacts. In this case the module will be destroyed.

Number of contacts

4

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Multi module acc. to DIN 41 626 Order contacts separately	09 14 004 4501	09 14 004 4512		

Contact arrangement view from termination side

Identification	Impedance	Part number	Drawing	Dimensions in mm
Coaxial contacts acc. to DIN 41 626*				
Solder / crimp contact	50 Ω 75 Ω	09 14 000 6211 09 14 000 6221	09 14 000 6111 09 14 000 6121	
				For cable group 2 flexible wires
F.O. contacts acc. to DIN 41 626 for SI fibre (HCS®) 200/230 µm		20 10 230 4211	20 10 230 4221	
for GI fibre 50/125 µm or 62.5/125 µm ceramic ferrule		20 10 125 4212	20 10 125 4222	
for 1 mm plastic fibre		20 10 001 4211	20 10 001 4221	

* Using of guiding pins is imperative (see chapter 95).

Features

- Suitable for coaxial contacts acc. to D-Sub (DIN 41 652)
- Using of guiding pins (male and female) is recommended (see chapter 95).

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Approvals



Inserts

Number of contacts	4
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Coaxial contacts

Material	copper alloy
Surface	- hard-gold plated
	Impedance demand level 2, S4 50 Ω / 75 Ω
Contact resistance	- Internal wire - Outer conductor
	$\leq 10 \text{ m}\Omega$ $\leq 3 \text{ m}\Omega$
Rated current	1.5 A
Rated voltage	50 V

Contact arrangement according to following matrix

Contacts	Male insert (M) 09 14 004 4501	Female insert (F) 09 14 004 4513
Coaxial contacts	09 14 000 62xx	09 14 000 61xx
Coaxial contacts	09 69 28x 5xxx	09 69 18x 5xxx

Number of contacts

4

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Multi module acc. to D-Sub Order contacts separately	09 14 004 4501	09 14 004 4513*	 Contact arrangement view from termination side	Han Modular

Identification	Impedance	Part number	Drawing	Dimensions in mm
Coaxial contacts acc. to D-Sub Performance level 2 Solder / solder contact	50 Ω	09 14 000 6215 09 14 000 6115		RG 58
Solder / crimp contact Performance level S4	50 Ω 50 Ω 50 Ω 75 Ω	09 69 281 5140 09 69 281 5141 09 69 281 5143 09 69 281 5230	09 69 181 5140 09 69 181 5141 09 69 181 5143 09 69 181 5230	RG 174 U, 188 AU, 316 U RG 178 BU, 196 AU, 404 U RG 58 CU, 141 AU RG 179 BU, 187 AU
Crimp / crimp terminal Performance level S4	50 Ω 75 Ω	09 69 282 5140 09 69 282 5230	09 69 182 5140 09 69 182 5230	RG 174 U, 188 AU, 316 U RG 179 BU, 187 AU

* Due to the closed entry design of female insert the upper part has to be removed by screw driver (7 mm) before extracting the contacts. In this case the module will be destroyed.

Features

- Suitable for FOC and coaxial contacts acc. to DIN 41 626
- Using of guiding pins (male and female) is imperative (see chapter 95).

Technical characteristics

Specifications

DIN EN 60 664-1
DIN EN 61 984

Inserts

Number of contacts	12
Insulation resistance	$\geq 10^{10} \Omega$
Material	polycarbonate
Limiting temperatures	-40 °C ... +125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Coaxial contacts

Material	copper alloy
Surface	
- hard-gold plated	demand level 2
Impedance	50 Ω / 75 Ω
Contact resistance	
- Internal wire	$\leq 10 \text{ m}\Omega$
- Outer conductor	$\leq 3 \text{ m}\Omega$
Rated current	1.5 A
Rated voltage	50 V

F.O. contacts

Fibre type	copper alloy
Attenuation	< 1.5 dB

F.O. contacts

Fibre type	polymer Optical Fibre (POF)
Attenuation	< 2.5 dB

Contact arrangement according to following matrix


Contacts	Male insert (M) 09 14 004 4501	Female insert (F) 09 14 004 4512
Coaxial contacts	09 14 000 62xx	09 14 000 61xx
F.O. contacts	20 10 xxx 421x	20 10 xxx 422x

Coaxial cables (group 2)


Wires	Shell ∅	Internal wire ∅	Attenuation db/100 m at				
			mm	mm	100 MHz	200 MHz	800 MHz
50 Ω							
RG 174 / U	2.5	0.48					
RG 188 A / U	2.6	0.54	29		40		84
RG 316 / U	2.5	0.54			40		
75 Ω							
RG 179 B / U	2.55	0.3			41		
RG 187 A / U	2.7	0.3			41		

Assembly instructions

Stripping de- scription



Assembly details for coaxial contacts



Solder temperature
Solder duration

approx. 300 °C
approx. 2 s

Due to the closed entry design of female insert the upper part has to be removed by screw driver before extracting the contacts.

Number of contacts

12



Identification	Part number Male insert (M)	Part number Female insert (F)	Drawing	Dimensions in mm
Multi module acc. to DIN 41 626 Order contacts separately	09 14 012 4501	09 14 012 4512		Contact arrangement view termination side

Identification	Impedance	Part number	Drawing	Dimensions in mm
Coaxial contacts acc. to DIN 41 626* Solder / crimp contact 	50 Ω 75 Ω	09 14 000 6211 09 14 000 6221 09 14 000 6111 09 14 000 6121		For cable group 2 flexible wires
F.O. contacts acc. to DIN 41 626* for SI fibre (HCS®) 200/230 µm 		20 10 230 4211 20 10 230 4221		
for GI fibre 50/125 µm or 62,5/125 µm ceramic ferrule		20 10 125 4212 20 10 125 4222		
for 1 mm plastic fibre		20 10 001 4211 20 10 001 4221		

* Usage of guiding pins is imperative (see chapter 95).

Features

- For the transmission of clean and dry compressed
- Female contacts with / without shut off
- Removal of tubes from pre-assembled pneumatic contacts is possible

Technical characteristics

Approvals



Inserts *

Number of contacts	2
Colour	blue
Material	polycarbonate
Limiting temperatures	-40 °C ... +80 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	delrin acetal
Colour	black
Tube termination - Internal diameter (ID)	6.0 mm / 1/4"
Working pressure	up to 8 bar / 116 psi

Sealing

Material	Buna-N
----------	--------

Shut off valve

Material	Polypropylen
----------	--------------

Shut off principle:


In the disconnected position the spring integrated in the female contact is active, thus the O-ring of the valve seals the opening of the air-way. During the mating process, when the defined depth of insertion is reached the male contact presses on the valve head and moves it backwards against the spring tension, so that the air-way opens.

Using of guiding pins in connection with pneumatic modules is imperative.

In addition to this guiding pins guarantee a coding, if pneumatic modules are used exclusively.

Number of contacts

2



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
for 6 mm Order contacts separately	09 14 002 4501*	09 14 002 4501*		
Pneumatic contacts without shut off for tube internal diameter (ID)	6.0	09 14 000 6174		
Pneumatic contacts with shut off for tube internal diameter (ID)	6.0	09 14 000 6274		
		09 14 000 6279		

* Using of guiding pins is imperative (see chapter 95).

Features

- For the transmission of clean and dry compressed
- Female contacts with / without shut off
- Removal of tubes from pre-assembled pneumatic contacts is possible

Technical characteristics

Approvals



Inserts *

Number of contacts	3
Colour	blue
Material	polycarbonate
Limiting temperatures	-40 °C ... +80 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	delrin acetal
Colour	black
Tube termination - Internal diameter (ID)	1.6 mm / 1/16"
	3.0 mm
	4.0 mm / 1/8"

Working pressure

up to 8 bar / 116 psi

Sealing

Material	Buna-N
----------	--------

Shut off valve

Material	Polypropylen
----------	--------------

Shut off principle:


In the disconnected position the spring integrated in the female contact is active, thus the O-ring of the valve seals the opening of the air-way. During the mating process, when the defined depth of insertion is reached the male contact presses on the valve head and moves it backwards against the spring tension, so that the air-way opens.

Using of guiding pins in connection with pneumatic modules is imperative.

In addition to this guiding pins guarantee a coding, if pneumatic modules are used exclusively.

Number of contacts

3



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
for 1.6; 3; 4 mm Order contacts separately	09 14 003 4501*	09 14 003 4501*	 Contact arrangement view from termination side	
Pneumatic contacts without shut off for tube internal diameter (ID)	1.6 3.0 4.0	09 14 000 6151 09 14 000 6152 09 14 000 6153	09 14 000 6251 09 14 000 6252 09 14 000 6253	
Pneumatic contacts with shut off for tube internal diameter (ID)	1.6 3.0 4.0		09 14 000 6256 09 14 000 6257 09 14 000 6258	

* Using of guiding pins is imperative (see chapter 95).

Features

- Suitable for HARTING SC contacts
- For GI-Fibre 50 - 62.5 / 125µm
- Using of guiding pins (male and female) is recommended (see chapter 95).

Technical characteristics

Approvals




Inserts

Number of contacts	4
Insertion loss	< 0.5 dB
Material	polycarbonate
Limiting temperatures	-40 °C ... +85 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Assembly instructions

Male insert (09 14 004 4701)




A Assemble the SC contact

Push the SC contact from the side into the relevant insert (1)
 Push the fixing plate from the side over the contacts (2)

B SC contact fixed in the module

Female insert (09 14 004 4711)




A Assemble the SC contact

Push the centering ferrule (included in delivery) on the SC contact (1)
 Push the SC contact from the side into the relevant insert (2)
 Push the fixing plate from the side over the contacts (3)

B SC contact fixed in the module

Number of contacts

4

Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
SC module Order contacts separately	09 14 004 4701	09 14 004 4711*	 Contact arrangement view from termination side	
Fixing plate	09 14 000 9965	09 14 000 9965		
Identification	Part number		Drawing	Dimensions in mm
	Male contact	Female contact		
SC contact	20 10 125 5211	20 10 125 5211		
for GI fibre 50/125 µm or 62,5/125 µm ceramic ferrule				
for SI fibre (HCS®) 200/230 µm	20 10 230 5211	20 10 230 5211		
with quick assembly technique for 1 mm POF	20 10 001 5217	20 10 001 5217		
with crimp technique for 1 mm POF	20 10 001 5211	20 10 001 5211		

* The female inserts are equipped with centering ferrules.
4 ferrules are included in delivery range.

Features

- Signal pre-processing and conversion do fit into the connector
- Individual combination of input and output modules for optimal signal pre-processing
- Minimum size for integration in Han® industrial connectors (Han-Modular® and Han-Snap®)
- Economy of space by reduction the number of terminal blocks and interface modules in the switch cabinet

Technical characteristics

Power supply (combination input and output module)

Supply voltage	24 V (-10 % ... +25 %)
Current consumption	< 0.08 A
Power consumption	< 2 W
Total transmission error	< 0.2 %

Han
Modular


General description

The Han-Elisa® modules are a flexible I/O system - directly in the connector.

The input and output modules are developed for 1 or 2 channels and can be combined variously and flexible for optimal signal pre-processing. Within the product family modules are available for current/voltage conversion, temperature, relay and timer.

Due to the minimized size these modules can be integrated into the Han-Modular® and Han-Snap® system.

Signal pre-processing and conversion do fit into the connector and this will reduce installation space for terminal blocks and the number of interface modules. So the switch cabinets can be made smaller.



Product matrix and possible combinations

input module (male)	output module (female)	Relay	Optocoupler	Output current 4 ... 20 mA	Output voltage 0 ... 10 V
Different versions	Different versions			galvanically isolated	galvanically isolated
Timing	○	○			
Connecting 1:1	○	○			
Temperature Pt100 Different temperature ranges				●	●
Temperature thermo element type J, K Different temperature ranges				○	○
Input current 4 ... 20 mA				○	○
Input voltage 0 ... 10 V				○	○

○ = on request

● = available

Features

- Minimum size for integration in Han® industrial connectors (Han-Modular® and Han-Snap®)
- Economy of space by reduction the number of terminal blocks and interface modules in the switch cabinet
- Male module for signal input

Technical characteristics

Inserts

Sensor	Pt100 acc. to IEC 751
Termination technology	2-, 3-, 4 wire technology
Sensor input current	0.8 mA, constant
Conductor resistance, max. permissible	10 Ω per conductor
Min. measuring range	100 °C
Open circuit detection	integrated

Material

Termination	polycarbonate / LCP
- mm²	Cage-clamp terminal
- AWG	0.14 ... 1.5 mm² 26 ... 16

Power diagnostic

LED (green)

Temperature range

Working temperature	-20 °C ... +65 °C
Stock temperature	-40 °C ... +85 °C



Pt100 Input module

Identification	Part number Male insert (M)	Drawing	Dimensions in mm
Temperature module Pt100	20 75 108 1101		
Measuring range	0 ... 100 °C 0 ... 200 °C	20 75 108 1101 20 75 108 1103	

Features

- Minimum size for integration in Han® industrial connectors (Han-Modular® and Han-Snap®)
- Economy of space by reduction the number of terminal blocks and interface modules in the switch cabinet
- Female module for signal output

Technical characteristics

Inserts

Supply voltage	24 V (-10 % ... +25 %)
Load I_{out}	$< 500 \Omega$
Load U_{out}	$\geq 10 \text{ k}\Omega$
Residual ripple	$< 20 \text{ mV} (500 \Omega)$
Step response (0 ... 99 %)	$< 30 \text{ ms}$

Material

Termination	polycarbonate / LCP
- mm ²	Cage-clamp terminal
- AWG	0.14 ... 1.5 mm ² 26 ... 16

Power diagnostic

LED (green)

Temperature range

Working temperature	-20 °C ... +65 °C
Stock temperature	-40 °C ... +125 °C



Output module

Identification	Part number Female insert (F)	Drawing	Dimensions in mm
Output module, current 3-ways-isolating amplifier; galvanically isolated	20 75 104 2201		
Output signal 4 ... 20 mA	20 75 104 2201		
Output module, voltage 3-ways-isolating amplifier; galvanically isolated	20 75 105 2201		
Output signal 0 ... 10 V	20 75 105 2201		

Han
Modular

Features

- Coding of tools possible (e.g. press tools) by means of an alphanumeric identification
- I²C bus EEPROM as memory medium
- Communication with PLC via conventional digital I/Os
- Physical connection of PLC by means of well-proven Han® contacts
- Assembly of the ID module to the device by means of a Han® industrial connector

Technical characteristics

Inserts

Supply voltage	24 V via digital I/O device
Electrical connector, 24 V	Han E® module (see page 06.52)
Memory capacity	max. 128 Byte
Material	polycarbonate
Working temperature	0 °C ... +70 °C
Stock temperature	0 °C ... +85 °C
Max. length recommended between I/O device and ID module	100 m *

General description

The HARTING connector identification module (ID module) is suitable for storing of data and for coding of connectors. It is integrated in a Han-Modular® standard E module.

The module can be connected to a 24 V digital I/O device of a PLC. Two digital inputs are used for detecting the module connection and the data input. Two digital outputs are used for the data output and the system clock. Furthermore the ID module must be connected with 24 V and GND. Communication is carried out with voltage levels of 24 V according to the I²C bus standard. The total memory capacity is 128 Byte, e.g. for storing part numbers to identify the module. It is also possible to store the start parameters or operating data for machine components.

A typical data structure is displayed in the following table:

Byte no.

16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
Check sum	Operating hours of tool				Start parameter of the unit				Part number of the unit						


Applications for the ID module can be found in modular machines and product lines. A great advantage of the ID module is the non volatile decentralized storing of e.g. operating data. When changing the location stored data can protect the machines from damages. In service cases of the equipment data can be analyzed to minimize service time.



Input module

Identification	Part number Male insert (M)	Drawing	Dimensions in mm
Electronic identification module	20 70 001 1001		Han Modular

Block diagram / Wiring plan



Meaning of the connections

Pin no.	Name	Meaning/Function
1	Data IN	Input for data and control signals from PLC
2	DC 24 V	Power connection of the ID module
3	Data OUT	Output for data signals from ID module to PLC
4	GND	Ground
5	CLK	System clock for synchronisation
6	Connection	Output of the ID module for connection detection

Identification	Part number	Drawing	Dimensions in mm
Han-Modular® Dummy module to fill up module spaces not in use in the frame 	09 14 000 9950		
Module clamp with strain relief 	09 14 000 0312		
Delivery comprises one module clamp.			1 For cable ties with max. 5 mm width
Module clamp for rail 	09 14 000 0313		
Delivery comprises one module clamp.			1 G-rail DIN EN 60 715-G32 2 rail DIN EN 60 715-35 x 7,5 with 1 mm thickness or -35 x 15 with 1,5 mm thickness 3 C-rail DIN EN 60 715-C30
Frame for 1 module in housing Han® 10 A 	09 14 000 0304		
			1 Distance max. 23,5 mm 2 Hoods 3 Housings