HARTING. The *One* for the Ethernet



Ethernet Solutions for Automation IT





Quality Connections Worldwide

HARTING was founded in 1945 by the family that still owns the company.

Today, HARTING employs approximately 2,000 people worldwide, including 150 qualified engineers. The sales team, including more than 100 sales engineers is in daily contact with our customers.

The company is one of the world's leading manufacturers of connectors, and currently have 34 subsidiary companies in Europe, the United States and Asia. In several product areas, HARTING is a market leader.


Great emphasis is placed on close links with customers, including the provision of a 'Just-in-Time'-Service to ensure rapid delivery to key customers.

HARTING products are designed and manufactured using the latest automated techniques, from CAD systems in the research and development department to automatic production techniques on the assembly lines.

Production and quality control is based on a 'zero-defect' philosophy which can only be reached by the continuous successful implementation of fully automated production techniques.

The organisation and procedures for quality assurance are based on the EN ISO 9001 standard.

A total of 60 engineers and other employees, most of whom are trained and qualified to standards laid down by the DGQ (German Association of Quality) or the SAQ (Swiss Association of Quality), are employed solely on quality-assurance activities.





HARTING is the only provider that you need for the Ethernet.

- HARTING has the competence and decisive innovation for the Ethernet and most importantly it has the right people as well. For example, HARTING supplies the complete network infrastructure for communication from the director's office to the machine with HARTING Automation IT, bringing together the worlds of industrial automation and office IT. And not just in theory, but in practice with manageable solutions. For the benefit of decision-makers, IT specialists, automation specialists and users.
- HARTING Automation IT is the answer to the requirements of top management in manufacturing companies: quality and process security, networking of value-added chains, worldwide diagnose and much more. The complete infrastructure from HARTING makes possible consistent communication and thus consistent quality management. In other words, HARTING Automation IT opens the door to the transparent factory.
- As such, HARTING is one of the first providers to take on the paradigm shift in industrial communications: with a universal Ethernet network that fulfills both automation and IT requirements. The full-range program from HARTING creates the infrastructure basis for using the Ethernet as an universal network for industrial IT and automation. From the connector all the way to active network components.
- Previously critical interfaces between the classic IT specialists from office IT and the generalists working in automation have been overcome. IT specialists do not need to handle automation, meaning no additional burden is placed on them. Automation technicians have less worries when it comes to the network's operating safety.
- The great practical benefit of HARTING Automation IT can be illustrated using a theoretical model. The office IT pyramid is migrating into the classic automation pyramid. This migration gives rise to a new world of products, solution and applications to HARTING Automation IT.

HARTING. One for the Ethernet

General information:

It is the customer's responsibility to check whether the components illustrated in this catalogue also comply with different regulations from those stated in special fields of applications.

We reserve substance of quality, kee cement or restated in special fields of applications.

We reserve the right to modify designs or substance of content in order to improve quality, keep pace with technological advancement or meet particular requirements in production.

No part of this catalogue may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed by means of electronic systems without the prior written consent of HARTING Electric GmbH & Co. KG, Espelkamp. We are bound by the German version only.

© HARTING Electric GmbH & Co. KG, Espelkamp – All rights reserved, including those of the translation.

Contents



HARTING. One for the Ethernet	Page
HARTING Automation IT	6
System overview	8
Ethernet Switch IP 30 - Inside	11
Ethernet Switch IP 65 / IP 67 - Outside	43
Ethernet Switch IP 20 / IP 67 - In-between	57
Industrial Outlet	77
Industrial Power Supply	83
Connectors and Cables	89

HARTING Automation IT



Universal Ethernet networks represent the future for communication in industrial automation.

Ethernet open up the possibility for barrierfree communications without artificial hurdles - from the office through to the machine.

In addition, utilising Ethernet offers the opportunity to supplement conventional fieldbus systems or even replace these with a universal network architecture.

HARTING is playing a decisive role in merging IT from both the office world and industrial automation:


HARTING Automation IT



The migration of office IT to industrial applications and the associated paradigm change is primarily being driven by the demands of top management in manufacturing companies. Anyone today with responsibility for a business simply expects quality and process reliability, the networking of value chains and a global diagnostics capability. HARTING makes the transparent factory possible – from the office through to the machine, even to the final customer. The foundation for this is a comprehensive infrastructure, company-wide quality management and company-wide communications. Together these ensure the high-level availability of the automation and office networks. When taking a close look at the HARTING Automation IT model, it will become clear

that until now there had been a critical interface to be overcome: classic IT specialists from the office world were on the one side of the equation and generalists from the world of automation were on the other. Both will have to move towards one another if a comprehensive solution to the challenge that Ethernet represents is to be found.

Knowledge of individual system landscapes is a basis for achieving the required products. These represent the abstract applications. What is more, it is only with this knowledge of the applications that suitable products can be developed.



Thus, for example, a line topology can be modified to an optimum to network an application in materials handling engineering.

An Ethernet switch with hybrid technology can be utilised to provide simple cabling of the line topology. In this sense, hybrid means realising the connections for data and 24 V DC voltage supply via a joint connector.

In an office environment, these HARTING Automation IT Ethernet switches can be managed by a central administration using SNMP protocol. If the necessity for real-time functionality and top-level availability is taken into consideration, then these can be achieved through the compatibility with various Ethernet protocols.


For example, these include PROFINET and Ethernet IP. This compatibility is required in all conformance classes.

HARTING Automation IT



Rated to IP 67, the Ethernet Switch is by design an optimum solution for use in completely decentralised applications in harsh industrial environments. The model 'In-between' is an optimum solution for integrating individual switchgear cabinets into a network. Ethernet switches sealed to IP 20 can be utilised in pure structures in a protected environment (for example in a switchgear cabinet).

HARTING has a solution for all of these requirements in a comprehensive family of switches.



Rapid access to the world-wide Ethernet network is guaranteed via the 'simple' Ethernet connector. This is where HARTING has set the standard world-wide by offering the IT specialists the usual performance and compatibility to the RJ45 as well as offering the automation engineer the usual simple connection technology common to fieldbus systems without having to forgo features such as robustness and top IP ratings.

HARTING's Industrial Outlets – basically Ethernet wall mounted sockets – from the point of view of data transmission and connection technology these function the same manner as in a normal IT environment and can, therefore, be utilised by IT specialists in communication networks without any problem – and the automation engineer can rely on the proverbial robustness common to all HARTING solutions.


The industry is known for different networking philosophies, which allows the customer to choose from a wide spectrum of connector solutions for IP 67 applications. This spectrum ranges from M12, D-coded circular connectors through to RJ45 connectors that fulfil individual user organisation specifications (for example, PROFINET and Ethernet IP). In IP 20, the RJ45 is offered across the board rating for twisted pair cabling in switchgear cabinets providing a protected environment.

There is no such unity to be seen for solutions for optical data transmissions in IP 20 environments. Whereas the LC connector is the most prevalent solution for office environments, the SCRJ connector is often preferred in industrial applications. The SCRJ is backwards compatible to the SC connector: most standard SC connectors can be used in conjunction with an SCRJ socket.

HARTING supports the spectrum of connectors defined for Ethernet in the standard for Structured Building Cabling (ISO/IEC 24 702) and the fieldbus standard (IEC 61 1918).



With HARTING Automation IT, HARTING is setting the standard for universal Ethernet networks in industry.



Connectors and System cables


















	HARTING Automation IT	HARTING
)		

Ethernet Switch IP 30 - Inside



Contents	Page
Ethernet Switch ESC TP08	13
Ethernet Switch ESC TP08-F	15
Ethernet Switch ESC TP06/FX02-SC	17
Ethernet Switch ESC TP08/FX02-SC	21
Ethernet Switch SmartCon - Introduction	25
ESC TP10-SmartCon	29
ESC TP08/FX02-SC-SmartCon	31
ESC TP06/FX03-SC-SmartCon	33
Ethernet Switch IP 30, managed - Introduction	35
ESC TP10-M, managed	37
ESC TP08/FX02-SC-M, managed	39
ESC TP06/FX03-SC-M, managed	41

	Ethernet Switch IP 30 - Inside	HARTING
2		

Ethernet Switch ESC TP08





Ethernet Switch IP 30


Advantages

- Small housing format
- Robust metal housing
- Adapted for mounting onto top hat mounting rail 35 mm according to EN 60 715
- RoHS compliant

General Description

The Ethernet switch ESC TP08 can be used in industrial environments and supports Ethernet (10 Mbit/s) and Fast Ethernet (100 Mbit/s). Up to 8 Ethernet devices can be connected via the RJ45-ports.

The Ethernet switch supports a simple and quickly network diagnostics with integrated LEDs at every port. It works as unmanaged switch in the Store and Forward switching mode and supports Auto-crossing, Auto-negotiation and Auto-polarity.



13

Ethernet Switch ESC TP08



Technical characteristics

Features • Auto-crossing

Auto-negotiation

Auto-polarity

· Store and Forward switching mode

Ethernet Interface

Number of ports • 8x 10/100Base-TX, unmanaged

Cable types acc. to IEEE 802.3 • Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data rate • 10/100 Mbit/s (RJ45)

Maximum cable length
 100 m (Twisted Pair; with cable Category 5 acc. to EN 50 173-1)

Terminating method • RJ45 (Twisted Pair)

Diagnostics (via LED) • Power supply

• Status Link - Green

• Status Data transfer (Act) - Green flashing

Data transfer rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Power Supply

Power supply 24 V DC Permissible range 12 V to 30 V

Current consumption 125 mA (at 24 V DC)

Terminating Power supply 3-pole pluggable contact (24 V; GND; PE)

Design features

Material of housing Sheet steel (grey painted)

Dimensions (W x H x D) 23 x 130 x 100 mm (without connectors)

Degree of protection IP 30

acc. to DIN 60 529

Environmental conditions

Operating temperature $0 \,^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ Storage temperature $-40 \,^{\circ}\text{C}$ to +85 $^{\circ}\text{C}$

Relative humidity 30 % to 95 % (non-condensing)

Approvals

cUL (in preparation)

Ethernet Switch ESC TP08-F





Ethernet Switch IP 30


Advantages

- · Flat housing format
- Robust metal housing
- Adapted for mounting onto top hat mounting rail 35 mm according to EN 60 715
- RoHS compliant

General Description

The Ethernet switch ESC TP08-F can be used in industrial environments and supports Ethernet (10 Mbit/s) and Fast Ethernet (100 Mbit/s). Up to 8 Ethernet devices can be connected via the RJ45-ports.

The Ethernet switch supports a simple and quickly network diagnostics with integrated LEDs at every port. It works as unmanaged switch in the Store and Forward switching mode and supports Auto-crossing, Auto-negotiation and Auto-polarity.



15

Ethernet Switch ESC TP08-F



Technical characteristics

Features • Auto-crossing

Auto-negotiationAuto-polarity

· Store and Forward switching mode

Ethernet Interface

Number of ports 8x 10/100Base-TX, unmanaged

Cable types acc. to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data rate 10/100 Mbit/s (RJ45)

Maximum cable length 100 m (Twisted Pair; with cable Category 5 acc. to EN 50 173-1)

Terminating method RJ45 (Twisted Pair)
Diagnostics (via LED) • Power supply

• Status Link - Green

· Status Data transfer (Act) - Green flashing

Data transfer rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Power Supply

Power supply 24 V DC
Permissible range 12 V to 30 V

Current consumption 125 mA (at 24 V DC)

Terminating Power supply 3-pole pluggable contact (24 V; GND; PE)

Design features

Material of housing Sheet steel (grey painted)

Dimensions (W x H x D) 130 x 23 x 100 mm (without connectors)

Degree of protection IP 30

acc. to DIN 60 529

Environmental conditions

Operating temperature $0 \,^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ Storage temperature $-40 \,^{\circ}\text{C}$ to +85 $^{\circ}\text{C}$

Relative humidity 30 % to 95 % (non-condensing)

Approvals

cUL (in preparation)





Ethernet Switch IP 30

Advantages

- Small housing
- · Robust metal housing
- Adapted for mounting onto top hat mounting rail according to EN 60 715
- Extended temperature range
- · RoHS compatible

General

The Ethernet switch ESC TP06/FX02-SC has been designed for use in industrial environments and supports Ethernet (10 Mbit/s) and Fast Ethernet (100 Mbit/s). The Ethernet switch can support linear, star and mixed topologies.

Up to 8 Ethernet devices can be connected: 6 to RJ45 and 2 to SC fibre optic ports (100 Base-FX; Full Duplex, SC connectors).

The Ethernet switch has quick and simple network diagnostics via integrated LEDs.

Identification	Part number	Drawing	Dimensions in mm
ESC TP06/FX02-SC Ethernet switch with 6 ports RJ Industrial 2 ports F.O.	20 76 108 3100	0E 27 0 0E 27 0E 2	

17



Technical characteristics

Features • Auto-crossing

Auto-negotiation

Auto-polarity

· Store and Forward switching mode

Power Supply

Power supply 24 V DC
Permissible range 12 V to 48 V

Current consumption max. 250 mA (at 24 V DC)
Terminating Power supply 2-pole pluggable contact

Diagnostics (via LED) Power supply

Ethernet Interface RJ45

Number of ports • 6x 10/100Base-TX, unmanaged

Cable types acc. to IEEE 802.3 • Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data rate • 10/100 Mbit/s

Maximum cable length • 100 m (Twisted Pair; with cable Category 5 according to

EN 50 173-1)

Terminating method • RJ45 (Twisted Pair)

Diagnostics (via LED) • Status Link - Green

· Data transfer (Act) - Green flashed

• Data transfer rate (Speed) - 100 Mbit/s: Yellow

10 Mbit/s: OFF

Topology Line, Star or mixed



Ethernet Interface - Fibre Optic

Number of ports 2x 100 Base-FX, unmanaged

Multimode-fibre, 1300 nm; 50 / 125 μ m or 62.5 / 125 μ m Cable types acc. to IEEE 802.3

SC-D female

Data rate 100 Mbit/s 2000 m Maximum cable length

Terminating method Diagnostics (LED) Status Link - green

Data transfer (Act) - green flashed

Wave length 1300 nm

• -14 dBm (50 / 125 μm) Transceive power TX max. (dynamic)

-14 dBm (62.5 / 125 μm)

Transceive power TX min. • -23.5 dBm (50 / 125 μm)

• -20 dBm (62.5 / 125 μm)


Receive power RX typical (dynamic) • -33.9 dBm (window)

• -35.2 dBm (centre)

Receive power RX max. (dynamic) -14 dBm

Signal detection (dynamic) -33 dBm

Topology Line, Star or mixed





Design features

Material of housing Steel panel (grey painted)

Dimensions (W x H x D) 23 x 130 x 100 mm (without F.O.)

Weight approx. 0.5 kg

Degree of protection IP 30

acc. to DIN 60 529

Mechanical solidness

Shock according to IEC 60 068-2-27

• 15 g

11 ms duration

Shock form: Half sinus

Vibration according EN 60 068-2-6

Rail-standard according EN 50 155, Class 1

Environmental conditions

Operating temperature $-10 \, ^{\circ}\text{C}$ to $+70 \, ^{\circ}\text{C}$ Storage temperature $-40 \, ^{\circ}\text{C}$ to $+85 \, ^{\circ}\text{C}$

Relative humidity 30 % to 95 % (non-condensing)

Approvals

cUL (in preparation)

EMC standards

Interference immunity ESD IEC 61 000-4-2
Interference immunity, HF radiated IEC 61 000-4-3
Interference immunity, Burst IEC 61 000-4-4
Interference immunity, Surge IEC 61 000-4-5
Interference immunity IEC 61 000-4-6
Emitted radiation EN 55 011, Class A
Rail-standard EN 50 121-3-2





Ethernet Switch IP 30

Advantages

- Small housing
- · Robust metal housing
- Adapted for mounting onto top hat mounting rail according to EN 60 715
- Extended temperature range
- · RoHS compatible

General

The Ethernet switch ESC TP08/FX02-SC has been designed for use in industrial environments and supports Ethernet (10 Mbit/s) and Fast Ethernet (100 Mbit/s). The Ethernet switch can support linear, star and mixed topologies.

Up to 10 Ethernet devices can be connected: 8 to RJ45 and 2 to SC fibre optic ports (100 Base-FX; Full Duplex, SC connectors).

The Ethernet switch has quick and simple network diagnostics via integrated LEDs.

Identification	Part number	Drawing	Dimensions in mm
ESC TP08/FX02-SC Ethernet switch with 8 ports RJ Industrial 2 ports F.O.	20 76 110 3100	01 02 01 02 03 00, 38	° []

21



Technical characteristics

Features • Auto-crossing

Auto-negotiation

Auto-polarity

· Store and Forward switching mode

Power Supply

Power supply 24 V DC
Permissible range 12 V to 48 V

Current consumption max. 250 mA (at 24 V DC)
Terminating Power supply 2-pole pluggable contact

Diagnostics (via LED) Power supply

Ethernet Interface RJ45

Number of ports 8x 10/100Base-TX, unmanaged

Cable types acc. to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data rate 10/100 Mbit/s

Maximum cable length 100 m (Twisted Pair; with cable Category 5 according to

EN 50 173-1)

Terminating method RJ45 (Twisted Pair)

Diagnostics (via LED) • Status Link - Green

· Data transfer (Act) - Green flashed

Data transfer rate (Speed) - 100 Mbit/s: Yellow

10 Mbit/s: OFF

Topology Line, Star or mixed



Technical characteristics

Ethernet Interface - Fibre Optic

Number of ports 2x 100 Base-FX, unmanaged

Multimode-fibre, 1300 nm; 50 / 125 μ m or 62.5 / 125 μ m Cable types acc. to IEEE 802.3

SC-D female

Data rate 100 Mbit/s 2000 m Maximum cable length

Terminating method Diagnostics (LED) Status Link - green

Data transfer (Act) - green flashed

Wave length 1300 nm

Transceive power TX max. (dynamic) -14 dBm (50 / 125 μm)

-14 dBm (62.5 / 125 μm)

Transceive power TX min. • -23.5 dBm (50 / 125 μm)

-20 dBm (62.5 / 125 μm)

Receive power RX typical (dynamic) • -33.9 dBm (window)

• -35.2 dBm (centre)


Receive power RX max. (dynamic) -14 dBm

Signal detection (dynamic)

Topology

-33 dBm

Line, Star or mixed





Technical characteristics

Design features

Material of housing Steel panel (grey painted)

Dimensions (W x H x D) 23 x 130 x 100 mm (without F.O.)

Weight approx. 0.5 kg

Degree of protection IP 30

acc. to DIN 60 529

Mechanical solidness

Shock according to IEC 60 068-2-27

• 15 g

11 ms duration

Shock form: Half sinus

Vibration according EN 60 068-2-6

Rail-standard according EN 50 155, Class 1

Environmental conditions

Operating temperature $-10 \, ^{\circ}\text{C}$ to $+70 \, ^{\circ}\text{C}$ Storage temperature $-40 \, ^{\circ}\text{C}$ to $+85 \, ^{\circ}\text{C}$

Relative humidity 30 % to 95 % (non-condensing)

Approvals

cUL (in preparation)

EMC standards

Interference immunity ESD IEC 61 000-4-2
Interference immunity, HF radiated IEC 61 000-4-3
Interference immunity, Burst IEC 61 000-4-4
Interference immunity, Surge IEC 61 000-4-5
Interference immunity IEC 61 000-4-6
Emitted radiation EN 55 011, Class A
Rail-standard EN 50 121-3-2



Introduction

For the user, HARTING's novel and innovative solutions open up new, more convenient and extensive options for configuring unmanaged Ethernet switches. The solutions available to date offered only very limited or basic options for making alterations to different settings on an Ethernet switch.

The user made changes to the settings or the configuration via the DIP switches on the Ethernet switch. The extensive possibilities for applications were physically restricted by the enormous space requirements of the mechanical solution.

Now for the first time, HARTING's SmartCon solution makes it possible for the user to rea-

lise configurations than have been possible to date.

Ease of handling and simple operation have been designed in to meet real-life application requirements. Simple and fast configuration is what this solution aims to achieve.

All SmartCon Ethernet switches can be configured via a USB connection cable.

At first sight, SmartCon Ethernet switches do not differ from the Ethernet switches available to date. However, the possibilities that Smart-Con has to offer become more than apparent to the user when he connects the Ethernet switch via the front-side USB socket to a PC, laptop or hand-held PC.



Figure 1 The Start-up menu

Once the SmartCon Ethernet switch has been connected to a PC, it can be accessed on-screen in much the same manner as a commercially available USB stick (figure 1: The Start-up menu).

The user only has to copy the SmartCon software in advance onto the respective PC. No administrator rights are required. The respective Ethernet switch does not have to be connected to a power supply for configu-

ration purposes. That means that the configuration procedure can take place at the user's location of choice: in the office, workshop or production facility. The SmartCon Ethernet switch automatically detects which power supply is connected: mains supply or power supply via the USB port. Please note that it is not possible to operate the Ethernet switch purely via the USB port. For normal industry operations, the power must be supplied via one of the redundant inputs.



Making configuration settings by means of DIP switches may appear to be uncomplicated. However, accidentally initiating an alteration to the configuration can happen more quickly than one would think possible, and in so doing make considerable changes to the previously set procedures. The SmartCon family prevents these inadvertent alterations to the configuration. No alteration can be made to the configuration without an USB connection and the software.

Each configuration can be archived and the back-ups retrieved for future projects. By making back-ups of the configuration, all settings can be conveniently stored in case servicing is

necessary.

Archived configurations can be imported and printed out when convenient. These extensive options in SmartCon ensure that data security enjoys the significance it deserves.

The switch configuration is transmitted only when a new configuration is uploaded via the corresponding 'Send' button. That means that until the data has actually been uploaded, it is still possible to read-in the 'old' data from the SmartCon Ethernet switch via the Refresh option. This means it is easily possible to reverse any inadvertent activation in the corresponding menu.



Figure 2 Example of a configuration

Once configured, the Ethernet switch can be utilised immediately. The configuration remains stored in the Ethernet switch after the USB cable is removed.

Meeting international standards, the USB port described is recognised as state-of-the-art technology. The standardised possibility for world-wide utilisation with all notebooks, PCs and Palmtops (revisions 1.0, 1.1 and 2.0) mean that this technology is suitable for universal usage. The intuitive, but extensive setting options via corresponding buttons and the various options

offered by SmartCon extend the range of applications for unmanaged Ethernet switches. With SmartCon, the gap between unmanaged and manageable switches is getting smaller.

It is true that SmartCon is a solution for unmanaged Ethernet switches; however, it comes very close to managed Ethernet switch functionality.



Ethernet Switch SmartCon

General description

Ethernet switches devide former collision domains into point-to-point connections between the network components and the user equipment involved. Constructing the network this way prevents collisions.

The Fast Ethernet switches of the type SmartCon allow up 10 items (depending upon used type) of user equipment to be connected through Shielded Twisted Pair cable or multimode fibres (50/125 μ m or 62.5/125 μ m) in accordance to IEC 802.3. The degree of protection, temperature range and mechanical stability provide high operating security and satisfy the toughest demands.

The Fast Ethernet switches of the type SmartCon from HARTING are designed for an industrial, effective and individual use.

A maximum of flexibility is warranted by the using of SmartCon.

Features

- Ethernet switch according to IEEE 802.3
- Store and Forward Switching Mode non blocking, unmanaged
- Auto-crossing, Auto-negotiation, Auto-polarity
- For Ethernet (10 Mbit/s) and Fast Ethernet (100 Mbit/s)
- Diagnostics LEDs (Link status, Act, Data transmission rate, Power, Error)
- Following settings are adjustable via USB port:
 - o Alarm signalling contact
 - o Auto-negotiation
 - o 10/100 Mbit/s
 - o Full/Half Duplex
 - o Parallel redundancy
 - Ports enable/disenable
 - Priority Handling

Advantages

- · Individual configurable via USB port
- Robust metal housing
- EMC, temperature range and mechanical stability for the toughest demands

Application fields

- Industrial automation
- Power distribution systems
- Automotive industry
- Mechanical engineering



Technical characteristics

Features • Auto-crossing

Auto-negotiationAuto-polarity

Store and Forward Switching Mode

Design features

Material of housing Metal (coated)

Dimension (W x H x D) 59 x 104 x 132 mm (without connectors)

Degree of protection IP 30

according to DIN 60 529

Mounting
 35 mm top hat mounting rail according to EN 60 715

Wall mounting, vertical

Weight approximately 0.6 kg

Environmental conditions

Operating temperature $0 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ Storage temperature $-40 \,^{\circ}\text{C}$ to $+85 \,^{\circ}\text{C}$

Relative humidity 30 % to 95 % (non-condensing)

Mechanical solidness

 Shock
 IEC 60 068-2-27

 Vibration
 IEC 60 068-2-6

 Rail-standard
 EN 50 155, Class 1

EMC

Interference immunity ESD IEC 61 000-4-2
Interference immunity HF, radiated IEC 61 000-4-3
Interference immunity Burst IEC 61 000-4-4
Interference immunity Surge IEC 61 000-4-5
Interference immunity IEC 61 000-4-5
Emitted radiation EN 55 011, Class A

Approvals

cUL (in preparation)

ESC TP10-SmartCon





ESC TP10-SmartCon RJ45

Identification Part number Drawing Dimensions in mm ESC TP10-SmartCon Ethernet switch 20 76 110 1000 10 ports RJ45 including set for assembly onto top hat mounting rail

ESC TP10-SmartCon



Technical characteristics

Features • Auto-crossing

Auto-negotiationAuto-polarity

· Store and Forward Switching Mode

Parallel redundancyPort priorisation

Ethernet Interface

Number of ports 10x 10/100Base-TX, unmanaged

Cable types according to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data transmission rate 10 Mbit/s or 100 Mbit/s (RJ45)

Maximum cable length 100 m (Twisted Pair; with cable Categorie 5 according to EN 50 173-1)

Termination RJ45 (Twisted Pair)
Diagnostics (LED) • Status Link - Green

• Status data transfer (Act) - Green flashing

Data transmission rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Power supply

Power supply 24 V DC Permissible range 18 V to 30 V

Input current 250 mA (at 24 V DC)

Termination power supply 5-pole pluggable screw contact, for redundant power supply

Diagnostics (LED) Power supply

Alarm signalling contact Change-over contact, potential-free, 24 V DC / 0.5 A

3-pole pluggable screw contact

ESC TP08/FX02-SC-SmartCon





ESC TP08/FX02-SC-SmartCon RJ45 / SC

Identification Part number Drawing Dimensions in mm ESC TP08/FX02-SC-SmartCon 20 76 110 1100 Ethernet switch 8 ports RJ45 2 ports SC including set for assembly onto top hat mounting rail

ESC TP08/FX02-SC-SmartCon



Technical characteristics

Features • Auto-crossing

Auto-negotiationAuto-polarity

· Store and Forward Switching Mode

Parallel redundancyPort priorisation

Ethernet Interface RJ45

Number of ports 8x 10/100Base-TX, unmanaged

Cable types according to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data transmission rate 10 Mbit/s or 100 Mbit/s

Maximum cable length 100 m (Twisted Pair; with cable Categorie 5 according to EN 50 173-1)

Termination RJ45 (Twisted Pair)
Diagnostics (LED) • Status Link - Green

· Status data transfer (Act) - Green flashing

Data transmission rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Ethernet Interface F.O.

Number of ports 2, unmanaged

Cable types according to IEEE 802.3 Multimode fibre, 50 / 125 μm or 62.5 / 125 μm

Data transmission rate 100 Mbit/s

Maximum cable length 2000 m

Termination SC-D female

Wave length 1300 nm

Diagnostics (LED) • Status Link - Green

· Status data transfer (Act) - Green flashing

Topology Line, Star or mixed

Power supply

Power supply 24 V DC
Permissible range 18 V to 30 V

Input current 250 mA (at 24 V DC)

Termination power supply 5-pole pluggable screw contact, for redundant power supply

Diagnostics (LED) Power supply

Alarm signalling contact Change-over contact, potential-free, 24 V DC / 0.5 A

3-pole pluggable screw contact

ESC TP06/FX03-SC-SmartCon





ESC TP06/FX03-SC-SmartCon RJ45 / SC

Identification Part number Drawing Dimensions in mm ESC TP06/FX03-SC-SmartCon 20 76 109 1100 Ethernet switch 6 ports RJ45 3 ports SC including set for assembly onto top hat mounting rail

ESC TP06/FX03-SC-SmartCon



Technical characteristics

Features • Auto-crossing

Auto-negotiationAuto-polarity

· Store and Forward Switching Mode

Parallel redundancyPort priorisation

Ethernet Interface RJ45

Number of ports 6x 10/100Base-TX, unmanaged

Cable types according to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data transmission rate 10 Mbit/s or 100 Mbit/s

Maximum cable length 100 m (Twisted Pair; with cable Categorie 5 according to EN 50 173-1)

Termination RJ45 (Twisted Pair)
Diagnostics (LED) • Status Link - Green

· Status data transfer (Act) - Green flashing

Data transmission rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Ethernet Interface F.O.

Number of ports 3, unmanaged

Cable types according to IEEE 802.3 Multimode fibre, 50 / 125 μm or 62.5 / 125 μm

Data transmission rate 100 Mbit/s

Maximum cable length 2000 m

Termination SC-D female

Wave length 1300 nm

Diagnostics (LED) • Status Link - Green

• Status data transfer (Act) - Green flashing

Topology Line, Star or mixed

Power supply

Power supply 24 V DC
Permissible range 18 V to 30 V

Input current 350 mA (at 24 V DC)

Termination power supply 5-pole pluggable screw contact, for redundant power supply

Diagnostics (LED) Power supply

Alarm signalling contact Change-over contact, potential-free, 24 V DC / 0.5 A

3-pole pluggable screw contact

Ethernet Switch IP 30, managed - Introduction



Fast Ethernet Switch, managed for industrial applications

General description

Ethernet switches devide former collision domains into point-to-point connections between the network components and the user equipment involved. Constructing the network this way prevents collisions.

The managed Fast Ethernet switches (IP 30) of HARTING allow up 10 items (depending upon used type) of user equipment to be connected through Shielded Twisted Pair cable or multimode fibres (50 / 125 μ m or 62.5 / 125 μ m) in accordance to IEC 802.3. The degree of protection, temperature range and mechanical stability provide high operating security and satisfy the toughest demands.

The Fast Ethernet switches ESC TPxxM from HARTING are designed for an industrial, effective and individual use. They provide two alternative access methods for the management: SNMP and a comfortable web access.

Application fields



- Industrial automation
- Automotive industry
- Wind power
- Power distribution systems

Advantages

- Robust metal housing
- EMC, temperature range and mechanical stability for the toughest demands
- Management functions integrated

Technical characteristics

- Ethernet switch according to IEEE 802.3
- Store and Forward Switching mode
- up to 10 ports, managed, non-blocking
- Auto-crossing, Auto-negotiation, Auto-polarity

Ethernet Switch IP 30, managed - Introduction



Management

Web-based access with password protection

- Status overview
- Port Settings
- Network Configuration
- Password settings
- Alarm Settings
- Diagnostics
- Parameter Import / Export
- Firmware Import / Export

SNMP Agent

- SNMP V1 and SNMP V3
- MIB II objects:
 - TCP/IP
 - UDP
 - System
 - Interface
 - IP
 - ICMP
 - SNMP
- HARTING MIB

Additional services

- DHCP
- DNS
- E-Mail
- · Parameter and firmware import and export via TFTP
- System time via SNTP
- Service Mode via port 1

Diagnostics

- LEDs for Power, Link, Status, Data transmission and Fault
- Port diagnostic
- Port mirroring
- History
- Alarms via signalling contact and / or E-Mail

ESC TP10-M, managed





ESC TP10-M, managed RJ45

Identification	Part number	Drawing	Dimensions in mm
ESC TP10-M Ethernet switch, managed 10 ports RJ45 including set for assembly onto top hat mounting rail	20 76 110 4000	130	

ESC TP10-M, managed



Technical characteristics

Features • Auto-crossing

Auto-negotiationAuto-polarity

· Store and Forward Switching Mode

full managed

Ethernet Interface

Number of ports 10x 10/100Base-TX

Cable types according to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data transmission rate 10 Mbit/s or 100 Mbit/s (RJ45)

Maximum cable length 100 m (Twisted Pair; with cable Categorie 5 according to EN 50 173-1)

Termination RJ45 (Twisted Pair)
Diagnostics (LED) • Status Link - Green

Status data transfer (Act) - Green flashing

Data transmission rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Power supply

Power supply 24 V DC
Permissible range 18 V to 30 V

Input current 250 mA (at 24 V DC)

Termination power supply 5-pole pluggable screw contact, for redundant power supply

Diagnostics (LED) Power supply

Alarm signalling contact Change-over contact, potential-free, 24 V DC / 0.5 A

3-pole pluggable screw contact

ESC TP08/FX02-SC-M, managed





ESC TP08/FX02-SC-M, managed RJ45 / SC

Identification Part number Drawing Dimensions in mm ESC TP08/FX02-SC-M 20 76 110 4100 Ethernet switch, managed 8 ports RJ45 2 ports SC including set for assembly onto top hat mounting rail

ESC TP08/FX02-SC-M, managed



Technical characteristics

Features • Auto-crossing

Auto-negotiationAuto-polarity

· Store and Forward Switching Mode

full managed

Ethernet Interface RJ45

Number of ports 8x 10/100Base-TX, unmanaged

Cable types according to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data transmission rate 10 Mbit/s or 100 Mbit/s

Maximum cable length 100 m (Twisted Pair; with cable Categorie 5 according to EN 50 173-1)

Termination RJ45 (Twisted Pair)
Diagnostics (LED) • Status Link - Green

Status data transfer (Act) - Green flashing

Data transmission rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Ethernet Interface F.O.

Number of ports 2

Cable types according to IEEE 802.3 Multimode fibre, 50 / 125 µm or 62.5 / 125 µm

Data transmission rate 100 Mbit/s

Maximum cable length 2000 m

Termination SC-D female

Wave length 1300 nm

Diagnostics (LED) • Status Link - Green

• Status data transfer (Act) - Green flashing

Topology Line, Star or mixed

Power supply

Power supply 24 V DC
Permissible range 18 V to 30 V

Input current 250 mA (at 24 V DC)

Termination power supply 5-pole pluggable screw contact, for redundant power supply

Diagnostics (LED) Power supply

Alarm signalling contact Change-over contact, potential-free, 24 V DC / 0.5 A

3-pole pluggable screw contact

ESC TP06/FX03-SC-M, managed





ESC TP06/FX03-SC-M, managed RJ45 / SC

Identification	Part number	Drawing	Dimensions in mm
ESC TP06/FX03-SC-M Ethernet switch, managed 6 ports RJ45 3 ports SC including set for assembly onto top hat mounting rail	20 76 109 4100	100	

ESC TP06/FX03-SC-M, managed



Technical characteristics

Features Auto-crossing

 Auto-negotiation Auto-polarity

· Store and Forward Switching Mode

full managed

Ethernet Interface RJ45

Number of ports 6x 10/100Base-TX

Cable types according to IEEE 802.3 Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP),

Category 5

Data transmission rate 10 Mbit/s or 100 Mbit/s

100 m (Twisted Pair; with cable Categorie 5 according to EN 50 173-1) Maximum cable length

Termination RJ45 (Twisted Pair) Diagnostics (LED) Status Link - Green

Status data transfer (Act) - Green flashing

Data transmission rate (Speed) - 100 Mbit/s: Yellow / 10 Mbit/s: OFF

Topology Line, Star or mixed

Ethernet Interface F.O.

Number of ports 3, managed

Cable types according to IEEE 802.3 Multimode fibre, 50 / 125 µm or 62.5 / 125 µm

Data transmission rate 100 Mbit/s 2000 m Maximum cable length **Termination** SC-D female Wave length 1300 nm

Status Link - Green Diagnostics (LED)

· Status data transfer (Act) - Green flashing

Topology Line, Star or mixed

Power supply

24 V DC Power supply 18 V to 30 V Permissible range

Input current 350 mA (at 24 V DC)

Termination power supply 5-pole pluggable screw contact, for redundant power supply

Diagnostics (LED) Power supply

Alarm signalling contact Change-over contact, potential-free, 24 V DC / 0.5 A

3-pole pluggable screw contact

Ethernet Switch IP 65 / IP 67 - Outside



Contents	Page
ESC 67-10 TP10U M12 D-coding	45
Ethernet Switch, managed - Introduction	47
ESC 67-10 TP05M HARTING RJ Industrial® IP 67 Data 3A	49
ESC 67-10 TP05M M12 D-coding	51
ESC 67-10 TP10M HARTING RJ Industrial® IP 67 Data 3A	53
ESC 67-10 TP10M M12 D-coding	55

Ethernet Switch IP 65 / IP 67 - Outside	HARTING

ESC 67-10 TP10U M12 D-coding





ESC 67-10 TP10U M12 M12 D-coding

Identification	Part number	Drawing	Dimensions in mm
ESC 67-10 TP10U Ethernet switch M12 D-coding	20 70 310 3941		90

Technical characteristics

Power supply

Input voltage 24 V DV (16,8 ... 30 V DV)

Current consumption approx. 180 mA (at 24 V DC)

Connections Compatible with circular connector, A-coding, redundant power supply

Ethernet Interface

Ports 10

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device Pluggable with connectors M12 D-coding

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 90 x 120 x 87 mm (without connectors)

Mounting Panel mounting, upright or flat assembly; mounting onto top hat mounting rail

35 mm according to DIN EN 60 715

Weight approx. 1.4 kg

ESC 67-10 TP10M M12 D-coding



Identification			Part num Power termination	nber Ethernet terminatio	n
HARAX® M12-L circular connector female, A-coding			21 03 212 2305		
HARAX® M12-L circular connector shielded, 4-wires, male, D-coding				21 03 281 1405	
Protection cover M12			21 01 000 0003	21 01 000 0003	
Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m	21 03 483 1401 21 03 483 1403 21 03 483 1405 21 03 483 1400 ¹⁾	Connectors: 2	ndustrial Ethernet Star able, x2 x AWG 26 / 0,14 m x circular connectors 112 D-coding, straight
	Length:	1 m 3 m 5 m	21 03 485 1401 21 03 485 1403 21 03 485 1405 21 03 485 1400 ¹⁾	c c 2 Connectors: 2	ndustrial Ethernet Star able, x2 x AWG 22 / 0,34 m x circular connectors 112 D-coding, straight
Identification			Part number	Drawing	Dimensions in
Set for wall mounting vertical assembly			20 80 010 0002		95.5

Ethernet Switch, managed - Introduction



Fast Ethernet Switch, managed for industrial applications

General description

Ethernet switches devide former collision domains into point-to-point connections between the network components and the user equipment involved. Constructing the network this way prevents collisions.

The managed Fast Ethernet switches of the type ESC 67-x0 TPxxM allow up 10 items (depending upon used type) of user equipment to be connected through Shielded Twisted Pair cable in accordance to IEC 802.3. The degree of protection, temperature range and mechanical stability satisfy the toughest demands. The Fast Ethernet Switche can therefore be directly used in industrial environments.

The Fast Ethernet switches ESC 67-x0 TPxxM from HARTING provides two alternative access methods for the management:

SNMP and a comfortable web access.

Application fields



- Industrial automation
- · Automotive industry
- Wind power
- Power distribution systems

Advantages

- High degree of protection IP 65 / IP 67
- Robust metal housing, zinc die-cast
- · Can be used directly in industrial environments
- EMC, temperature range and mechanical stability for the toughest demands
- Management functions integrated

Technical characteristics

- Ethernet switch according to IEEE 802.3
- Store and Forward Switching mode
- 5 or 10 ports, managed, non-blocking
- Auto-crossing, Auto-negotiation, Auto-polarity

Ethernet Switch, managed - Introduction



Management

Web-based access with password protection

- Status overview
- Port Settings
- Network Configuration
- Password settings
- Alarm Settings
- Diagnostics
- Parameter Import / Export
- Firmware Import / Export

SNMP Agent

- SNMP V1 and SNMP V3
- MIB II objects:
 - TCP/IP
 - UDP
 - System
 - Interface
 - IP
 - ICMP
 - SNMP
- HARTING MIB

Additional services

- DHCP
- DNS
- E-Mail
- · Parameter and firmware import and export via TFTP
- System time via SNTP
- Service Mode via port 1

Diagnostics

- LEDs for Power, Link, Status, Data transmission and Fault
- Port diagnostic
- Port mirroring
- History
- Alarms via signalling contact and / or E-Mail

ESC 67-10 TP05M HARTING RJ Industrial® IP 67 Data 3A





ESC 67-10 TP05M HARTING RJ Industrial® IP 67 Data 3A

Identification	Part number	Drawing	Dimensions in mm
ESC 67-10 TP05M Ethernet switch, managed HARTING RJ Industrial® IP 67 Data 3A	20 70 305 4921	120	45

Technical characteristics

Power supply

Input voltage 24 V DV (16,8 ... 30 V DV)

Current consumption max 160 mA (at 24 V DC)

Connections Compatible with Han® 4 A connector, redundant power supply

(incl. fixing srew 09 20 000 9918, to maintain IP 67)

Ethernet Interface

Ports 5

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device Pluggable with connectors HARTING RJ Industrial[®] Data 3A

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 45 x 120 x 87 mm (without connectors)

Mounting Panel mounting, upright or flat assembly; mounting onto top hat mounting rail

35 mm according to DIN EN 60 715

Weight approx. 0.8 kg

ESC 67-10 TP05M HARTING RJ Industrial® IP 67 Data 3A



Identification		Part num Power termination	ber Ethernet termina	ation
Hood metal, straight, metric		19 20 003 1440 ¹⁾		
Protection cover Han® 3 A		09 20 003 5422	09 20 003 542	5
Han® 4 A female insert		09 20 004 2711		
Cable gland metal IP 65, metric M20, cable diameter: 5 9	mm	19 00 000 5080		
Connector set HARTING RJ Industrial [®] IP 67 Data 3 A in metal			09 45 115 1100	0
Coding pin set			09 45 820 000	0
Identification		Part number		
System cables for Length: Industrial Ethernet, pre-assembled at both ends metal, IP 65 / IP 67 (when mated)	1.5 m 3.0 m 5.0 m 10.0 m 20.0 m 50.0 m 100.0 m	09 45 715 1123 09 45 715 1123	Cable type: Connectors:	Industrial Ethernet Stand cable, 2x2 x AWG 22/1, double shielding 2x HARTING RJ Industri IP 67 Data 3A in metal w IDC fast termination technology
Identification		Part number	Drawing	Dimensions in ı
Set for assembly on standard rail 35 mm according to DIN EN 60 715				
		20 80 000 0003		
Set for wall mounting vertical assembly		20 80 000 0003		
_				

ESC 67-10 TP05M M12 D-coding





ESC 67-10 TP05M M12 M12 D-coding

Identification	Part number	Drawing	Dimensions in mm
ESC 67-10 TP05M Ethernet switch, managed M12 D-coding	20 70 305 4941	95 93	45

Technical characteristics

Power supply

Input voltage 24 V DV (16,8 ... 30 V DV)

Current consumption max 160 mA (at 24 V DC)

Connections Compatible with circular connector, A-coding, redundant power supply

Ethernet Interface

Ports

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device Pluggable with connectors M12 D-coding

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 45 x 120 x 87 mm (without connectors)

Mounting Panel mounting, upright or flat assembly; mounting onto top hat mounting rail

35 mm according to DIN EN 60 715

Weight approx. 0.8 kg

ESC 67-10 TP05M M12 D-coding



Identification			Part num Power termination	nber Ethernet termination	1
HARAX® M12-L circular connector female, A-coding			21 03 212 2305		
HARAX® M12-L circular connector shielded, 4-wires, male, D-coding				21 03 281 1405	
Protection cover M12			21 01 000 0003	21 01 000 0003	
Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m	21 03 483 1401 21 03 483 1403 21 03 483 1405 21 03 483 1400 ¹⁾	Connectors: 23	dustrial Ethernet Stand able, <2 x AWG 26 / 0,14 mm < circular connectors 12 D-coding, straight
	Length:	1 m 3 m 5 m	21 03 485 1401 21 03 485 1403 21 03 485 1405 21 03 485 1400 ¹⁾	Connectors: 25	dustrial Ethernet Stand able, <2 x AWG 22 / 0,34 mm < circular connectors 12 D-coding, straight
Identification			Part number	Drawing	Dimensions in r
Set for assembly on standard rail 39 according to DIN EN 60 715	5 mm		20 80 000 0003		
Set for wall mounting vertical assembly			20 80 010 0001		
Set for wall mounting flat assembly			20 80 024 0002		
				6	

ESC 67-10 TP10M HARTING RJ Industrial® IP 67 Data 3A





ESC 67-10 TP10M HARTING RJ Industrial® IP 67 Data 3A

Identification	Part number	Drawing	Dimensions in mm
ESC 67-10 TP10M Ethernet switch, managed HARTING RJ Industrial® IP 67 Data 3A	20 70 310 4921		

Technical characteristics

Power su	pply	
----------	------	--

Input voltage 24 V DV (16,8 ... 30 V DV)

Current consumption approx. 260 mA (at 24 V DC)

Connections Compatible with Han® 4 A connector, redundant power supply

(incl. fixing srew 09 20 000 9918, to maintain IP 67)

Ethernet Interface

Ports 10

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device Pluggable with connectors HARTING RJ Industrial[®] Data 3A

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 90 x 120 x 87 mm (without connectors)

Mounting Panel mounting, upright or flat assembly; mounting onto top hat mounting rail

35 mm according to DIN EN 60 715

Weight approx. 1.4 kg

ESC 67-10 TP10M HARTING RJ Industrial® IP 67 Data 3A



Identification		Part num Power termination	ber Ethernet terminatio	on
Hood metal, straight, metric		19 20 003 1440 ¹⁾		
Protection cover Han® 3 A		09 20 003 5422	09 20 003 5425	
Han® 4 A female insert		09 20 004 2711		
Cable gland metal IP 65, metric M20, cable diameter: 5 9	mm	19 00 000 5080		
Connector set HARTING RJ Industrial [®] IP 67 Data 3 A in metal			09 45 115 1100	
Coding pin set			09 45 820 0000	
Identification		Part number		
System cables for Length: Industrial Ethernet, pre-assembled at both ends metal, IP 65 / IP 67 (when mated)	1.5 m 3.0 m 5.0 m 10.0 m 20.0 m 50.0 m 100.0 m	09 45 715 1123 09 45 715 1123	Connectors: 2	ndustrial Ethernet Stan cable, 2x2 x AWG 22/1, double shielding ex HARTING RJ Industr P 67 Data 3A in metal v DC fast termination echnology
Identification		Part number	Drawing	Dimensions in
Set for wall mounting vertical assembly		20 80 010 0002		
_		20 80 010 0002		

ESC 67-10 TP10M M12 D-coding





ESC 67-10 TP05M M12 M12 D-coding

Identification	Part number	Drawing	Dimensions in mm
ESC 67-10 TP10M Ethernet switch, managed M12 D-coding	20 70 310 4941		90

Technical characteristics

Power supply

Input voltage 24 V DV (16,8 ... 30 V DV)

Current consumption approx. 260 mA (at 24 V DC)

Connections Compatible with circular connector, A-coding, redundant power supply

Ethernet Interface

Ports 10

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device Pluggable with connectors M12 D-coding

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 90 x 120 x 87 mm (without connectors)

Mounting Panel mounting, upright or flat assembly; mounting onto top hat mounting rail

35 mm according to DIN EN 60 715

Weight approx. 1.4 kg

ESC 67-10 TP10M M12 D-coding




Identification			Part num Power termination	ber Ethernet terminatio	n
HARAX® M12-L circular connector female, A-coding			21 03 212 2305		
HARAX® M12-L circular connector shielded, 4-wires, male, D-coding				21 03 281 1405	
Protection cover M12			21 01 000 0003	21 01 000 0003	
Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m	21 03 483 1401 21 03 483 1403 21 03 483 1405 21 03 483 1400 ¹⁾	Connectors: 2	ndustrial Ethernet Standable, able, x2 x AWG 26 / 0,14 mr x circular connectors 112 D-coding, straight
	Length:	1 m 3 m 5 m	21 03 485 1401 21 03 485 1403 21 03 485 1405 21 03 485 1400 ¹⁾	Connectors: 2	ndustrial Ethernet Stand able, x2 x AWG 22 / 0,34 mn x circular connectors 112 D-coding, straight
Identification			Part number	Drawing	Dimensions in
Set for wall mounting vertical assembly			20 80 010 0002		35.5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Ethernet Switch IP 20 / IP 67 - In-between



Contents	Page
ESC 67-30 TP08U HARTING RJ Industrial® IP 67 Data 3A	59
ESC 67-30 TP08U M12 D-coding	61
ESC 67-30 TP08U HARTING RJ Industrial® Hybrid	63
Ethernet Switch In-between, managed - Introduction	67
ESC 67-30 TP05M HARTING RJ Industrial® IP 67 Data 3A	69
ESC 67-30 TP05M M12 D-coding	71
ESC 67-30 TP08M HARTING RJ Industrial® IP 67 Data 3A	73
ESC 67-30 TP08M M12 D-coding	75



ESC 67-30 TP08U HARTING RJ Industrial® IP 67 Data 3A











Identification Part number Dimensions in mm Drawing 105 86,5 ESC 67-30 TP08U Ethernet switch 20 73 308 3921 HARTING RJ Industrial® IP 67 Data 3A 86 14,1

Technical characteristics

Power supply

Input voltage 24 V DV (18 ... 30 V DV) Current consumption approx. 140 mA (at 24 V DC)

Screw terminal with 5 contacts, plug-in, for redundant power supply Connections

(on the inside of control cabinet)

Change-over contact, potential-free, 24 V DC / 0.5 A (on the inside of cabinet) Alarm signal contact

Screw terminal with 3 contacts, pluggable

Ethernet Interface

8 (2x IP 65 / 6x IP 20) **Ports**

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

On the outside of control cabinet: 2x connectors HARTING RJ Industrial® Available device

IP 67 Data 3A

On the inside of control cabinet 6x RJ45 connectors Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 105 x 40 x 105 mm (without connectors)

Directly on control cabinets and terminal boxes Mounting

Weight approx. 0.6 kg


ESC 67-30 TP08U HARTING RJ Industrial® IP 67 Data 3A



Identification	Part number
Connector set HARTING RJ Industrial® IP 67 Data 3A, metal	09 45 115 1100
Coding pin set	09 45 820 000
Mounting plate to the inside of control cabinet	20 80 000 0004

Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m 10 m 20 m 50 m	09 45 715 1123 09 45 715 1125 09 45 715 1127 09 45 715 1151 09 45 715 1153 09 45 715 1156 09 45 715 1161	Cable type: Connectors:	Industrial Ethernet standard cable, 2x2 x AWG 22/1 double shielding 2x HARTING RJ Industrial® IP 67 Data 3A with IDC fast termination technology and zinc die-cast full metal housing
	Length:	1 m 3 m 5 m 10 m 20 m 50 m 100 m	09 45 715 1164 09 45 715 1166 09 45 715 1168 09 45 715 1173 09 45 715 1175 09 45 715 1178 09 45 715 1183	Cable type: Connectors:	Industrial Ethernet stranded cable, 2x2 x AWG 22/7 double shielding 2x HARTING RJ Industrial® IP 67 Data 3A with IDC fast termination technology and zinc die-cast full metal housing

Details for panel holes



ESC 67-30 TP08U M12 D-coding







ESC 67-30 TP08U M12 D-coding

Identification	Part number	Drawing	Dimensions in mm
ESC 67-30 TP08U Ethernet switch M12 D-coding	20 73 308 3941	105 86,5 The State of the Blad is for Bla	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)

Technical characteristics

Power supply

Input voltage 24 V DV (18 ... 30 V DV)

Current consumption approx. 140 mA (at 24 V DC)

Connections Screw terminal with 5 contacts, plug-in, for redundant power supply

(on the inside of control cabinet)

Alarm signal contact Change-over contact, potential-free, 24 V DC / 0.5 A (on the inside of cabinet)

Screw terminal with 3 contacts, pluggable

Ethernet Interface

Ports 8 (2x IP 65 / 6x IP 20)

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device On the outside of control cabinet: 2x circular connectors, M12, D-coding

On the inside of control cabinet 6x RJ45 connectors

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 105 x 40 x 105 mm (without connectors)

Mounting Directly on control cabinets and terminal boxes

Weight approx. 0.6 kg


ESC 67-30 TP08M M12 D-coding



Identification	Part number
HARAX® M12-L circular connector shielded, 4 contacts, male, D-coding	21 03 281 1405
Protection cover M12	21 01 000 0003
Mounting plate to the inside of control cabinet	20 80 000 0004

Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m	21 03 483 1401 21 03 483 1403 21 03 483 1405 21 03 483 1400 ¹⁾	Cable type: Connectors:	Industrial Ethernet Standard cable 2x2 x AWG 26 / 0.14 mm ² 2x circular connectors M12, D-coding, straight
	Length:	1 m 3 m 5 m	21 03 485 1401 21 03 485 1403 21 03 485 1405 21 03 485 1400 ¹⁾	Cable type: Connectors:	Industrial Ethernet Standard cable 2x2 x AWG 22 / 0.34 mm ² 2x circular connectors M12, D-coding, straight


Details for panel holes











Identification	Part number	Drawing	Dimensions in mm
ESC 67-30 TP08U Ethernet switch HARTING RJ Industrial® Hybrid	20 73 308 3972	105 86,5 86,5 102 1 Mail 102 1 Ma	4.0 4.0 Section Section Sect

Technical characteristics

Power supply

Input voltage 24 V DV (18 ... 30 V DV) Current consumption approx. 150 mA (at 24 V DC)

Connections (plug-in) On the inside of control cabinet: Screw terminal with 5 contacts,

> for redundant power supply Screw terminal with 6 contacts,

for hybrid power supply

Alarm signal contact Change-over contact, potential-free, 24 V DC / 0.5 A (on the inside of cabinet)

Screw terminal with 3 contacts, pluggable

Ethernet Interface

Ports 8 (2x IP 65 / 6x IP 20)

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Connections On the outside of control cabinet: 2x connectors HARTING RJ Industrial®

Hvbrid

On the inside of control cabinet: 6x RJ45 connectors 100 m (with Category 5 Kabel) according to EN 50 173

Mechanical data

Maximum cable length

Dimensions (B x T x H) 105 x 40 x 105 mm (without connectors)


Mounting Directly on control cabinets and terminal boxes

Weight approx. 0.6 kg



Identification Part number

Connector set HARTING RJ Industrial[®] Hybrid metal 10 12 005 2001



Mounting plate

to the inside of control cabinet

20 80 000 0004


Identification	Part number

System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67

IP 65 / IP 67 (when mated)


on request

Details for panel holes






Hybrid connector - Contact assignment 24 V DC



Power supply, alternative 1

Voltage supply and distribution are made by both hybrid haven. A feed over the post plug connector on the switchgear cabinet inside does not take place.






Power supply, alternative 2

The feed is made by the post plug connector on the switchgear cabinet inside of the Ethernet Switch, the distribution by means of the hybrid plug connectors.

Power supply inside of the switching cabinet



Ethernet Switch In-between, managed - Introduction



Fast Ethernet Switch, managed for industrial applications

General description

Ethernet switches devide former collision domains into point-to-point connections between the network components and the user equipment involved. Constructing the network this way prevents collisions.

The managed In-between Fast Ethernet switches of the type ESC 67-x0 TPxxM are an integrated solution, combining an Ethernet switch with a through panel connection in one device. The compact housing is mounted directly on the external wall of a control cabinet or a terminal box. Up to 6 ports in IP 20 are available for connection inside. For networking outside of the cabinet, the Ethernet switch allows the connection of up 2 items of user equipment to be connected through Shielded Twisted Pair cable in accordance to IEC 802.3 in IP 65 / IP 67.

The Fast Ethernet switches ESC 67-x0 TPxxM from HARTING provides two alternative access methods for the management:

SNMP and a comfortable web access.

Application fields



- Industrial automation
- Automotive industry
- Wind power
- Power distribution systems

Advantages

- High degree of protection IP 65 / IP 67
- Robust metal housing, zinc die-cast
- · Can be used directly in industrial environments
- EMC, temperature range and mechanical stability for the toughest demands
- Management functions integrated

Technical characteristics

- Ethernet switch according to IEEE 802.3
- Store and Forward Switching mode
- up to 6 ports, managed, non-blocking, IP 20
 2 ports, managed, non-blocking, IP 65 / IP 67
- Auto-crossing, Auto-negotiation, Auto-polarity

Ethernet Switch, managed



Management

Web-based access with password protection

- Status overview
- Port Settings
- Network Configuration
- Password settings
- Alarm Settings
- Diagnostics
- Parameter Import / Export
- Firmware Import / Export

SNMP Agent

- SNMP V1 and SNMP V3
- MIB II objects:
 - TCP/IP
 - UDP
 - System
 - Interface
 - IP
 - ICMP
 - SNMP
- HARTING MIB

Additional services

- DHCP
- DNS
- E-Mail
- · Parameter and firmware import and export via TFTP
- System time via SNTP
- Service Mode via port 1

Diagnostics

- LEDs for Power, Link, Status, Data transmission and Fault
- Port diagnostic
- Port mirroring
- History
- Alarms via signalling contact and / or E-Mail

ESC 67-30 TP05M HARTING RJ Industrial® IP 67 Data 3A





ESC 67-30 TP05M HARTING RJ Industrial® IP 67 Data 3A

Identification	Part number	Drawing	Dimensions in mm
ESC 67-30 TP05M Ethernet switch, managed HARTING RJ Industrial® IP 67 Data 3A	20 73 305 4921	105 86,5	

Technical characteristics

Power supply

Input voltage 24 V DV (18 ... 30 V DV)

Current consumption approx. 160 mA (at 24 V DC)

Connections Screw terminal with 5 contacts, plug-in, for redundant power supply

(on the inside of control cabinet)

Alarm signal contact Change-over contact, potential-free, 24 V DC / 0.5 A (on the inside of cabinet)

Screw terminal with 3 contacts, pluggable

Ethernet Interface

Ports 5 (2x IP 65 / 3x IP 20)

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device On the outside of control cabinet: 2x connectors HARTING RJ Industrial®

IP 67 Data 3A

On the inside of control cabinet 3x RJ45 connectors

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 105 x 40 x 105 mm (without connectors)

Mounting Directly on control cabinets and terminal boxes

Weight approx. 0.6 kg


ESC 67-30 TP05M HARTING RJ Industrial® IP 67 Data 3A



Identification	Part number
Connector set HARTING RJ Industrial® IP 67 Data 3A, metal	09 45 115 1100
Coding pin set	09 45 820 000
Mounting plate to the inside of control cabinet	20 80 000 0004

Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m 10 m 20 m 50 m	09 45 715 1123 09 45 715 1125 09 45 715 1127 09 45 715 1151 09 45 715 1153 09 45 715 1156 09 45 715 1161	Cable type: Connectors:	Industrial Ethernet standard cable, 2x2 x AWG 22/1 double shielding 2x HARTING RJ Industrial [®] IP 67 Data 3A with IDC fast termination technology and zinc die-cast full metal housing
	Length:	1 m 3 m 5 m 10 m 20 m 50 m 100 m	09 45 715 1164 09 45 715 1166 09 45 715 1168 09 45 715 1173 09 45 715 1175 09 45 715 1178 09 45 715 1183	Cable type: Connectors:	Industrial Ethernet stranded cable, 2x2 x AWG 22/7 double shielding 2x HARTING RJ Industrial [®] IP 67 Data 3A with IDC fast termination technology and zinc die-cast full metal housing

Details for panel holes



ESC 67-30 TP05M M12 D-coding







ESC 67-30 TP05M M12 D-coding

Identification	Part number	Drawing	Dimensions in mm
ESC 67-30 TP05M Ethernet switch, managed M12 D-coding	20 73 305 4941	105 86,5 Remark for the large of the large o	40,2

Technical characteristics

Power supply

Input voltage 24 V DV (18 ... 30 V DV)

Current consumption approx. 160 mA (at 24 V DC)

Connections Screw terminal with 5 contacts, plug-in, for redundant power supply

(on the inside of control cabinet)

Alarm signal contact Change-over contact, potential-free, 24 V DC / 0.5 A (on the inside of cabinet)

Screw terminal with 3 contacts, pluggable

Ethernet Interface

Ports 5 (2x IP 65 / 3x IP 20)

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device On the outside of control cabinet: 2x circular connectors, M12, D-coding

On the inside of control cabinet 3x RJ45 connectors

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 105 x 40 x 105 mm (without connectors)

Mounting Directly on control cabinets and terminal boxes

Weight approx. 0.6 kg


ESC 67-30 TP05M M12 D-coding



Identification	Part number
HARAX® M12-L circular connector shielded, 4 contacts, male, D-coding	21 03 281 1405
Protection cover M12	21 01 000 0003
Mounting plate to the inside of control cabinet	20 80 000 0004

Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m	21 03 483 1401 21 03 483 1403 21 03 483 1405 21 03 483 1400 ¹⁾	Cable type: Connectors:	Industrial Ethernet Standard cable 2x2 x AWG 26 / 0.14 mm ² 2x circular connectors M12, D-coding, straight
	Length:	1 m 3 m 5 m	21 03 485 1401 21 03 485 1403 21 03 485 1405 21 03 485 1400 ¹⁾	Cable type: Connectors:	Industrial Ethernet Standard cable 2x2 x AWG 22 / 0.34 mm ² 2x circular connectors M12, D-coding, straight

Details for panel holes



ESC 67-30 TP08M HARTING RJ Industrial® IP 67 Data 3A







ESC 67-30 TP08M HARTING RJ Industrial® IP 67 Data 3A

Identification	Part number	Drawing	Dimensions in mm
ESC 67-30 TP08M Ethernet switch, managed HARTING RJ Industrial® IP 67 Data 3A	20 73 308 4921	105 86,5 86,5 86,5 100 \$\$\$\$ 100 \$\$ 100 \$\$ 10	(a)

Technical characteristics

Power supply

Input voltage 24 V DV (18 ... 30 V DV)

Current consumption approx. 190 mA (at 24 V DC)

Connections Screw terminal with 5 contacts, plug-in, for redundant power supply

(on the inside of control cabinet)

Alarm signal contact Change-over contact, potential-free, 24 V DC / 0.5 A (on the inside of cabinet)

Screw terminal with 3 contacts, pluggable

Ethernet Interface

Ports 5 (2x IP 65 / 3x IP 20)

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device On the outside of control cabinet: 2x connectors HARTING RJ Industrial®

IP 67 Data 3A

On the inside of control cabinet 6x RJ45 connectors

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 105 x 40 x 105 mm (without connectors)

Mounting Directly on control cabinets and terminal boxes

Weight approx. 0.6 kg


ESC 67-30 TP08M HARTING RJ Industrial® IP 67 Data 3A



Identification	Part number
Connector set HARTING RJ Industrial® IP 67 Data 3A, metal	09 45 115 1100
Coding pin set	09 45 820 000
Mounting plate to the inside of control cabinet	20 80 000 0004

Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m 10 m 20 m 50 m	09 45 715 1123 09 45 715 1125 09 45 715 1127 09 45 715 1151 09 45 715 1153 09 45 715 1156 09 45 715 1161	Cable type: Connectors:	Industrial Ethernet standard cable, 2x2 x AWG 22/1 double shielding 2x HARTING RJ Industrial® IP 67 Data 3A with IDC fast termination technology and zinc die-cast full metal housing
	Length:	1 m 3 m 5 m 10 m 20 m 50 m 100 m	09 45 715 1164 09 45 715 1166 09 45 715 1168 09 45 715 1173 09 45 715 1175 09 45 715 1178 09 45 715 1183	Cable type: Connectors:	Industrial Ethernet stranded cable, 2x2 x AWG 22/7 double shielding 2x HARTING RJ Industrial [®] IP 67 Data 3A with IDC fast termination technology and zinc die-cast full metal housing

Details for panel holes



ESC 67-30 TP08M M12 D-coding







ESC 67-30 TP08M M12 D-coding

Identification	Part number	Drawing	Dimensions in mm
ESC 67-30 TP08M Ethernet switch, managed M12 D-coding	20 73 308 4941	105 86,5 The S S S S S S S S S S S S S S S S S S S	4.4.0 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)

Technical characteristics

Power supply

Input voltage 24 V DV (18 ... 30 V DV)

Current consumption approx. 190 mA (at 24 V DC)

Connections Screw terminal with 5 contacts, plug-in, for redundant power supply

(on the inside of control cabinet)

Alarm signal contact Change-over contact, potential-free, 24 V DC / 0.5 A (on the inside of cabinet)

Screw terminal with 3 contacts, pluggable

Ethernet Interface

Ports 8 (2x IP 65 / 6x IP 20)

Data transmission rate 10 Mbit/s or 100 Mbit/s / Auto-crossing, Auto-negotiation, Auto-polarity

Cable Shielded Twisted Pair (STP) or Unshielded Twisted Pair (UTP), Category 5

Available device On the outside of control cabinet: 2x circular connectors, M12, D-coding

On the inside of control cabinet 6x RJ45 connectors

Maximum cable length 100 m (with Category 5 cable) according to EN 50 173

Mechanical data

Dimensions (W x D x H) 105 x 40 x 105 mm (without connectors)

Mounting Directly on control cabinets and terminal boxes

Weight approx. 0.6 kg


ESC 67-30 TP08M M12 D-coding



Identification	Part number
HARAX® M12-L circular connector shielded, 4 contacts, male, D-coding	21 03 281 1405
Protection cover M12	21 01 000 0003
Mounting plate to the inside of control cabinet	20 80 000 0004

Identification			Part number		
System cables for Industrial Ethernet, pre-assembled at both ends IP 65 / IP 67 (when mated)	Length:	1 m 3 m 5 m	21 03 483 1401 21 03 483 1403 21 03 483 1405 21 03 483 1400 ¹⁾	Cable type: Connectors:	Industrial Ethernet Standard cable 2x2 x AWG 26 / 0.14 mm ² 2x circular connectors M12, D-coding, straight
	Length:	1 m 3 m 5 m	21 03 485 1401 21 03 485 1403 21 03 485 1405 21 03 485 1400 ¹⁾	Cable type: Connectors:	Industrial Ethernet Standard cable 2x2 x AWG 22 / 0.34 mm ² 2x circular connectors M12, D-coding, straight

Details for panel holes



Industrial Outlet Page Contents HARTING Industrial Cabinet Outlet Cat. 6 79 HARTING RJ Industrial® Metal Outlet Cat. 6 81

	Industrial Outlet	HARTING
2		

HARTING Industrial Cabinet Outlet Cat. 6





HARTING Industrial Cabinet Outlet Cat. 6

Advantages

- Small package size for two RJ45 ports
- Angled area (45°) for simple plugin of patch cables
- Future-proof due to Category 6 de-embedded
- Termination of installation cables without special tools
- · Label for individual customer marking

General Description

The Industrial Ethernet Cabinet Outlet is an interchange module between an installation cable and a patch cable.

The small housing equipped with two RJ45 keystone jacks is directly mounting onto a top-hat mounting rail 35 mm according to EN 60 715.

Identification	Part number	Drawing	Dimensions in mm
HARTING Industrial Cabinet Outlet Cat. 6 Industrial Ethernet termination unit IP 20 including: 2 x Category 6 keystone jacks 1 x Housing with dust protection covers 1 x Mounting instructions	20 76 102 8000	69 66	28.4

HARTING Industrial Cabinet Outlet Cat. 6



Technical characteristics

Transmission performance Category 6 according to ISO / IEC 11 801:2002 for class E links

Transmission rate• Ethernet 10 Mbit/s
• Fast Ethernet 100 Mbit/s

Gigabit Ethernet 1000 Mbit/s

Transmission frequency max. 250 MHz

Termination 2x KRONE KM8 RJ45 keystone jack, Category 6

Wiring IDC without special tools (2x LSA-PLUS®)

min. 200 times reusable

Strands diameter 0.5 to 0.65 mm / AWG 24 to 22; flexible and solid

Cross section strands isolation 0.7 to 1.6 mm
Cross section sheath diameter 6 to 9 mm

Cable type • 2 pair installation cables, Category 5, 6 and 7 according to IEC 11801

4 pair installation cables, Category 5, 6 and 7 according to IEC 11801

Cable feeding 1 to 2 cable(s); from top side

Mating faceRJ45 according to IEC 60 603-7

Compatible to all standard RJ45 connectors

Mating cyclesmin. 750Shielding360 °

Mechanical data

Housing type Plastic

Dimensions (W x H x D) approx. 28 x 82 x 68 mm (without connectors)

Degree of protection IP 20

according to DIN 60 529

Mounting Onto top-hat mounting rail 35 mm according to EN 60 715

Colour Light-grey, RAL 7035

Einvironmental conditions

Operating temperature range -20 °C to +70 °C

Storage temperature range -40 °C to +85 °C

Relative humidity 30 % to 95 % (non-condensing)

Approvals

cUL (in preparation)

HARTING RJ Industrial® Metal Outlet Cat. 6



81



HARTING RJ Industrial[®] Metal Outlet Cat. 6

Advantages

- High IP 65 protection level
- Robust housing
- Can be used directly in industrial environments
- Future-proof due to Category 6 de-embedded
- Termination without special tools
- PROFINET compatible

General Description

The Industrial Outlet permits structrured building cabling in accordance with ISO / IEC 11 801:2002 or with EN 50 173:2002 to be continued in the industrial environment through to the machine.

With its aluminium die cast housing the Metal Outlet fulfills even the toughest requirements on the production floor. Thus it is possible to install network access directly within the unprotected environment of machines, welding robots etc.

Identification Part number Drawing Dimensions in mm HARTING RJ Industrial® Metal 20 79 302 0922 max.23 Outlet Cat. 6 Industrial Ethernet network outlet IP 65 includina: 2 x Category 6 keystone jacks 1 x Housing including protection covers 2 x Cable glands 1 x Mounting instructions

HARTING RJ Industrial® Metal Outlet Cat. 6



Technical characteristics

Transmission performance Category 6 according to ISO / IEC 11 801:2002 for class E links

Transmission rate• Ethernet 10 Mbit/s
• Fast Ethernet 100 Mbit/s

Gigabit Ethernet 1000 Mbit/s

Transmission frequency max. 250 MHz

Termination 2x KRONE KM8 RJ45 keystone jack, Category 6, vibration proof mounted

Wiring IDC without special tools (2x LSA-PLUS®)

min. 200 times reusable

Strands diameter 0.5 to 0.65 mm / AWG 24 to 22; flexible and solid

Cross section strands isolation 0.7 to 1.6 mm
Cross section sheath diameter 6 to 9 mm

Cable type • 2 pair installation cables, Category 5, 6 and 7 according to IEC 11801

4 pair installation cables, Category 5, 6 and 7 according to IEC 11801

Cable feeding1 to 2 cable(s); on the opposite side of the connector terminalsConnectorHARTING RJ Industrial® Data 3A Metal (PROFINET compliant)

Mating face
 RJ45 according to IEC 60 603-7

Compatible to all standard RJ45 connectors

Mating cyclesmin. 750Shielding 360°

Mechanical data

Housing type Aluminium die cast

Dimensions (W x H x D) 125 x 80 x 57.5 mm (without connectors)

Degree of protection IP 65; mated and unmated (by Han® 3A protection covers)

according to DIN 60 529

Mounting On-wall mounting with 4 screws

Colour Grey, RAL 7037

Environmental conditions

Operating temperature range $-20 \, ^{\circ}\text{C}$ to $+70 \, ^{\circ}\text{C}$ Storage temperature range $-40 \, ^{\circ}\text{C}$ to $+85 \, ^{\circ}\text{C}$

Relative humidity 30 % to 95 % (non-condensing)


Approvals

cUL (in preparation)

Industrial Power Supply Contents Page Industrial Power Supply IPS 67-10 1-2-95W 85

Industrial Power Supply	HARTING
Contents	Page
84	







Advantages

- High degree of protection IP65/67
- · Robust metal housing
- Worldwide assignment by long range input
- Suitable for the direct use in industrial environments
- Temperature range and mechanical solidness for highest demands

General

The Industrial Power Supply IPS 67-10 1-2-95W is available with termination versions M12 and ${\rm Han}^{\rm @}$ 4 A.

The Industrial Power Supply is applicable for the worldwide assignment by the long range input. It can be inserted thus at each manufacturing place of the world problem-free at walls, columns, carriers or manufacturing cells.

Identification	Part number	Drawing	Dimensions in mm
IPS 67-10 1-2-95W Han [®] 3 A Industrial Power Supply with termination Han [®] 4 A	20 80 300 3011	France Salcoly Post of Color France Salcoly France	
IPS 67-10 1-2-95W M12 Industrial Power Supply with termination M12, A-coding	20 80 300 3012	Power Suzely (PSS) Fower DC Town DC	



Identification	Part number	Drawing	Dimensions in mm
IPS 67-10 1-2-95W Han [®] 3 A Industrial Power Supply with termination Han [®] 4 A	20 80 300 3011		0.0000
IPS 67-10 1-2-95W M12 Industrial Power Supply with termination M12, A-coding	20 80 300 3012		088888
Identification	Part number	Drawing	Dimensions in mm
Set for mounting on standard rail according to DIN EN 60 715	20 80 000 0003		
Set for panel mounting vertical	20 80 010 0001		
Set for panel mounting horizontal	20 80 024 0002		



Technical characteristics

Input power supply

Input rated voltage 115 V AC / 230 V AC (Auto-ranging)

• 85 V AC ... 264 V AC

• Tolerances of input voltage according to IEC 1131-2 and

DIN 19 240

Input frequency 47 ... 63 Hz

Input rated current < 2 A
Input current (typ./cold start) < 30 A

Termination power supply Han® 4 A (male insert)

Diagnostics (LED) Input voltage is active: Green

Efficiency (for rated values) > 85 %

Open loop current < 10 mA (at DC) buffer time/Hold time > 20 ms at 230 V AC

Recommended back-up fuse 10 A characteristic B (EN 898)

Transient firmness according to VDE 0160

Output power supply

Output rated voltage 24 V DC

Range of output voltage 22.5 V ... 28.5 V DC (Vout)

Output current 3.9 A (at 24 V DC)

Output power 95 W

Termination output voltage Han® 4 A (female insert) / M12 A-coding (female insert)

Diagnostics (LED) Output voltage is active: Yellow (OFF at V_{out} < 22.5 VDC)

Sensibility < 2 %

Protection function Durable short-circuit proof, overload-proof and no-load operation

Power Factor Correction active PFC
Remaining ripple (at rated values) < 50 mVss
Setup Time < 500 ms
Rise Time < 50 ms
Hold Time > 20 ms

Overload behavior Switch off > 1,4 x I_N



Technical characteristics

Design features

Material of housing Robust metal housing of zinc die-cast Dimensions (W x H x D) 77.5 x 87 x 120 mm (without connectors)

Mounting
 35 mm top-hat mounting rail according to DIN EN 60 715,

Wall mounting, verticalWall mounting, horizontal

Weight approx. 1.2 kg
Degree of protection IP 65 / IP 67

acc. to DIN 60 529

Environmental conditions

Operating temperature $-25 \, ^{\circ}\text{C}$ to $+75 \, ^{\circ}\text{C}$ Storage temperature $-40 \, ^{\circ}\text{C}$ to $+85 \, ^{\circ}\text{C}$

Relative humidity 30 % to 95 % (non-condensing)

Mechanical solidness

Shock IEC 68-2-27-Ea Shock and vibration EN 50 155

according to Rail-standard

Vibration IEC 68-2-6-Fc

EMC standards

Interference immunity ESD IEC 61 000-4-2
Interference immunity HF radiated IEC 61 000-4-3
Interference immunity Burst IEC 61 000-4-4
Interference immunity Surge IEC 61 000-4-5
Interference immunity IEC 61 000-4-6
Emitted radiation EN 55 011, Klasse A

Rail-standard EN 50 121-3-2

Safety extra-low voltage • EN 50 178 (VDE 0160)

EN 60 204 (PELV)

Secure separation EN 60 950 (SELV)

Protection against electrical impact DIN VDE 0100-410

Delimitation of net harmonic stream DIN VDE 0106-101

Connectors and Cables



Contents	Page
Industrial Ethernet IP 20 Standard Patch cable	91
Industrial Ethernet IP 20 Standard Patch cable, angled	93
HARTING RJ Industrial [®] Hybrid Connector	95
HARTING RJ Industrial [®] Hybrid Panel feed through	97
HARTING RJ Industrial [®] Hybrid Gender changer	99
Han [®] PushPull Connectors	101
Han [®] PushPull Data RJ45	103
Han® PushPull Data SCRJ	104
Han [®] PushPull Power	105
Han [®] PushPull L Power	106
Push Pull Connector RJ Industrial	107
Push Pull Connector RJ Industrial	108
Push Pull Power 250 V	109
Push Pull Power 250 V	110
Han® M12 Circular Connectors for Ethernet applications	111
Han® M12 Panel Feed-Throughs	114
microFX	116

	Connectors and Cables	HARTING
)		

Industrial Ethernet IP 20 Standard Patch cable







HARTING RJ Industrial[®] IP 20 Standard patch cable, Cat. 5

General Information

- 1:1 cabling
- Shielded Twisted Pair cable
- Transmission characteristics to ISO/IEC 11 801:2002: Class D
- Mating geometry: 2x RJ45 to IEC 60 603-7
- Connectors: 2x RJ45 shielded with piercing connection technology, moulded
- Degree of protection: IP20 (when mated)
- Cable type: PUR, halogen-free

4x 2x AWG 26/7, twisted pair, shielded

Suitable for cabling of Ethernet networks in industrial environments with limited environmental impact on the connectors.

Composed of shielded connectors and cables with a halogen-free and oil-resistant sheath, the system cables are suitable for use in switchgear cabinets. The compact dimensions of the connectors mean that the cables are also generally suitable for installations where space is restricted.

The compact size of the connectors ensures that system cables can be utilised inside switchgear cabinets or on multiport switches.

The choice between green and black cables also opens up colour coding options. The cable lengths available range from 0.5 m to 20 m. In conjunction with the other characteristics of these system cables, they offer the prospect of covering a wide range of applications.

Industrial Ethernet Standard Patch cable IP 20



Identification	Part number	Drawing	Dimensions in mm
Standard patch cable for Industrial Ethernet pre-assembled; IP 20, Cat. 5		Cable type:	Industrial Ethernet cable; 4x2 x AWG 26/7, Twisted Pair, shielded
	09 45 971 1101	Sheath:	PUR green, halogen-free
Length: 0.5 m 1.0 m 1.5 m 2.0 m 2.5 m 3.0 m 4.0 m 5.0 m 7.5 m 10.0 m 15.0 m 20.0 m	09 45 971 1101 09 45 971 1115 09 45 971 1115 09 45 971 1116 09 45 971 1104 09 45 971 1105 09 45 971 1106 09 45 971 1109 09 45 971 1112 09 45 971 1113 09 45 971 1114	Connectors:	2x RJ45, shielded, with piercing termination technique, extrused
Standard patch cable for Industrial Ethernet		Cable type:	Industrial Ethernet cable; 4x2 x AWG 26/7, Twisted Pair, shielded
pre-assembled; IP 20, Cat. 5		Sheath:	PUR black, halogen-free
Length: 0.5 m 1.0 m 1.5 m 2.0 m 2.5 m 3.0 m 4.0 m 5.0 m 7.5 m 10.0 m 15.0 m 20.0 m	09 45 971 1121 09 45 971 1122 09 45 971 1135 09 45 971 1123 09 45 971 1124 09 45 971 1125 09 45 971 1126 09 45 971 1129 09 45 971 1132 09 45 971 1133 09 45 971 1134	Connectors:	2x RJ45, shielded, with piercing termination technique, extrused

Industrial Ethernet IP 20 Standard Patch cable, angled









Leaving right



Leaving top



Leaving bottom

Industrial Ethernet IP 20 Standard patch cable, Cat. 5, angled

General Information

- · System cables with connectors assembled on both ends
- Suitable for cabling industrial networks (for example, in accordance with PROFINET guidelines)
- · Based on RJ45 connectors
- Application: switchgear cabinets and industrial environments with minor environmental impact on the connectors

Technical characteristics

Ethernet cable

Transmission characteristics Class D according to ISO / IEC 11 801:2002

Facing geometriy 2x RJ45 according to IEC 60 603-7

Degree of protection IP 20 (when mated)

Electrical characteristics at 20 °C

Contact resistance $\leq 20 \text{ m}\Omega$ Insulating resistance $\geq 500 \text{ M}\Omega$

Electrical strength

Contact - contact 1 kV Contact - ground 1.5 kV

Electrical characteristics after cyclic heat load

Contact resistance $\leq 20 \text{ m}\Omega$ Insulating resistance $\geq 100 \text{ M}\Omega$

Electrical strength

Contact - contact 1 kV Contact - ground 1.5 kV

Industrial Ethernet IP 20 Standard Patch cable, angled



Identification	Part number	Drawing	Dimensions in mm
Standard patch cable for Industrial Ethernet pre-assembled; leaving right		Cable type:	Industrial Ethernet cable; 2x2 x AWG 22/1, shielded twisted pair
Length: 1.5 m	09 45 771 4023 09 45 771 4025	Sheath:	PVC green, Ø 6.5 mm
5.0 m 10.0 m 20.0 m 50.0 m 100.0 m leaving left leaving top leaving bottom	09 45 771 4025 09 45 771 4027 09 45 771 4051 09 45 771 4053 09 45 771 4061 on request on request on request	Connectors:	2x HARTING RJ Industrial [®] IP 20 Data with extrused housing, 90° angled, leavers rigth
Flexible patch cable for Industrial Ethernet pre-assembled; leaving right		Cable type:	Industrial Ethernet flexible cable; 2x2 x AWG 22/7, shielded twisted pair
Length: 1.5 m	09 45 771 4123 09 45 771 4125	Sheath:	PVC green, Ø 6.5 mm
5.0 m 10.0 m 20.0 m 50.0 m 100.0 m leaving left leaving top	09 45 771 4125 09 45 771 4127 09 45 771 4151 09 45 771 4153 09 45 771 4161 on request on request	Connectors:	2x HARTING RJ Industrial [®] IP 20 Data with extrused housing, 90° angled, leavers rigth
leaving bottom	on request		
Patch cable for power chains for Industrial Ethernet pre-assembled; leaving right		Cable type:	Industrial Ethernet cable for power chains; 2x2 x AWG 22/1, shielded twisted pair
Length: 1.5 m 3.0 m	09 45 771 4164 09 45 771 4166	Sheath:	PVC green, Ø 6.5 mm
5.0 m 10.0 m 20.0 m 50.0 m 100.0 m	09 45 771 4168 09 45 771 4173 09 45 771 4175 09 45 771 4178 09 45 771 4183	Connectors:	2x HARTING RJ Industrial [®] IP 20 Data with extrused housing, 90° angled, leavers rigth
leaving left	on request		
leaving top leaving bottom	on request on request		

HARTING RJ Industrial® Hybrid Connector




95





HARTING RJ Industrial[®] Hybrid connector IP 67 (metal)

General Information



With the HARTING RJ Industrial® Hybrid connector, HARTING has developed an interface solution that integrates the data lines and the power supply into one connector for hybrid Ethernet networks. The connector's geometry nevertheless maintains a clear separation between the data and the power contacts. This brings a significant reduction in the costs of installation and of field devices suitable for industrial application with hybrid cabling.

The four power contacts of the hybrid module have also been designed with *HARAX*® rapid termination technology, allowing stranded cables of up to 1.5 mm² to be connected.

Connector set inclusive housings, cable gland and assembly instruction 10 12 005 2001 10 12

HARTING RJ Industrial® Hybrid Connector



Technical characteristics

Transmission characteristics Category 5 according to ISO / IEC 11 801:2002 and EN 50 173-1

Degree of protection IP 65 / IP 67 (when mated)

Mating interface RJ45 according to IEC 60 603-7

plus 4x power supply

Wire diameter, dataAWG 22 - 24 stranded

AWG 22 - 23 solid

Wire diameter, power supply 1.5 mm²

Rated voltage, power supply 48 V DC

Rated current, power supply see Derating curve

Temperature range -40 °C ... +70 °C

Cable sheath diameter 10 mm ... 11 mm

Mating cycles min. 500

Housing material Zinc die-cast, grey; UL 94-V0

HARTING RJ Industrial® Hybrid Panel feed through







HARTING RJ Industrial[®] Hybrid Panel feed through IP 67 (Metall)

General Description

With the HARTING RJ Industrial® Hybrid connector, HARTING has developed an interface solution that integrates the data lines and the power supply into one connector for hybrid Ethernet networks.

The connector's geometry nevertheless maintains a clear separation between the data and the power contacts. This brings a significant reduction in the costs of installation and of field devices suitable for industrial application with hybrid cabling.

The panel feed through is compatible with RJ45 connectors, which means that the standard patch cables for service and test purposes can be used.

The data lines are connected at the rear via an RJ45 jack, while the power lines use a cage clamp terminal.

Optional the hybrid interface can be integrated in the device directly, thus preventing the use of rear side data lines.

Identification	Part number	Drawing	Dimensions in mm
Panel feed through set screw termination including housing and assembly instruction	10 12 005 1001	23max 2 max 2 max	28max Ø3,2 IEC 60603-7 5,1 35max
Panel feed through set cage clamp including housing and assembly instruction	10 12 005 1002	23max	28max Ø3,2 IEC 60603-7 5,1 35max
			g

HARTING RJ Industrial® Hybrid Panel feed through



Technical characteristics

Transmission characteristics Category 5 according to ISO / IEC 11 801:2002 and EN 50 173-1

Degree of protection IP 65 / IP 67 (when mated)

Mating interface external RJ45 according to IEC 60 603-7

plus 4x power supply

Mating interface internal RJ45 according to IEC 60 603-7

plus 4x power supply with cage clamp 1.5 mm²

Rated voltage power supply 48 V DC

Rated current power supply see Derating curve on page 95

Panel cut out 22 x 22 mm

Temperature range -40 °C ... +70 °C

Cable sheath diameter 10 mm ... 11 mm

Mating cycles min. 500

Material RJ45 panel feed through Metal

HARTING RJ Industrial® Hybrid Gender changer







HARTING RJ Industrial[®] Hybrid gender changer IP 67 (metal)

General Information

With the HARTING RJ Industrial® Hybrid connector, HARTING has developed an interface solution that integrates the data lines and the power supply into one connector for hybrid Ethernet networks. The connector's geometry nevertheless maintains a clear separation between the data and the power contacts. This brings a significant reduction in the costs of installation and of field devices suitable for industrial application with hybrid cabling.

The gender changer can be inserted outside control cabinets directly in the field for the separation of segments with different cable material as for example the transition to power chains.

It can directly be mounted onto machines and components as for example a bulkhead of robotics.

Identification	Part number	Drawing	Dimensions in mm
Gender changer inclusive housings, cable gland and assembly instruction	10 12 005 1003	60.5max 122, 4max	35max 28max 16,5 40max

HARTING RJ Industrial® Hybrid Gender changer



Technical characteristics

Transmission characteristics Category 5 according to ISO / IEC 11 801:2002 and EN 50 173-1

Degree of protection IP 65 / IP 67 (when mated)

Mating interface RJ45 according to IEC 60 603-7

plus 4x power supply

Wire diameter, data

• AWG 22 - 24 stranded

AWG 22 - 23 solid

Wire diameter, power supply 1.5 mm²

Rated voltage, power supply 48 V DC

Rated current, power supply see Derating curve on page 95

Temperature range -40 °C ... +70 °C

Cable sheath diameter 10 mm ... 11 mm

Mating cycles min. 500

Housing material Metal

Han® PushPull Connectors





Han® PushPull For structured cabling in the field

General description


The connector family based on HARTING Push Pull interlocking technology.

Connectors from this family conform to the specifications of German motor vehicle manufacturers.

The connectors support line topology cabling.

Available: summer 2006

Application fields



- Industrial automation
- Automotive industry
- Wind power
- · Power distribution systems

Advantages

Automation

Simple cabling of PROFINET in line topology

Installation

Robust HARTING Push Pull technology

IT

 Design in IP 67 for harsh industrial environments on the field level

Technical characteristics

- Compact design
- · Conform to PROFINET standards
- For optical or electrical transmission of data or power
- Simple handling with Push Pull technology
- Termination technique locally configurable

	Han® PushPull Connectors	HARTING
102		

Han® PushPull Data RJ45





Han-Cubic Data RJ45



Automation Initiative German Domestic Automobile Manufactures

Advantages

Ethernet connector on base RJ45

- HARTING Push Pull technology
- Compact design
- · High density of components
- Integration of devices via RJ45 PCB connector
- Tool lots high-speed connection technology

General Description

Locking system Push Pull
Degree of protection IP 65 / IP 67
Mating face RJ45 according to

iting face RJ45 according IEC 60 603-7

Max. cable diameter 9 mm

Wire gauge AWG 24 - 22 flexible AWG 23 - 22 solid

Transmission characteristic Cat 5e
Number of contacts 4, shielded
Material of housing Plastic

Flammability according to UL 94 V0

Identification Part number Dimensions in mm Drawing Han® PushPull Data RJ45 PROFINET identification: **PROFINET O-Plug RJ45** 09 35 221 0421 Cable side including hood and male insert HARTING RJ Industrial® Panel cut out Device side 09 35 002 0321 bulkhead mounted housing RJ45 female not included Female recommendation and assembly manual on request.

Han® PushPull Data SCRJ





Han® PushPull Data SCRJ



Automation Initiative German Domestic Automobile Manufactures

Advantages

Optical connector on base SCRJ

- HARTING Push Pull technology
- · Compact design
- High density of components
- Integration of devices via transceiver

General Description

Locking system Push Pull Degree of protection IP 65

Mating face SCRJ according to

IEC 50377-3-6

Fibre types MM 50 μ m / 125 μ m

MM 62.5 μm / 125 μm SM 10 μm / 125 μm HCS $^{\otimes 1}$) 200 μm / 230 μm

POF²) 1 mm

Material of housing Plastic Flammability accord. to UL 94 V0

Han® PushPull Data SCRJ

PROFINET identification: PROFINET O-Plug SCRJ

Cable side

including housing and insert

SCRJ

09 35 241 0422


Device side


bulkhead mounted housing Optical transceiver not


included


Transceiver recommendation and assembly manual on request.

09 35 002 0321









Panel cut out

¹⁾ HCS® = Hard Clad Silica (registered trademark of SpecTran Corporation)

²⁾ POF = Polymer Optical Fibre

Han® PushPull Power





Han® PushPull Power

General Description Advantages Power connector for supply of device Locking system Push Pull Degree of protection IP 65 HARTING Push Pull technology Max. cable diameter 13 mm Compact, space-saving design · Finger protected Wire gauge 2.5 mm² · Cable side; female Number of contacts 4 + PE - crimp termination Rated current 16 A - Tension clamp high-speed Rated voltage 230/400 V connection (planning) Material of housing Plastic · Device side; male Flammability according to UL 94 V0 - solder termination, angled

condition mattern, unights		
Part number	Drawing	Dimensions in mm
09 35 231 0421	cu. 67	72 22 22 22 22 22 22 22 22 22 22 22 22 2
09 35 231 0323		Panel cut out
	Part number 09 35 231 0421	Part number Drawing 09 35 231 0421 09 35 231 0323

Han® PushPull L Power





Han[®] PushPull L Power



Automation Initiative German Domestic Automobile Manufactures

General Description Advantages Power connector for supply of device Push Pull Locking system Degree of protection IP 65 • HARTING Push Pull technology Max. cable diameter 13 mm · Finger protected Wire gauge 2.5 mm² · Cable side; female Number of contacts 4 + PE - Tension clamp high-speed Rated current 16 A connection Rated voltage 24 V · Device side; male Material of housing **Plastic** - solder termination, angled Flammability according to UL 94 V0

Identification	Part number	Drawing	Dimensions in mm
Han [®] PushPull L Power PROFINET identification: PROFINET O-Plug Power24			
Cable side including hood and female insert 16 A 24 V with fast termination technique	09 35 431 0421		
Device side including housing and male insert 16 A 24 V with solder termination	09 35 431 0321		
PCB layout on request			

Push Pull Connector RJ Industrial





IP 67 Push Pull connector

Identification	Part number	Drawing	Dimensions in mm
Connector set incl. housing, cable gland and instruction manual	09 45 145 1100	max.2.35 max.55	
Protection cover for connectors with cord, IP 67/65	09 45 145 1100	max. 20, 15 B	mox .20, 15

General information

The IP 67 Data version in a push pull housing is fitted with innovative housing locking technology. The housing of the connector is locked tightly to the hood by means of a locking sleeve that surrounds it. The connector can be locked and unlocked using one hand and only minimal force. In spite of its high degree of protection, the housing is very compact, and is ideally suited for compact industrial applications.

The HARTING RJ Industrial® Push Pull is thus the smallest IP 67/65 Industrial Ethernet connector based on RJ 45 with IDC connection technology in the world.

Technical characteristics

Transmission properties in accordance with Category 5

ISO/IEC 11 801:2002 and EN 50173-1 Degree of protection: IP 67/65

Degree of protection: IP 67/65
Locking mechanism: Push Pull ac

Push Pull according to ISO/IEC 24 702 and IEC 61 076-3-106,

variant 4

Mating interface: RJ 45 according to

IEC 60 603-7

Wire gauge data¹⁾: AWG 22 - 24 stranded

AWG 22 - 23 solid

Temperature range: -40 °C ... +70 °C Cable sheath diameter: 6,5 mm ... 8,6 mm

Mating cycles: mind. 750

Housing material: Polyamide, black

Polycarbonate, black

UV resistant

UL 94-V0

UL recognised, E102079



Push Pull Connector RJ Industrial





IP 67 Push Pull connector

Identification	Part number	Drawing	Dimensions in mm
Connector set incl. housing, cable gland and instruction manual Cable manager, white Cable manager blue	09 45 145 1500 09 45 145 1510	A	rding to IEC 60 603-7
Protection cover for connectors with cord, IP 67/65	09 45 145 1100	*****	,15 maxi Representation of the contact no. 1

General information

The IP 67 data version in push pull housing is fitted with innovative housing locking technology. The housing of the connector is locked tightly to the coupling by means of a surrounding locking sleeve. The connector can be locked and unlocked using one hand and only a little force. In spite of its high degree of protection, the housing is very compact, and is ideally suited for compact industrial applications.

The HARTING RJ Industrial[®] Push Pull Category 6 is ideally suited to compact industrial applications that require 4 pair or Gigabit Ethernet wiring.

For Category 6 patch cords it is recommended to use 1 connector with a white wire manager and 1 with a blue wire manager, in order to optimise the crosstalk between different signal pairs.

Technical characteristics

Transmission properties in accordance with Category 6

ISO/IEC 11 801:2002 and EN 50173-1 Degree of protection: IP 67/65

Locking mechanism: Push Pull according to

ISO/IEC 24 702 and IEC 61 076-3-106,

variant 4

Mating interface: RJ 45 according to

IEC 60 603-7

Wire gauge data¹⁾: AWG 24 - 27 stranded Temperature range: -40 °C ... +70 °C Cable sheath diameter: 6,5 mm ... 8,6 mm

Mating cycles: mind. 750

Housing material: Polyamide, black Polycarbonate, black

UV resistant UL 94-V0

UL recognised, E102079



Push Pull Power 250 V





IP 67 Push Pull connector

for supply voltage 250 V

Identification	Part number	Drawing	Dimensions in mm
Connector set inkl. 3 turned crimp contacts (male), insulator body (black), housing, cable gland	09 46 145 3410	contact no. 1	
Set of coding pins To avoid accidental incorrect mating a coding system is required. The coding pins are inserted without loss of contacts.	09 46 840 0000	Sealing gland, washer and nut PG9	
Protective cap IP 65 / 67	09 45 845 0001	41,5 max i	

Technical characteristics

Specifications	DIN VDE 0627, DIN VDE 0110, DIN EN 61 984
Working voltage	250 V
Working current per contact	16 A @ 55 °C
Rated impulse voltage	4.0 kV (DIN EN 61 984)
Overvoltage category	III (DIN VDE 0110 and IEC 60 664-1)
Pollution degree	3 (DIN VDE 0110 and IEC 60 664-1)
No. of current carrying contacts	2
Pre-leading PE contact	1
Contact resistance	max. 5 mΩ
Protection against contact	acc. to IEC DIN EN 60 529
Wire gauge	1.5 mm² (AWG 16) 1), stranded
Cable sheath diameter	6.9 - 8.6 mm
Protection class – mated	IP 67 / 65 (IEC DIN EN 60 529)
unmated	IP 20 (IEC DIN EN 60 529)
Vibration and shock resistance	acc. to EN 50 155
Ambient temperature	- 40 + 70 °C
Mating security	Polarisation with polarisation nose,
	no mating of different connector variants possible
Coding	4 different possibilities, without losing contacts
Mating cycles	min. 750 ¹⁾
Strain relief	min. 100 N
Housing material	Polycarbonate and Polyamide, UL 94 V-0, UV resistant

Push Pull Power 250 V





IP 67 Push Pull connector

for low voltage 48 V

Identification	Part number	Drawing	Dimensions in mm
Connector set inkl. 4 turned crimp contacts (male), insulator body (grey), housing, cable gland	09 46 145 4400	contact no.1	contact no.2
Set of coding pins To avoid accidental incorrect mating a coding system is required. The coding pins are inserted without loss of contacts.	09 46 840 0000	contact no.4	contact no.3
Protective cap IP 65 / 67	09 45 845 0001	41,5 maxi	

Technical characteristics

Specifications	DIN VDE 0627, DIN VDE 0110, DIN EN 61 984
Working voltage	48 V
Working current per contact	12 A @ 55 °C
Rated impulse voltage	1.5 kV (DIN EN 61 984)
Overvoltage category	III (DIN VDE 0110 and IEC 60 664-1)
Pollution degree	3 (DIN VDE 0110 and IEC 60 664-1)
No. of current carrying contacts	4
Pre-leading PE contact	•
Contact resistance	max. 5 mΩ
Protection against contact	acc. to IEC DIN EN 60 529
Wire gauge	1.5 mm² (AWG 16) 1), stranded
Cable sheath diameter	6.9 - 8.6 mm
Protection class – mated	IP 67 / 65 (IEC DIN EN 60 529)
– unmated	IP 20 (IEC DIN EN 60 529)
Vibration and shock resistance	acc. to EN 50 155
Ambient temperature	- 40 + 70 °C
Mating security	Polarisation with polarisation nose,
	no mating of different connector variants possible
Coding	4 different possibilities, without losing contacts
Mating cycles	min. 750 ¹⁾
Strain relief	min. 100 N
Housing material	Polycarbonate and Polyamide, UL 94 V-0, UV resistant

Han® M12 Circular Connectors for Ethernet applications





Technical Data: Circular Connectors shielded, D-coded

	M12 / AWG 22	M12 / AWG 26
Working voltage	max. 50 V AC/DC	max. 50 V AC/DC
Working current per contact	max. 4 A	max. 2 A
Locking	Screw locking M12 x 1mm (recom	. tightening torque 0.6 Nm) self securing
Temperature range	- 20°C +60°C	- 5°C +60°C
Degree of Protection	IP 67	IP 67

Technical Data: System Cabling

	M12 / AWG 22	M12 / AWG 26
Number of wires/ wire gauge	2 x 2 x AWG 22/7	2 x 2 x AWG 26/7
Conductor insulation	Polyethylene (yellow, orange, white, blue) acc. to PROFINET	Polyethylene (white/orange, orange, white/green, green) according to EIA / TIA 568B
Arrangement of insulated strands	7 x 0.25 mm	7 x 0.16 mm
Jacket	Polyurethane (UL/CSA)	Polyurethane (UL/CSA)
Outer diameter	approx. 6.5 mm	approx. 5.6 mm
Bending radius	10 x outer diameter	10 x outer diameter
Temperature range	- 20°C +60°C	- 5°C +60°C

Han® M12 Circular Connectors



System Cabling with Circular Connectors Han® M12 D-coding, pre-assembled on both ends



Identification	11	Part-Number	Drawing			Dimension	s in mm
Pre-assembled and			Cable ty	pe:	Shielded Twisted Pair Stranded wire		
tested system cabli for structured cabling of Industrial Ethernet netwo					M12 D-coding acc. to IEC 61 076-2-101		
based on circular connect M12 D-coding			in accord	ssion properties dance with 11801:2002:	Class D, 10	0% tested	
			Degree	of protection	IP 65 / 67 (v	vhen mated)	
			Pin ar	rangement			
			Signal	Function	Conductor Colour PROFINET	Conductor Colour EIA/TIA 568B	Pin no.
			TD+	Transmission Data+	Yellow	White/Orange	1
			TD-	Transmission Data-	Orange	Orange	3
			RD+	Receiver Data+	White	White/Green	2
			RD-	Receiver Data-	Blue	Green	4
other	gth: 1 m 3 m 5 m r lengths n request	21 03 483 1401 21 03 483 1403 21 03 483 1405	915.3 M12x1	Cable: A	WG 26 / 0.14	l mm²	
other	tors gth: 1 m 3 m 5 m r lengths r request	21 03 485 1401 21 03 485 1403 21 03 485 1405	1.815.3 M12x1	Cable: A	WG 22 / 0.34	l mm²	
112							

Han® M12 Circular Connectors



System Cabling with Circular Connectors Han® M12 D-coding, pre-assembled on one end



Identification	Part-Number	Drawing			Dimension	s in mm
Pre-assembled and tested system cabling		Cable type:		Shielded Twisted Pair Stranded wire		
for structured cabling of Industrial Ethernet networks		Transmission properties in accordance with		M12 D-codi acc. to IEC	ng 61 076-2-101	
based on circular connectors, M12 D-coding				Class D, 10	0% tested	
		Degree	of protection	IP 65 / 67 (v	vhen mated)	
		Pin ar	rangement			
		Signal	Function	Conductor Colour PROFINET	Conductor Colour EIA/TIA 568B	Pin no.
		TD+	Transmission Data+	Yellow	White/Orange	1
		TD-	Transmission Data-	Orange	Orange	3
		RD+	Receiver Data+	White	White/Green	2
		RD-	Receiver Data-	Blue	Green	4
straight version length: 1 m 3 m 5 m other lengths on request	21 03 583 1401 21 03 583 1403 21 03 583 1405					
1 x circular connector M12 D-coding straight version length: 1 m 3 m 5 m other lengths on request	21 03 585 1401 21 03 585 1403 21 03 585 1405					

Han® M12 Panel Feed-Throughs





Identification	Part-Number	Drawing Dimensions in mi
M12 panel feed-through female, D-coding, 50 cm flying lead cable, 4 poles	21 03 371 2403	21,9 500 21,9 9,819
female, D-coding, 4 poles solder terminal, straight version	21 03 371 2402	width across flats 17/ SW17
male, D-coding, 50 cm flying lead cable, 4 poles	21 03 371 1403	5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
male, A-coding, 50 cm flying lead cable, 4 poles	21 03 311 1402	500 22, L
Adaptor M12-RJ45 angled version, 4 poles	21 03 381 4400	21,6 28,9 46,2
Adaptor M12-RJ45 straight version, 4 poles	2103 381 2400	22.6 SWO Width acress Flots 20

Han® M12 Panel Feed-Throughs



Identification	Part-Number	Drawing Dimensions in mm
M12 Panel feed-through for outside assembly female, D-coding, shielded, 360 mm flying lead cable, 4 poles	21 03 383 6407	23.9 Schirmgelegt/ sheelding allocated
M12 Panel feed-through with RJ45 female, D-coding, shielded, 48 mm cable, 4 poles	21 03 683 6401	23,9
M12 Panel feed-through for inside assembly female, D-coding, shielded, 700 mm flying lead cable, 4 poles	21 03 383 6405	SM17/ #10th across flats 17
Cap M12	21 01 000 0003	

microFX





General Description

Fibre optical data transmission system for industrial applications

Optical transceiver for 660 nm and 1300 nm

Passive interface as coupling unit and panel feed-through

Based on M12 hoods and housings in accordance with IEC 61 076-2-101

Suitable for plastic fibre, multimode and singlemode optical fibre

2 supplementary electrical contacts

Degree of protection: IP 65 / IP 67

Large temperature range of -40 °C up to +85 °C

Minimum insertion loss: < 0.3 dB

Technical Data

Mechanical Features

Storage temperature $-40^{\circ}\text{C} \dots +85^{\circ}\text{C}$ Working temperature $-25^{\circ}\text{C} \dots +85^{\circ}\text{C}$ Degree of protection IP 65 / 67 Tightening torque 50 ... 60 Ncm

Electrical Data

Rated voltage of electrical contacts 60 V DC Rated current 4 A max.

Optical Data Transceiver for Multimode

Center wave length (λ_c) 1270 nm up to 1380 nm

Output optical power max. (P_0) -14 dBm Input optical power min. (P_{SAT}) -31 dBm Data transmission rate 125 Mbit/s

in accordance with Fast Ethernet 100Base FX; IEE 802.3u

Optical Data Transceiver for Singlemode

Center wave length (λ_c) 1270 nm up to 1340 nm

Output optical power max. (P_0) -8 dBm Input optical power min. (P_{SAT}) -31 dBm Data transmission rate 125 Mbit/s

in accordance with Fast Ethernet 100Base FX; IEE 802.3u

microFX



Identification Part-Number Drawing Dimensions in mm View mating side Transceiver 20 50 004 3411 for multimode with 1300 nm Panel cut out 20 50 004 3412 Ø 16.3 mm for singlemode with 1300 nm for POF with 650nm on request 23 025 Contact Function Description Receiver supply voltage 3.3 V Receiver data output, noninverted, PECL 2 Receiver data output, inverted, PECL 3 RX-GND SD Ground (Receiver) Signal Defect, PECL 4 Receiver signal strength indica-tor output, analog voltage RSSI 6 Reserved for future use 9 10 Ground (Transmitter) Transmitter data input, inverted, PECL 11 GND 12 TX-Transmitter data input, noninver ted, PECL 13 VCCTX Transmitter supply voltage 3.3 V 14 Connector 20 10 004 3411 View Contacts order separately mating side maxi 64.85 max **Optical Contacts** 29.10 maxi 20 10 125 3411 Multimode 125 20 10 009 3411 Singlemode POF on request on request HCS® HCS (=Hard Clad Silica) is a registered trade mark of SpecTran Corporation **Electrical Contacts** 20 10 000 3411

*micro*FX



Identification	Part-Number	Drawing	Dimensions in mm
Panel feed-through	20 80 004 3411	20.5 maxi	View mating side
Adapter	20 80 004 3412	20.5 maxi	View mating side
Jumper	on request		

HARTING Product range





Industrial connectors Han®



Fibre Optic Data Link Systems (F.O.)

Subsidiary companies worldwide

HARTING

Austria: HARTING Ges. m. b. H. Deutschstraße 3, A-1230 Wien Phone +431/6162121, Fax +431/6162121-21 E-Mail: at@HARTING.com

Belgium: HARTING N.V./S.A. Doornveld 8, B-1731 Zellik Phone +322/4660190, Fax +322/4667855 E-Mail: be@HARTING.com

Ermail: Degrindrings.com Brazil: HARTING Ltda. Av. Dr. Lino de Moraes, Pq. Jabaquara, 255 CEP 04360-001 - São Paulo - SP - Brazil Phone +5511/5035-0073, Fax +5511/5034-4743 E-Mail: br@HARTING.com, Internet: www.HARTING.com.br

China: Zhuhai HARTING, Limited Shanghai branch Comma. Zituliar HAN TING, Lillined Shanghar branch Room 5403, 300 Huaihai Zhong Road Hong Kong New World Tower, Luwan District, P.R.C Shanghai 200021, China Phone +86 21 - 63 86 22 00, Fax +86 21 - 63 86 86 36 E-Mail: cn@HARTING.com

Czech Republic: HARTING spol. s.r.o., Mlýnská 2, 16000 Praha 6 Phone +420 220 380 460, Fax +420 220 380 461 E-Mail: cz@HARTING.com, Internet: www.HARTING.cz

E-Mail: c2@HARTING.com, mcc. Finland: HARTING Oy Hakamäenkuja 11 A, FIN-01510 Vantaa Phone +358 9 350 873 00, Fax +358 9 350 873 20 E-Mail: fi@HARTING.com

France: HARTING France France: HARTING France 181 avenue des Nations, Paris Nord 2 BP 66058 Tremblay en France F-95972 Roissy Charles de Gaulle Cédex Phone +33149838400, Fax +33148632306 E-Mail: fr@HARTING.com

E-Mail: fr@HARTING.com

Germany: HARTING Deutschland GmbH & Co. KG
Postfach Z451 · D-32381 Minden
Simeonscarré 1 · D-32427 Minden
Phone (0571) 8896-0, Fax (0571) 8896-282
E-Mail: de@HARTING.com, Internet: www.HARTING.com

Office Germany: HARTING Deutschland GmbH & Co. KG
Blankenauer Straße 99, D-09113 Chemitz
Phone +49 0371 429211, Fax +49 0371 429222
E-Mail: de@HARTING.com

E-Mail: de@HARTING.com

Great Britain: HARTING Ltd.
Caswell Road, Brackmills Industrial Estate
GB-Northampton, NN4 7PW
Phone +441604/766686, 827500, Fax +441604/706777,
E-Mail: gb@HARTING.com, Internet: www.HARTING.co.uk

Hong Kong: HARTING (HK) Limited, Regional Office Asia Pacific
4208 Metroplaza Tower 1, 223 Hing Fong Road
Kwai Fong, N. T., Hong Kong
Phone +852/2423-7338, Fax +852/2480-4378
E-Mail: ap@HARTING.com, Internet: www.HARTING.com.hk

Hungary: HARTING Fastern Europe GmbH

Hungary: HARTING Eastern Europe GmbH Hungary: HARTING Eastern Europe GmbH Magyarországi Kereskedelmi Képviselete, 1119 Budapest Fehérvári út 89-95, II. emelet 217/A. Phone +36-1-205 3464, Fax +361-1-205 3465 E-Mail: hu@HARTING.com, Internet: www.HARTING.hu

E-Mail: nu@HARTING.com, Internet: www.HARTING.nu India: HARTING India Private Limited No. D, 4th Floor, 'Doshi Towers', No. 156 Poonamallee High Road, Kilpauk, Chennai 600 010, 'Tamil Nadu, Chennai Phone +91 (44) 52611552, Fax +91 (44) 26223316 E-Mail: in@HARTING.com, Internet: www.HARTING.com

Italy: HARTING SpA Via Dell' Industria 7, I-20090 Vimodrone (Milano), Phone +3902/250801, Fax +3902/2650597, E-Mail: ti@HARTING.com



Fieldbus components, sensor-/actor components, Han-InduNet® cabling system



Network components for industrial communication

Japan: HARTING K. K. Yusen Shin-Yokohama 1 Chome Bldg., 2F, 1-7-9, Shin-Yokohama Kohoku-ku, Yokohama, 222-0033 Japan Phone +81 45 476 3456, Fax +81 45 476 3466 E-Mail: jp@HARTING.com, Internet: www.HARTING.co.jp

Korea: HARTING Korea Limited #308 Leaders Bldg., 342-1, Yatap-dong, Bundang-gu, Sungnam-City, Kyunggi-do, 463-828, Korea Phone +82-31-781-4616, Fax +82-31-781-4616 E-Mail: kr@HARTING.com

Netherlands: HARTING B.V. Larenweg 44, NL-5234 KA 's-Hertogenbosch Postbus 3526, NL-5203 DM 's-Hertogenbosch Phone +3173/6410404, Fax +3173/6440699 E-Mail: nl@HARTING.com

Norway: HARTING A/S, Østensjøveien 36, N-0667 Oslo, Phone +4722/700555, Fax +4722/700570 E-Mail: no@HARTING.com

Poland: HARTING Eastern Europe GmbH Przedstawicielstwo w Polsce, ul. Kamiejuskiego 201-219 51-126 Wroclaw Phone +48 71-352 81 71 , Phone +48 71-352 81 74 Fax +48 71-320 74 44 E-Mail: pl@HARTING.com, Internet: www.HARTING.pl

Portugal: HARTING Iberia, S. A. Avda. Josep Tarradellas, 20-30, 4º 6ª, E-08029 Barcelona Phone +351.219.673.177, Fax +351.219.678.457 E-Mail: es@HARTING.com

Russia: HARTING ZAO ul. Tobolskaja 12, Saint Petersburg, 194044 Russia Phone +7/812/3276477, Fax +7/812/3276478 E-Mail: ru@HARTING.com, Internet: www.HARTING.ru

Singapore: HARTING Singapore Pte Ltd. No. 1 Coleman Street, #B1-21 The Adelphi, Singapore 179803 Phone +6562255285, Fax +6562259947 E-Mail: sg@HARTING.com

Spain: HARTING Iberia S.A. Josep Tarradellas 20-30 4º 6ª, E-08029 Barcelona Phone +34 933 638 475, Fax +34 934 199 585 E-Mail: es @ HARTING.com

Sweden: HARTING AB Gustavslundsvägen 141 B 4tr, 167 51 Bromma Phone +468/4457171, Fax +468/4457170 E-Mail: se@HARTING.com

Switzerland: HARTING AG Industriestrasse 26, CH-8604 Volketswil Phone +41 44 908 20 60, Fax +41 44 908 20 69 E-Mail: ch@HARTING.com

Taiwan: HARTING R.O.C. Limited Room 6, 10 Floor, No. 171, Sung-Te-Road, Taipei, 110 Taiwan Phone +886-2-2346-3177, Fax +886-2-2346-2690 E-Mail: tw@HARTING.com

USA: HARTING Inc. of North America USA: HAKTING Inc. of North America 1370 Bowes Road, Elgin, Illinois 60123 Phone +1 (877) 741-1500 (toll free) Fax +1 (866) 278-0307 (Inside Sales) Fax +1 (847) 717-9430 (Sales and Marketing) E-Mail: us@HARTING.com, Internet: www.HARTING-USA.com

Eastern-Europe: HARTING Eastern Europe GmbH Bamberger Straße 7, D-01187 Dresden Phone +49 351 / 4361760, Fax +49 351 / 4361770 E-Mail: Eastern.Europe@HARTING.com

Other countries: Please contact your Global Business Unit



People | Power | Partnership

Representatives – worldwide



Argentina:

Argentina.
Condel Electronica
Julian Agüero 3355
(1605) Munro, Pcia. de Buenos Aires
Phone + Fax +54114762.0118
E-Mail: mediavicondel@arnet.com.ar Roberto Mediavilla Rivera Indarte 390, (5000) Córdoba Phone +54 351 425-0567 Fax +54 351 421-2282 E-Mail: rmediavilla@arnet.com.ar

Australia: ADILAM Electronics Pty. Ltd. 14 Nicole Close, North Bayswater, 3153 Victoria Phone +61 3 9737 4900, Fax +61 3 9737 4999 E-Mail: mark.c@adilam.com.au, Internet: www.adilam.com.au

Bulgaria: COMET ELECTRONICS 16, Tsar Samuil Str., BG-1000 Sofia Phone +359-2-9155800, Fax +359-2-9540384 E-Mail: office @comet.bg, Internet: www.comet.bg

Denmark: Knud Wexøe A/S Skaettekaeret 11, P.O. Box 152, DK-2840 Holte Phone +4545465800, Fax +4545465801 E-Mail: wexoe@wexoe.dk, Internet: www.wexoe.dk

Estland: SKS-tehnika Ou Mustamäe tee 55, EE-10621 Tallinn Phone +372 6819 234, Fax +372 6819 235 E-Mail: peeter.kuus@sks.fi

Finland: SKS-automaatio OY Martinkyläntie 50, FIN-01721 Vantaa Phone +3589852661, Fax +35898526820 E-Mail: automaatio@sks.fi

Hungary: Mile Kft. Mádi u. 52, H-1104 Budapest Phone +36-1-431-9800, Fax +36-1-431-9817 E-Mail: milekft@mile-kft.hu, Internet: www.mile-kft.hu

Island: Smith & Norland Nóatún 4, IS - 105 Reykjavík Phone +354 520 3000, Fax +354 520 3011 E-Mail: olaf@sminor.is, Internet: www.sminor.is

Israel: MIGVAN Technologies & Engineering Ltd. 13 Hashiloh St., P.O.Box 7022, IL - Petach Tikva 49170 Phone +972 3 9240784, Fax +972 3 9240787 E-Mail: info@mte.co.il, Internet: www.mte.co.il

Poland: Soyter Sp. z o. o. ul. Warszawsa - Stare Babice Phone +48 22 722 0 685, Fax. +48 22 722 0 550 E-Mail: handlowy@soyter.com.pl, Internet: www.soyter.com

South-Africa: HellermannTyton Pty Ltd., Private Bag X158 Rivonia 2128, 34 Milky Way Avenue Linbro Business Park 2065, Johannesburg, South Africa Phone +27(0)11879-6600, Fax +27(0)11879-6606 E-Mail: sales.jhb@hellermann.co.za

Turkey: Gökhan Elektrik San. Tic. Ltd. Sti.
Perpa Elektrikçiler Is Merkezi A Blok
Kat.7-8-9 No.694, TR - 80270 Okmeydani/Istanbul
Phone +90(212) 2213236 (pbx), Fax +90(212) 2213240
E-Mail: gokhan@gokhanelektrik.com.tr
Internet: www.gokhanelektrik.com

Ukraine: Incomtech I td. A Lermontovskaya St., UA-04050 Kiev Phone +380-44-213-3641, Fax +380-44-213-3814 E-Mail: eletech@incomtech.com.ua Internet: www.incomtech.com.ua

Production Plants



China · Germany · Great Britain · Romania · Switzerland

Global Business Unit Electric



HARTING Electric GmbH & Co. KG P.O. Box 1473, D-32328 Espelkamp Phone +49 5772/47-97100, Fax +49 5772/47-495 E-Mail: HARTING.electric@HARTING.com Internet: http://www.HARTING.com